



KINEMATICA

Homogenizing perfected.



MICROTRON®

LABORATORY LINE

MICROTRON® MB 550 and MB 800

Laboratory mixer, homogenizing and mixing technology for cuttable, dry or liquid samples

MICROTRON[®] MB 550 and MB 800

Laboratory mixer.

Analysis and quality control requires equipment that is flexible for preparing samples and easy to work with. These mixers are well suited for intense mixing, dispersing, homogenizing, emulsifying and mincing operations for cuttable materials. Simple handling, high user safety and efficiency are just a few advantages offered by these mixers.

PROCESSING VOLUMES

The robust design allows for high stability and a long service life, even when using high rotational speeds. There are four different attachments for the MB 550 with the volumes 125 ml, 250 ml, 500 ml and 1000 ml. Larger volumes up to 2 or 4 liters can be processed with the M800 and the associated stainless steel mixing cups.

SAFETY SYSTEM

The safety system prevents uncontrolled operation. Both models can only be operated with properly attached protective covers (MB550) or with a lid (MB800). If stones or similar materials are accidentally mixed, the user will be protected by a Plexiglas protection cover (MB550).

Both devices comply with CE regulations for industrial machines.



After unscrewing the blade unit, the borosilicate glass sample container can be used in its full functionality for other analysis purposes or for sample storage.

ERGONOMICS

- Smooth rotational speed adjustment with integrated on- and off switch
- Load compensated rotational speed adjustment
- Switching of mixing attachment and protection cover without tools
- Operation only possible with security cover and lid in place
- Variety of sample container designs
- Vibration dampening quick coupling
- Very quiet motor with integrated ventilation cooling
- Integrated load, heat and blockage protection

RESULTS ARE CRUCIAL

- Production of very fine particle sizes in both liquid and dry mediums: precise analyses require homogeneous samples
- Efficient sample preparation: through high rotational speeds
- Flexibility: various sample volumes with different mixing attachments
- Handling: mounting of mixing attachment and protection cover without tools
- Durability a Swiss virtue





TECHNICAL INFORMATION

Working volumes	MB 550: 125, 250, 500, 1000 ml MB 800: 2000 or 4000 ml
Motor	Collector motor (Class H) Gearless direct drive Security system auto-off
Drive power	MB 550: 550 Watt MB 800: 800 Watt
Speed range	MB 550: 1000 to 14 000 rpm MB 800: 1000 to 14 000 rpm
Sound level	MB 550: ca. 72 dB(A) at 14 000 rpm MB 800: ca. 79 dB(A) at 14 000 rpm
Supply voltage	230 V ± 10 %, 50Hz / 60Hz 120 V ± 10 %, 60Hz
Maximum relative humidity	80 % in storage 80 % during operation
Operating temperature	0 – 40 °C
Protection Class according to DIN	IP 20
Drive dimensions (H/ø)	MB 550: 245 mm / ø 190 mm MB 800: 245 mm / ø 190 mm
Weight	MB 550: 4,4 kg MB 800: 5,3 kg
Standard EMC	EN 60335-1:1988, EN 60335-2-64:1993, EN 55014:1993, EN 55104:1995, EN 61000-3-2:1995, EN 61000-3-3:1995, EN 60335-2-64:1997
Safety norm	Protection Class 1 according to EN 60335-1



USERS / APPLICATION RANGES

- Mixing, dispersing, homogenizing, emulsifying with liquids
- Mixing of cuttable materials
- Sample preparation for content analysis in quality control and/or quality assurance
- Prevention of excessive aeration due to closed system (MB 550)
- Pollutant analysis (e.g. foodstuffs)

This list provides a small selection of possible applications.

Mixing attachments and blade heads.

Your requirements are our standard.

The solution for processing of your cuttable materials. You have diverse vessels to choose from. The integrated safety system prevents start-up in open condition.



BOROSILICATE GLASS MIXING ATTACHMENTS AND PROTECTION COVERS (MICROTRON® MB 550)

Mixing attachments

After sample preparation the mixing attachments from heat resistant borosilicate glass MBA 125 to MBA 1000 can be used for further laboratory tasks without the need to transfer contents. The vessels are simply screwed to the blade head with a glass thread and spacer ring.

Protection cover

The protection covers are for the various MBA mixing attachments. For safety reasons, it is not possible to start the MB 550 mixer without a protection cover. The 5mm thick Plexiglas cover also protects the operator in case of glass breakage when stones or similar solid materials are accidentally mixed.

These mixing attachments and protection covers can only be used with the MB 550.



MIXING ATTACHMENTS OF STAINLESS STEEL (MICROTRON® MB 800)

Mixing attachments

MBA 2000 and MBA 4000, made of stainless steel, allow processing of larger amounts. Due to safety reasons, it is not possible to start the machine when the lid is open or open the machine when it is running. Additional sample material can be added during operation only via the integrated opening in the lid.

The blade head can be easily unscrewed for cleaning purposes.

These mixing attachments can only be used with the MB 800.



HIGH-PERFORMANCE STAINLESS STEEL CUTTING BLADE ASSEMBLY (MICROTRON® MB 550 AND MB 800)

The cutting blade assembly

The six polished premium steel rotor blades have been optimized for intense and quick processing for all types of samples. All parts that touch the product are made from stainless steel and can be easily detached and cleaned. Integrated stainless steel ball bearings ensure ease of movement and a perfectly true run. Power transmission occurs via a rubber cushioned plug coupling.

Gaskets

The standard gaskets are made from NBR material. Upon request, gaskets from EPDM, or viton are also available.

Order information and accessories.

Authorized extension of your system.

The laboratory mixers MB 550 and MB 800 can be expanded with functional accessories according to your wishes and requirements. Our experts will gladly assist you if you have any application related questions.

LABORATORY MIXER

Sales No.	Product	Description
MICROTRON® MB 550 without mixing attachment and protective cover		
36010005	MB 550, 230 V	EU-power cable
36010006	MB 550, 230 V	CH-power cable
36010007	MB 550, 230 V	UK-power cable
36010010	MB 550, 100 - 120 V	Power cable
MICROTRON® MB 800 without mixing attachment		
36010003	MB 800, 230 V	EU-power cable
36010011	MB 800, 230 V	CH-power cable
36010012	MB 800, 230 V	UK-power cable
36010004	MB 800, 100 - 120 V	Power cable



MIXING ATTACHMENTS (MICROTRON® MB 550)

Mixing attachments MBA 125 to MBA 1000 consist of borosilicate glass, gasket and blade head.

Sales No.	Product	Description
36050005	MBA 125	Working volumes: 125 ml
36050010	MBA 250	Working volumes: 250 ml
36050015	MBA 500	Working volumes: 500 ml
36050020	MBA 1000	Working volumes: 1000 ml



PROTECTIVE COVERS (MICROTRON® MB 550)

Plexiglass protection glass is absolutely required when using MBA mixing attachment.

Sales No.	Product	Description
36050025	MBH 125	Height: 86 mm
36050030	MBH 250	Height: 128 mm
36050035	MBH 500	Height: 149 mm
36050040	MBH 1000	Height: 228 mm



LABORATORY MIXER (MICROTRON® MB 800)

Mixing attachment consists of stainless steel, gasket and blade head as well as lid with opening for material addition.


Sales No.	Product	Description
36050050	MBA 2000	Working volumes: 2000 ml
36050055	MBA 4000	Working volumes: 4000 ml



Users / application ranges.

Best solution for every application.

Since 1962 we are a leading supplier of dispersing solutions for applications in the chemical, biotechnology, pharmaceutical, cosmetics and food industries. Due to our close relationships with our customers we detect new trends early and we always look for ways to find an ideal solution for you.





Our mission. Your solution.

Homogenizing perfected: for every industry.

Kinematica's broad portfolio of solutions can address almost every dispersing application for the pharmaceutical, cosmetic, chemical, food, and biotech industry. Innovative powder-induction systems, solutions for completely sterile environments, or fully-compliant ATEX architecture are just some examples of the broad portfolio that Kinematica can offer with true scalability from pilot-plant to large plant configurations.

Our state-of-the-art technology, in addition to a professional consulting and engineering suite of services, can address a variety of processes such as blending / mixing / stirring, emulsifying, deagglomerating, foaming, crushing, and homogenizing with particle size reduction from a few micrometers down to nanometers in size: the proprietary design and innovative geometry of our aggregates / generators can downsize and provide perfect statistical particle distribution for the finest emulsions / suspensions and foam dispersions.



PHARMA



CHEMICAL



COSMETICS



FOOD



LIFE SCIENCE



HEADQUARTERS

Kinematica AG

Luzernerstrasse 147a
CH-6014 Luzern
Switzerland

Phone +41 41 259 65 65

Fax +41 41 259 65 75

info@kinematica.ch

kinematica.ch

EUROPE

Kinematica GmbH / Germany / Phone +49 7634 504 800 0 / info@kinematica.de

-

NORTH AND SOUTH AMERICA

Kinematica, Inc. / USA / Phone +1 631 750 6653 / info@kinematica-inc.com

-

RUSSIA AND CIS

Kinematica AG / Switzerland / Phone +41 41 259 65 65 / info@kinematica.ch

-

GREATER CHINA

Kinematica Asia Limited / Hong Kong / Phone +852 249 769 65 / info@kinematica.ch