

# Safety Data Sheet

according to Regulations 1907/2006/EC (REACH) and 2015/830/EU

REF: 931220	VISOCOLOR ECO Chromium (VI), refill pack	Page: 1/9
Printing date: 12.05.2021	Date of issue: 11.09.2018	

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1 Product identifier

REF 931220  
 Product name VISOCOLOR ECO Chromium (VI), refill pack  
 REACH Registration number(s): see SECTION 3.1/3.2 or  
 A registration number for the substance(s) does not exist because the annual tonnage does not require registration or the substance or its use is excluded from registration.  
 1 x 30 mL Cr-1  
 1 x 25 mL Cr-2

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

**Relevant identified uses**  
 Product for analytical use.  
 Exposure Scenario Classification according REACH, RIP 3.2 Codes: SU 0-2, PC 21, PROC 15, AC 0  
 The exposure scenario is integrated into sections 1-16.  
**Uses advised against**  
 not described

### 1.3 Details of the supplier of the safety data sheet

**Manufactured by:**  
 MACHEREY-NAGEL GmbH & Co. KG  
 Valenciener Str. 11, 52355 Düren, GERMANY  
 Tel.: +49 2421 969 0  
 E-mail: sds@mn-net.com (msds@mn-net.com)

### 1.4 Emergency telephone number

Outside Germany (DE): Call your regional Poisons Information Service or call local Life Saving Service.  
 DE: Gemeinsames Giftinformationszentrum (GGIZ) 99089 Erfurt tel. +49 361 730 730

You find our current versions of SDS (22 languages) in Internet: <http://www.mn-net.com/SDS>

## SECTION 2: Hazard identification

### 2.0 Classification of the complete product



GHS05 GHS07

Signal word DANGER

Hazard identification	Hazard classes/categories
H290	Met. Corr. 1
H302	Acute Tox. 4 oral
H314	Skin Corr. 1B

### 2.1 Classification of the substance or mixture

30 mL Cr-1



GHS05 GHS07

# Safety Data Sheet

according to Regulations 1907/2006/EC (REACH) and 2015/830/EU

REF: 931220	VISOCOLOR ECO Chromium (VI), refill pack	Page: 2/9
Printing date: 12.05.2021	Date of issue: 11.09.2018	

Signal word	DANGER
<b>Hazard identification</b>	<b>Hazard classes/categories</b>
H290	Met. Corr. 1
H302	Acute Tox. 4 oral
H314	Skin Corr. 1B

**25 mL Cr-2**

Signal word	Do not need labelling as hazardous
No hazard class	-

## 2.2 Label elements

According **CLP directive** inner packages must be only labelled with GHS symbol(s) and product identifier(s) (EU 1272/2008 Annex I - 1.5.1.2).

Harmful chemicals/mixtures with signal word: **WARNING** must not be labelled with H and P phrases **until 125 mL** (EU 1272/2008 Annex I - 1.5.2).

Metal corrosive solutions **do not have to** be labelled with GHS symbol, signal word, H and P phrases **until 125 mL** (EU 1272/2008 Annex I - 1.5.2.1.3).

**30 mL Cr-1**



GHS05 GHS07

Signal word: DANGER

H314  
Causes severe skin burns and eye damage.

P260sh, P280sh, P303+361+353, P305+351+338, P310  
Do not breathe dust/vapours. Wear protective gloves/eye protection. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower]. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/doctor.

**25 mL Cr-2**

Do not need labelling as hazardous  
Signal word: -

## 2.3 Other hazards

**Possible hazards from physicochemical properties**  
Generally in the case of pH values are less than 2 or higher than 11.5 then it is corrosive. ---

**Information pertaining to particular risks to human and possible symptoms**  
Causes varying degrees of acid burns on the skin, to the eyes and to the mucous membranes and wounds which do not heal quickly depending on the concentration, temperature and the exposure time. Vapours especially which steam from hot liquids and mist can have a severe irritant effect upon the eyes and the respiratory organs.  
Cause after oral intake, impairments of health when ingested in small quantities. -

**Information pertaining to particular risks to the environment**  
Avoid contact of substance/mixture to environment.

**PBT:** not applicable  
**vPvB:** not applicable

**Other hazards**  
---

# Safety Data Sheet

according to Regulations 1907/2006/EC (REACH) and 2015/830/EU

REF: 931220

VISOCOLOR ECO Chromium (VI), refill pack

Page: 3/9

Printing date: 12.05.2021

Date of issue: 11.09.2018

## SECTION 3: Composition/information on ingredients

### 3.1 Substances or 3.2 Mixtures

#### 30 mL Cr-1

Chemical: *o*-phosphoric acid CAS No.: 7664-38-2  
 Classification: H290, Met. Corr. 1, H302, Acute Tox. 4 oral, H314, Skin Corr. 1B  
 Formula: H<sub>3</sub>PO<sub>4</sub> • H<sub>2</sub>O  
 Pseudonym: orthophosphoric acid  
 TSCA Inventory: listed  
 REACH Reg. No.: 01-2119485924-24-xxxx  
 EC No.: 231-633-2 Indice No.: 015-011-00-6  
 RTECS: TB6300000  
 KE No.: KE-27427  
 Concentration: 55 - <70 %  
 acc. CLP (GHS): H290, Met. Corr. 1, H302, Acute Tox. 4 oral, H314, Skin Corr. 1B

#### 25 mL Cr-2

Chemical: *1,5-diphenylcarbazide* CAS No.: 140-22-7  
 Classification: No criteria for classification or naming of chemical not required.  
 Formula: C<sub>13</sub>H<sub>14</sub>N<sub>4</sub>O  
 Pseudonym: 2,2'-diphenyl-carbonic dihydrazide  
 TSCA Inventory: listed  
 REACH Reg. No.: not necessary, amount <1 t/a  
 EC No.: 205-403-7  
 RTECS: FF2750000 MFCD: 00003013  
 Concentration: < 0.10 %  
 acc. CLP (GHS): The criteria for classification are not fulfilled.

Chemical: *dimethyl sulfoxide* CAS No.: 67-68-5  
 Classification: No criteria for classification or naming of chemical not required.  
 Formula: C<sub>2</sub>H<sub>6</sub>OS  
 Pseudonym: DMSO, 1,1'-sulfinylbis-methane  
 TSCA Inventory: listed  
 REACH Reg. No.: 01-2119431362-50-xxxx  
 EC No.: 200-664-3  
 RTECS: PV6210000 MFCD: 00002089  
 KE No.: KE-32367  
 Concentration: 80 - <100 %  
 acc. CLP (GHS): The criteria for classification are not fulfilled.

### 3.3 Remarks

When not listed, mixtures are added with water [CAS No. 7732-18-5] to 100%.

List of H and P phrases: see section 16.1

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

Place insured person out of danger zone to fresh air immediately. Ensure quiet, warmth, and provide resuscitation if necessary. If necessary contact medical advice. Remove contaminated clothing. Show product package, packing insert and this material safety data sheet to the doctor.

#### 4.1.1 After SKIN Contact

Remove contaminated clothing immediately. Rinse the affected skin or mucous membrane thoroughly for min. 15 minutes under running water. (If possible) use soap. Avoid neutralisation. Then apply a loose bandage.

#### 4.1.2 After EYE Contact

After contact with the eyes rinse thoroughly under running water with the eyelid wide open for min. 10 minutes with eye washing bottle, eye douche or running water (protect intact eye). Before (if possible) apply eye drops Proxymetacaine 0.5%, if the opening the eyelid convulsion is painful. Further treatment to be carried out by an eye specialist.

#### 4.1.3 After INHALATION of vapours

After inhalation of foam or vapour fresh air should be inhaled. Keep airways free. If vomiting and if insensible place patient in recovery position and keep airways free. ---

# Safety Data Sheet

according to Regulations 1907/2006/EC (REACH) and 2015/830/EU

REF: 931220

VISOCOLOR ECO Chromium (VI), refill pack

Page: 4/9

Printing date: 12.05.2021

Date of issue: 11.09.2018

- 4.1.4 After ORAL Intake**  
After oral intake lots of water with activated charcoal supplement should be drunk after it has been ingested. Do not induce vomiting under any circumstances. Do not make any efforts to neutralise it. Contact medical advice for possible consequences. ---
- 4.2 Most important symptoms and effects, both acute and delayed**  
---
- 4.3 Indication of any immediate medical attention and special treatment needed**  
CORROSIVE DAMAGE: After SKIN CONTACT rinse with water for a long time. Efforts to neutralise the substance can frequently make matters worse. Apply glucocorticosteroides following inflammatory reactions. After EYE CONTACT rinse immediately with plenty of water for a long time. Eyelid convulsion measures. Name the corrosive chemical. Further treatment must be carried out by an eye specialist. After INTAKE administer aluminium oxide drug suspensions. Administer a prophylaxis to counter pulmonary oedema following the INGESTION of corrosive aerosols. In the event of RESPIRATORY DISTRESSES ensure that the patient inhales oxygen. ---

## SECTION 5: Firefighting measures

- 5.1 Extinguishing media**  
Fire extinguishers appropriate to the fire classification, and, if applicable, a fire blanket must be available in a prominent location in the work area. All extinguishers like FOAM, WATER SPRAY, DRY POWDER, CARBON DIOXIDE can be used.
- 5.2 Special hazards arising from the substance or mixture**  
Formation of hazardous and caustic vapour-air mixtures possible. ---
- 5.3 Advice for firefighters**  
No, for listed product. Product package burns like paper or plastic. Spray any vapours released with water. Retent fire water. Use only acid-resistant safety equipment.  
For great amount - if necessary - protective breathing apparatus which is independent of the ambient air (isolated equipment), and sealed protective clothing is necessary in the event of a large-scale formation of toxic substances.
- 5.4 Additional information**  
Danger for environment **only in the event of a large-scale leakage** or formation of hazardous substances. ---

## SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures**  
Do not breathe vapours. Wear suitable protective gloves (see 8.2.2). Wear eye protection, respectively face protection. Regular staff training is necessary, indicating hazards and precautions on the basis of operating instructions. Restrictions on activity must be observed.
- 6.2 Environmental precautions**  
not necessary
- 6.3 Methods and material for containment and cleaning up**  
Bind any escaping liquid with inert absorbent. And dispose in accordance to local regulations for the disposal of hazardous chemicals. Clean any contaminated equipment and floors with plenty of water. Collect small amounts of leaked liquid and flush with water into drains.
- 6.4 Reference to other sections**  
see information in section 5.4 ---

## SECTION 7: Handling and storage

- 7.1 Precautions for safe handling**  
Handling in accordance with the test instruction, that comes with the product.
- 7.2 Conditions for safe storage, including any incompatibilities**  
The original product package of MACHEREY-NAGEL allows a safe storage.  
Storage class (VCI): 8B  
Water hazard class (DE): 2
- 7.2.1 Requirements for stock rooms and containers**  
Keep original product packages tightly closed during handling and storage. Use inbreakable container for transport of glass bottles.
- 7.3 Specific end use(s)**  
Product for analytical use.

# Safety Data Sheet

according to Regulations 1907/2006/EC (REACH) and 2015/830/EU

REF: 931220

VISOCOLOR ECO Chromium (VI), refill pack

Page: 5/9

Printing date: 12.05.2021

Date of issue: 11.09.2018

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### 30 mL Cr-1

Chemical: *o*-phosphoric acid

CAS No.: 7664-38-2

DNEL: 2.92 mg/m<sup>3</sup>  
DNEL = Derived No-Effect Level (for workers)

EU value: [TWA] 1 / [STEL] 2 mg/m<sup>3</sup>  
 TRGS 900 (DE): [8h] 1 / [15min] 2 mg/m<sup>3</sup>  
E/e respirable

Short-term exposure factor: 2 (I), Y  
skin resorptive (H), respiratory sensitizable (Sa), skin sensitizable (Sh), teratogenic (Z) not securely excluded / (Y) certainly excluded

SUVA(CH) MAK value: 1 mg/m<sup>3</sup>

NIOSH: TWA 1 / ST 3 mg/m<sup>3</sup>

NIOSH STEL: 3 mg/m<sup>3</sup>

[TWA] Time-weighted average to a reference period of 8 hours, [STEL] Short-term exposure limit related to a 15-minute period

OSHA: TWA 1 mg/m<sup>3</sup>

#### 25 mL Cr-2

Chemical: 1,5-diphenylcarbazide

CAS No.: 140-22-7

Chemical: dimethyl sulfoxide

CAS No.: 67-68-5

DNEL: 394<sub>inh</sub> mg/m<sup>3</sup>  
DNEL = Derived No-Effect Level (for workers)

PNEC<sub>(fresh water)</sub>: 17 mg/L  
PNEC = Predicted No Effect Concentration

TRGS 900 (DE): 50 ppm / 160 mg/m<sup>3</sup>  
E/e respirable

Short-term exposure factor: 2 (I), H, Z  
skin resorptive (H), respiratory sensitizable (Sa), skin sensitizable (Sh), teratogenic (Z) not securely excluded / (Y) certainly excluded

SUVA(CH) MAK value: 50 ppm / 160 mg/m<sup>3</sup>

### 8.2 Exposure controls

Good ventilation and extraction system in the room, floor resistant to chemicals with floor drainage and washing facilities. The highest level of cleanliness must be maintained at the workplace.

#### 8.2.1 Respiratory protection

No additional recommendations.

#### 8.2.2 Hand protection

Yes, gloves according EN 374 (permeation time >30 min - level 2), consist of PVC, natural latex, Neopren, or Nitril (f.ex. from Ansell or KCL). Use for short times chemical resistant latex gloves with code EN 374-3 level 1.

#### 8.2.3 Eye protection

Yes, safety glasses according EN 166 with integrated side shields or wrap-around protection or face protection.

#### 8.2.4 Skin protection

Recommended to avoid clothing damage, and to avoid contamination with these hazards.

#### 8.2.5 Personal hygiene

Eating, drinking, smoking, taking snuff and storage of food in work areas and at outdoor workplaces is prohibited. Avoid contact with the skin, eyes and clothing. Rinse any clothing on which the substance has been spilled, and soak it in water. Wash hands thoroughly with soap and water when stopping work and before eating, and then apply protective skin cream.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

#### 30 mL Cr-1

Appearance: liquid	Colour: colourless	Odor: odorless
pH: 2		
Specific gravity: 1,50 g/cm <sup>3</sup>		
Solubility in water: 0-100 %		

#### 25 mL Cr-2

Appearance: liquid	Colour: rose	Odor: organic
--------------------	--------------	---------------

# Safety Data Sheet

according to Regulations 1907/2006/EC (REACH) and 2015/830/EU

REF: 931220

VISOCOLOR ECO Chromium (VI), refill pack

Page: 6/9

Printing date: 12.05.2021

Date of issue: 11.09.2018

pH:	7
Flash point:	95 °C
Specific gravity:	1,1 g/cm <sup>3</sup>
Solubility in water:	0-100 %

## 9.2 Other information

Data for the other parameters of the mixtures are not available, because no registration and no chemical safety report is required.  
**Relevant Properties of Substance Group**

---

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

no further data available.

### 10.2 Chemical stability

No known instability.

### 10.3 Possibility of hazardous reactions

Can react violently with organic material. No further data available.

### 10.4 Conditions to avoid

Not necessary. ---

### 10.5 Incompatible materials

Avoid contact with strong acids or alkalines.

### 10.6 Hazardous decomposition products

In the original package all parts/all reagents are safety and separated stored. Decompositions are not observed during the expiration period under recommended conditions.

## SECTION 11: Toxicological information

### 11.1 Information on toxicological effects

Following information is valid for pure substances. Quantitative data on the toxicity of this product are not available.

#### 30 mL Cr-1

Chemical:	<i>o</i> -phosphoric acid	CAS No.: 7664-38-2
TSCA Inventory:	listed	California Proposition 65 List: not listed
ACGIH:	1 ppm	
Exposure Routes:	inhalation, ingestion, skin and/or eye contact	
Target Organs:	Eyes, skin, respiratory system	
Symptoms:	irritation eyes, skin, upper respiratory system; eye, skin, burns; dermatitis	
Australia NICNAS:	not listed	Canada CEPA 1999: DSL Yes
Japan CSCL/PRTR:	not listed, Japan PDSCL: not listed	
Japan ISHL:	listed ≥1,0%/≥1,0%, Article 57-2 (SDS required)	
South Korea TCCA:	not listed	
Korea Exist.Chem.Inventory:	KE-27427	
LD50 <sub>orl rat</sub> :	1530 mg/kg	
LC50 <sub>ihl rbt</sub> :	1.689 mg/L	
LD50 <sub>drm rbt</sub> :	2750 mg/kg	
Acute Effects:	Cause after oral intake, impairments of health when ingested in small quantities.	
TRGS 905 (DE):	R <sub>F</sub> C	

#### 25 mL Cr-2

Chemical:	<i>1,5-diphenylcarbazine</i>	CAS No.: 140-22-7
TSCA Inventory:	listed	
Chemical:	<i>dimethyl sulfoxide</i>	CAS No.: 67-68-5
TSCA Inventory:	listed	
Korea Exist.Chem.Inventory:	KE-32367	
LD50 <sub>orl rat</sub> :	14,5 g/kg	
LD50 <sub>drm rat</sub> :	40 g/kg	



# Safety Data Sheet

according to Regulations 1907/2006/EC (REACH) and 2015/830/EU

REF: 931220

VISOCOLOR ECO Chromium (VI), refill pack

Page: 7/9

Printing date: 12.05.2021

Date of issue: 11.09.2018

## SECTION 12: Ecological information

### 12.1 Toxicity

Following information is valid for pure substances.

#### 30 mL Cr-1

Chemical: *o-phosphoric acid*  
 Avoid contact of substance/mixture to environment.  
 LC50<sub>fish/96h</sub>: 3-3.5 mg/L  
 Water hazard class (DE): 1 WGK No.: 0392  
 Storage class (VCI): 8 B

CAS No.: 7664-38-2

#### 25 mL Cr-2

Chemical: *1,5-diphenylcarbazine*  
 Water hazard class (DE): 2  
 Storage class (VCI): 12-13

CAS No.: 140-22-7

Chemical: *dimethyl sulfoxide*  
 PNEC<sub>(fresh water)</sub>: 17 mg/L  
 PNEC = Predicted No Effected Concentration  
 LC50<sub>fish/96h</sub>: 38.5 g/L  
 EC50<sub>daphnia/48h</sub>: 24.6 g/L  
 EC10<sub>pseudomonas putita/16h</sub>: EC/16h: 7100 mg/L  
 Water hazard class (DE): 1 WGK No.: 5050  
 Dispersion coefficient<sub>(octanol-water)</sub>: -1.35  
 Storage class (VCI): 12

CAS No.: 67-68-5

### 12.2 Persistence and degradability

not necessary

### 12.3 Bioaccumulative potential

not necessary

### 12.4 Mobility in soil

not necessary

### 12.5 Results of PBT and vPvB assessment

no data available

### 12.6 Other adverse effects

no additional data available

## SECTION 13: Disposal considerations

Please observe local regulations for collection and disposal of hazardous waste and contact waste disposal company, where you will obtain information on laboratory waste disposal (waste code number 16 05 06).

### 13.1 Waste treatment methods

Normally it is possible to empty small amounts (diluted!) into drains. Empty containers of corrosive reagents prior to disposal, rinse with water.

## SECTION 14: Transport information

14.1. UN number: 3316 14.2. UN proper shipping name: Chemical Kit

14.3. Class: 9 14.4. Packing group: II

Road transport

Classification code: M11 Tunnel restriction code: E

Limited Quantity: acc. ADR 3.3.1/251: see LQ in Alternative declaration for transportation

Air transport

PAX: 960 max. weight PAX: 10 KG

CAO: 960 max. weight CAO: 10 KG

Maritime transport

EmS: F-A, S-P Storage category: A

Or use **Alternative declaration for transportation:**

UN No.: (see below) class 8 III, **Excepted Quantities** ( $\leq 30 \text{ mL}/\sum \leq 1 \text{ L}$ ) = ADR/ IATA E1

or

# Safety Data Sheet

according to Regulations 1907/2006/EC (REACH) and 2015/830/EU

REF: 931220  
 Printing date: 12.05.2021  
 VISOCOLOR ECO Chromium (VI), refill pack  
 Date of issue: 11.09.2018  
 Page: 8/9

**14.1 UN number:** 3264 **14.2 UN proper shipping name:** Corrosive liquid, acidic, inorganic, n.o.s. (o-phosphoric acid solution)  
**14.3 Class:** 8 **14.4 Packing group:** III  
*Road transport*  
 Classification code: C1  
 Limited Quantity: 5 L Tunnel restriction code: E  
 Excepted Quantity: E 1  
*Air transport*  
 PAX: 852 max. weight PAX: 5 L  
 CAO: 856 max. weight CAO: 60 L  
*Maritime transport*  
 EmS: F-A, S-B Storage category: A

- 14.5 Environmental hazards**  
 none, contains only small quantities of hazardous substances
- 14.6 Special precautions for user**  
 not necessary
- 14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code**  
 not applicable

## SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**  
 German act governing protection from hazardous substances (Chemicals Act / Chemikaliengesetz- ChemG), revised on August 2013  
 German order governing protection from hazardous substances (Ordinance on Hazardous Substances / Gefahrstoffverordnung - GefStoffV), revised on November 2010, according to Directive 98/24/EC  
 TRGS 200, German engineering rules governing the classification and labelling of hazardous substances, preparations and products, updated October 2011  
 MN Leaflet/User manual, also see www.mn-net.com  
 Look for your country-specific regulations.
- 15.2 Chemical safety assessment**  
 not necessary for these small amounts ---

## SECTION 16: Other information

- 16.1 List of H and P phrases**
  - 16.1.1 List of relevant H phrases**
    - H290 May be corrosive to metals.
    - H302 Harmful if swallowed.
    - H314 Causes severe skin burns and eye damage.
  - 16.1.2 List of relevant P phrases**
    - P260sh Do not breathe dust/vapours.
    - P264W Wash with water thoroughly after handling.
    - P280sh Wear protective gloves/eye protection.
    - P301+312 IF SWALLOWED: Call a POISON CENTER/doctor if you feel unwell.
    - P303+361+353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
    - P305+351+338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
    - P310 Immediately call a POISON CENTER/doctor.
    - P330 Rinse mouth.
    - P390 Absorb spillage to prevent material damage.
- 16.2 Training advice**  
 Multiple safety training of staffs about danger and protection by using hazards in working area. Additionally training and introduction of staffs for using these products.
- 16.3 Recommended restriction on use**  
 Only for professional user.  
 Look about employee restrictions for young people (f. ex. 94/33/EC or DE § 22 JArbSchG)!  
 Look about employee restrictions for pregnant women and nursing women (f.ex. 92/85/EEC or for DE §§ 11-13 MuSchG 2017)!  
 An individual package of this product or test kit has a moderate hazardous potential.



# Safety Data Sheet

according to Regulations 1907/2006/EC (REACH) and 2015/830/EU

REF: 931220

VISOCOLOR ECO Chromium (VI), refill pack

Page: 9/9

Printing date: 12.05.2021

Date of issue: 11.09.2018

## 16.4 Further information

MACHEREY-NAGEL GmbH & Co. KG provides the information contained herein in good faith being up-to-date of own realizations at revision time. This document is intended only as a guide to the appropriate precautionary handling of the material by a properly trained person using this product. Individuals receiving the information must exercise their independent judgement in determining its appropriateness for a particular purpose.

MACHEREY-NAGEL GmbH & Co. KG makes NO REPRESENTATIONS or WARRANTIES, either expressed or implied, including without limitation any warranties of merchantability, fitness for a particular purpose with respect to the information set forth herein or the product to which the information refers. Accordingly MACHEREY-NAGEL GmbH & Co. KG will not be responsible for damages resulting from use of or reliance upon this information. See terms and conditions at the end of our price lists for additional information.

## 16.5 Sources of key data

Regulation 453/2010/EU REACH - REQUIREMENTS FOR THE COMPILATION OF SAFETY DATA SHEETS

Regulation 487/2013/EU, 4<sup>th</sup> adaptation of CLP regulation to technical and scientific progress

Regulation 669/2018/EU, 4<sup>th</sup> adaptation of CLP regulation to technical and scientific progress

Regulation 1480/2018/EU, 4<sup>th</sup> adaptation of CLP regulation to technical and scientific progress

TRGS 900, German engineering rules governing limits in air at work, updated 03/2019

SUVA .CH, Limits in air at work 2009, revised on 01.2009

KÜHN, BIRETT Merkblätter Gefährliche Arbeitsstoffe (Data Sheets of Hazardous Substances)

### Revisions/Updates

Reason for Revision: 2016-03 Adaptation of regulation 1221/2015/EU