MACHEREY-NAGEL

Data sheet

Filter paper

Parameter*	Value*
Grade	MN GF-6
Basis weight	70 g/m²
Thickness	0.35 mm
Filtration speed	12 s
Surface	smooth / glatt
Average retention capacity	0.6 μm
Maximum temperature	500 °C
Application	Glass fiber filter without binder

*These data are typical values and must not be regarded as specification.



MACHEREY-NAGEL GmbH & Co. KG · Neumann-Neander-Str. 6–8 · 52355 Düren · Germany US: DE/international: CH: FR:

 Tel.:
 +49 24 21 969-0
 Tel.:
 +41 62 388 55 00
 Tel.:
 +33 388 68 22 68

 Fax:
 +49 24 21 969-199
 Fax:
 +41 62 388 55 05
 Fax:
 +33 388 51 76 88

 E-mail:
 info@mn-net.com
 E-mail:
 sales-ch@mn-net.com
 E-mail:
 sales-fr@mn-net.com

 Tel.: +1 484 821 0984 Fax: +1 484 821 1272 E-mail: sales-us@mn-net.com

www.mn-net.com



28.12.2019

MACHEREY-NAGEL

Data sheet

*These data are typical values and must not be regarded as specification.

DE/international:

CH:

MACHEREY-NAGEL GmbH & Co. KG · Neumann-Neander-Str. 6–8 · 52355 Düren · Germany

FR:

 Tel.:
 +49 24 21 969-0
 Tel.:
 +41 62 388 55 00
 Tel.:
 +33 388 68 22 68

 Fax:
 +49 24 21 969-199
 Fax:
 +41 62 388 55 05
 Fax:
 +33 388 51 76 88

 E-mail:
 info@mn-net.com
 E-mail:
 sales-ch@mn-net.com
 E-mail:
 sales-fr@mn-net.com

US: Tel.: +1 484 821 0984 Fax: +1 484 821 1272 E-mail: sales-us@mn-net.com

www.mn-net.com

