

according to Regulation (EC) No. 1907/2006

Revision Date 17.08.2018

Version 10.2

SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Catalogue No. 106507

Product name Sodium dithionite for analysis EMSURE®

REACH Registration Number A registration number is not available for this substance as the

substance or its use are exempted from registration according to Article 2 REACH Regulation (EC) No 1907/2006, the annual tonnage does not require a registration or the registration is envisaged for a

later registration deadline.

CAS-No. 7775-14-6

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses Reagent for analysis

In compliance with the conditions described in the annex to this safety

data sheet.

1.3 Details of the supplier of the safety data sheet

Company Merck KGaA * 64271 Darmstadt * Germany * Phone: +49 6151 72-0

Responsible Department LS-QHC * e-mail: prodsafe@merckgroup.com

1.4 Emergency telephone

number

Please contact the regional company representation in your country.

SECTION 2. Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

according to Regulation (EC) No. 1907/2006

Catalogue No. 106507

Product name Sodium dithionite for analysis EMSURE®

Self-heating substances, Category 1, H251

For the full text of the H-Statements mentioned in this Section, see Section 16.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms



Signal word

Danger

Hazard statements

H251 Self-heating: may catch fire.

EUH031 Contact with acids liberates toxic gas.

EUH208 - Contains:

Hexamethylenetetramine

May produce an allergic reaction.

Reduced labelling (≤125 ml)

Hazard pictograms



Signal word

Danger

Hazard statements

H251 Self-heating: may catch fire.

Index-No. 016-028-00-1

2.3 Other hazards

according to Regulation (EC) No. 1907/2006

Catalogue No. 106507

Product name Sodium dithionite for analysis EMSURE®

None known.

SECTION 3. Composition/information on ingredients

3.1 Substance

Formula $Na_2S_2O_4$ $Na_2O_4S_2$ (Hill)

Index-No. 016-028-00-1 EC-No. 231-890-0

Molar mass 174,11 g/mol

Hazardous components (REGULATION (EC) No 1272/2008)

Chemical name (Concentration)

CAS-No. Registration number Classification

sodium dithionite (>= 50 % - <= 100 %)

Substance does not meet the criteria for PBT or vPvB according to Regulation (EC) No 1907/2006, Annex XIII.

7775-14-6 01-2119520510-57-

XXXX Self-heating substances, Category 1, H251

Acute toxicity, Category 4, H302

sodium carbonate (>= 3 % - < 10 %)

Substance does not meet the criteria for PBT or vPvB according to Regulation (EC) No 1907/2006, Annex XIII.

497-19-8 01-2119485498-19-

XXXX Eye irritation, Category 2, H319

Hexamethylenetetramine (>= 0,1 % - < 1 %)

Substance does not meet the criteria for PBT or vPvB according to Regulation (EC) No 1907/2006, Annex XIII.

100-97-0 01-2119474895-20- Flammable solid, Category 2, H228

XXXX Skin sensitisation, Category 1, H317

For the full text of the H-Statements mentioned in this Section, see Section 16.

according to Regulation (EC) No. 1907/2006

Catalogue No. 106507

Product name Sodium dithionite for analysis EMSURE®

3.2 Mixture

Not applicable

SECTION 4. First aid measures

4.1 Description of first aid measures

After inhalation: fresh air. Consult doctor if feeling unwell.

In case of skin contact: Take off immediately all contaminated clothing. Rinse skin with water/shower.

After eye contact: rinse out with plenty of water. Remove contact lenses.

After swallowing: immediately make victim drink water (two glasses at most). Consult a physician.

4.2 Most important symptoms and effects, both acute and delayed

irritant effects, Cough, respiratory paralysis, Shortness of breath, pain, Diarrhoea, Nausea, Vomiting, collapse, muscular weakness, Allergic reactions, death

4.3 Indication of any immediate medical attention and special treatment needed

Laxative: Sodium sulfate (1 tablespoon/1/4 I water).

SECTION 5. Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Carbon dioxide (CO2), Dry powder, Sand

Unsuitable extinguishing media

Water, Foam

5.2 Special hazards arising from the substance or mixture

Combustible.

danger of spontaneous combustion!

Risk of dust explosion.

Vapours are heavier than air and may spread along floors.

according to Regulation (EC) No. 1907/2006

Catalogue No. 106507

Product name Sodium dithionite for analysis EMSURE®

Forms explosive mixtures with air on intense heating.

Development of hazardous combustion gases or vapours possible in the event of fire.

Fire may cause evolution of:

Sulphur oxides

May not get in touch with:

Water

Caution! in contact with water product releases:

Sulphur oxides, The product reacts with water and generates heat.

5.3 Advice for firefighters

Special protective equipment for firefighters

Stay in danger area only with self-contained breathing apparatus. Prevent skin contact by keeping a safe distance or by wearing suitable protective clothing.

Further information

Suppress (knock down) gases/vapours/mists with a water spray jet. Prevent fire extinguishing water from contaminating surface water or the ground water system.

SECTION 6. Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Advice for non-emergency personnel: Avoid inhalation of dusts. Avoid substance contact. Ensure adequate ventilation. Evacuate the danger area, observe emergency procedures, consult an expert.

Advice for emergency responders:

Protective equipment see section 8.

6.2 Environmental precautions

Do not let product enter drains.

6.3 Methods and materials for containment and cleaning up

Cover drains. Collect, bind, and pump off spills. Observe possible material restrictions (see sections 7 and 10). Take up dry. Dispose of properly. Clean up affected area. Avoid generation of dusts.

6.4 Reference to other sections

according to Regulation (EC) No. 1907/2006

Catalogue No. 106507

Product name Sodium dithionite for analysis EMSURE®

Indications about waste treatment see section 13.

SECTION 7. Handling and storage

7.1 Precautions for safe handling

Advice on safe handling

Caution! Temperatures > 50°C cause evolution of gas in closed containers. Overpressure produces a risk of bursting.

Observe label precautions.

Keep workplace dry. Do not allow product to come into contact with water.

Hygiene measures

Change contaminated clothing. Preventive skin protection recommended. Wash hands after working with substance.

7.2 Conditions for safe storage, including any incompatibilities

Storage conditions

Tightly closed. Keep away from heat and sources of ignition.

Recommended storage temperature see product label.

7.3 Specific end use(s)

See exposure scenario in the Annex to this MSDS.

SECTION 8. Exposure controls/personal protection

8.1 Control parameters

Derived No Effect Level (DNEL)

sodium dithionite (7775-14-6)

Worker DNEL, Systemic effects inhalation 10 mg/m³

longterm

sodium carbonate (497-19-8)

Worker DNEL, Local effects inhalation 10 mg/m³

longterm

Hexamethylenetetramine (100-97-0)

Worker DNEL, Systemic effects dermal 8,8 mg/kg Body weight

longterm

according to Regulation (EC) No. 1907/2006

Catalogue No. 106507

Product name Sodium dithionite for analysis EMSURE®

Worker DNEL, Systemic effects inhalation 31 mg/m³

longterm

Predicted No Effect Concentration (PNEC)

sodium dithionite (7775-14-6)

PNEC Fresh water 1 mg/l

PNEC Marine water 0,1 mg/l

PNEC Sewage treatment plant 45,3 mg/l

sodium carbonate (497-19-8)

PNEC no data available

Hexamethylenetetramine (100-97-0)

PNEC Fresh water 3 mg/l

PNEC Marine water 0,5 mg/l

PNEC Fresh water sediment 2,4 mg/kg

PNEC Marine sediment 0,4 mg/kg

PNEC oral 53,33 mg/kg

PNEC Sewage treatment plant 100 mg/l

8.2 Exposure controls

Engineering measures

Technical measures and appropriate working operations should be given priority over the use of personal protective equipment.

See section 7.1.

Individual protection measures

Protective clothing needs to be selected specifically for the workplace, depending on concentrations and quantities of the hazardous substances handled. The chemical resistance of the protective equipment should be enquired at the respective supplier.

according to Regulation (EC) No. 1907/2006

Catalogue No. 106507

Product name Sodium dithionite for analysis EMSURE®

Eye/face protection

Safety glasses

Hand protection

full contact:

Glove material: Nitrile rubber
Glove thickness: 0,11 mm

Break through time: > 480 min

splash contact:

Glove material: Nitrile rubber
Glove thickness: 0,11 mm
Break through time: > 480 min

The protective gloves to be used must comply with the specifications of EC Directive 89/686/EEC and the related standard EN374, for example KCL 741 Dermatril® L (full contact), KCL 741 Dermatril® L (splash contact).

The breakthrough times stated above were determined by KCL in laboratory tests acc. to EN374 with samples of the recommended glove types.

This recommendation applies only to the product stated in the safety data sheet<(>,<)> supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

Other protective equipment protective clothing

Respiratory protection

required when dusts are generated.

Recommended Filter type: filter ABEK

The entrepeneur has to ensure that maintenance, cleaning and testing of respiratory protective devices are carried out according to the instructions of the producer. These measures have to be properly documented.

Environmental exposure controls

Do not let product enter drains.

according to Regulation (EC) No. 1907/2006

Catalogue No. 106507

Product name Sodium dithionite for analysis EMSURE®

SECTION 9. Physical and chemical properties

9.1 Information on basic physical and chemical properties

Form powder

Colour white

Odour stinging

Odour Threshold No information available.

pH 5,5 - 8,5

at 50 g/l 20 °C

Melting point ca. 100 °C

(decomposition)

Boiling point/boiling range Not applicable

Flash point > 100 °C

Method: DIN 51758

Evaporation rate No information available.

Flammability (solid, gas) No information available.

Lower explosion limit Not applicable

Upper explosion limit Not applicable

Vapour pressure Not applicable

according to Regulation (EC) No. 1907/2006

Catalogue No. 106507

Product name Sodium dithionite for analysis EMSURE®

Relative vapour density No information available.

Density 2,5 g/cm³

at 20 °C

Relative density No information available.

Water solubility ca.250 g/l

at 20 °C

(slow decomposition)

Partition coefficient: n- log Pow: < -4,7

octanol/water (calculated)

(External MSDS) Bioaccumulation is not expected.

Auto-ignition temperature Self-heating: may catch fire.

Decomposition temperature > 80 °C

Viscosity, dynamic No information available.

Explosive properties Not classified as explosive.

Oxidizing properties none

9.2 Other data

Ignition temperature > 200 °C

Method: DIN 51794

Bulk density ca.1.250 kg/m3

SECTION 10. Stability and reactivity

10.1 Reactivity

Self-heating: may catch fire.

according to Regulation (EC) No. 1907/2006

Catalogue No. 106507

Product name Sodium dithionite for analysis EMSURE®

Forms explosive mixtures with air on intense heating.

Risk of dust explosion.

10.2 Chemical stability

In case of decomposition in closed containers and tubes risk of bursting due to buildup of overpressure.

10.3 Possibility of hazardous reactions

Violent reactions possible with:

Oxidizing agents, salts of oxyhalogenic acids

Risk of ignition or formation of inflammable gases or vapours with:

Water

Generates dangerous gases or fumes in contact with:

Acids

10.4 Conditions to avoid

Exposure to moisture

Heating (decomposition).

Strong heating.

10.5 Incompatible materials

no information available

10.6 Hazardous decomposition products

in the event of fire: See section 5.

SECTION 11. Toxicological information

11.1 Information on toxicological effects

Acute oral toxicity

LD50 Rat: 2.500 mg/kg

(External MSDS) (Regulation (EC) No 1272/2008, Annex VI)

according to Regulation (EC) No. 1907/2006

Catalogue No. 106507

Product name Sodium dithionite for analysis EMSURE®

Acute inhalation toxicity

Symptoms: Irritation symptoms in the respiratory tract., Cough, Shortness of breath

Acute dermal toxicity

This information is not available.

Skin irritation

Rabbit

Result: No irritation

(External MSDS)

Eye irritation

Possible damages: slight irritation

Sensitisation

May produce an allergic reaction.

Germ cell mutagenicity

Genotoxicity in vitro

Ames test

Result: negative

(External MSDS)

Carcinogenicity

This information is not available.

Reproductive toxicity

This information is not available.

Teratogenicity

This information is not available.

Specific target organ toxicity - single exposure

This information is not available.

Specific target organ toxicity - repeated exposure

This information is not available.

according to Regulation (EC) No. 1907/2006

Catalogue No. 106507

Product name Sodium dithionite for analysis EMSURE®

Aspiration hazard

This information is not available.

11.2 Further information

After uptake of large quantities:

Nausea, Vomiting

Systemic effects:

pain, Diarrhoea, muscular weakness, collapse, respiratory paralysis, death

Other dangerous properties can not be excluded.

Handle in accordance with good industrial hygiene and safety practice.

SECTION 12. Ecological information

12.1 Toxicity

Toxicity to fish

LC50 Leuciscus idus (Golden orfe): 46 - 68 mg/l; 96 h

DIN 38412

(Regulation (EC) No 1272/2008, Annex VI)

Toxicity to daphnia and other aquatic invertebrates

EC50 Daphnia magna (Water flea): 98 mg/l; 48 h

(External MSDS) (Regulation (EC) No 1272/2008, Annex VI)

Toxicity to algae

IC50 Desmodesmus subspicatus (green algae): 206 mg/l; 72 h

(External MSDS) (Regulation (EC) No 1272/2008, Annex VI)

Toxicity to bacteria

EC50 Pseudomonas putida: 107 mg/l; 17 h

DIN 38412

(Regulation (EC) No 1272/2008, Annex VI)

12.2 Persistence and degradability

Biodegradability

The methods for determining the biological degradability are not applicable to inorganic substances.

according to Regulation (EC) No. 1907/2006

Catalogue No. 106507

Product name Sodium dithionite for analysis EMSURE®

Chemical Oxygen Demand (COD)

210 mg/g

(External MSDS)

12.3 Bioaccumulative potential

Partition coefficient: n-octanol/water

log Pow: < -4,7

(calculated)

(External MSDS) Bioaccumulation is not expected.

12.4 Mobility in soil

No information available.

12.5 Results of PBT and vPvB assessment

PBT/vPvB assessment not available as chemical safety assessment not required/not conducted.

12.6 Other adverse effects

Additional ecological information

Reacts with water to form toxic decomposition products.

Discharge into the environment must be avoided.

according to Regulation (EC) No. 1907/2006

Catalogue No. 106507

Product name Sodium dithionite for analysis EMSURE®

SECTION 13. Disposal considerations

Waste treatment methods

See www.retrologistik.com for processes regarding the return of chemicals and containers, or contact us there if you have further questions.

SECTION 14. Transport information

Land transport (ADR/RID)

14.1 UN number UN 1384

14.2 Proper shipping name SODIUM DITHIONITE

14.3 Class 4.2

14.4 Packing group

14.5 Environmentally hazardous ---

14.6 Special precautions for yes

user

Tunnel restriction code D/E

Inland waterway transport (ADN)

Not relevant

Air transport (IATA)

14.1 UN number UN 1384

14.2 Proper shipping name SODIUM DITHIONITE

14.3 Class 4.2

14.4 Packing group

14.5 Environmentally hazardous --

14.6 Special precautions for no

user

Sea transport (IMDG)

according to Regulation (EC) No. 1907/2006

Catalogue No. 106507

Product name Sodium dithionite for analysis EMSURE®

14.1 UN number UN 1384

14.2 Proper shipping name SODIUM DITHIONITE

14.3 Class 4.2

14.4 Packing group

14.5 Environmentally hazardous --

14.6 Special precautions for yes

user

EmS F-A S-J

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not relevant

SECTION 15. Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulations

Major Accident Hazard SEVESO III
Legislation Not applicable

Occupational restrictions Take note of Dir 94/33/EC on the protection of young people at

work.

Regulation (EC) No 1005/2009 on substances that not regulated

deplete the ozone layer

Regulation (EC) No 850/2004 of the European not regulated

Parliament and of the Council of 29 April 2004 on

persistent organic pollutants and amending

Directive 79/117/EEC

Substances of very high concern (SVHC)

This product does not contain substances

of very high concern according to

Regulation (EC) No 1907/2006 (REACH), Article 57 above the respective regulatory

concentration limit of $\geq 0.1 \%$ (w/w).

according to Regulation (EC) No. 1907/2006

Catalogue No. 106507

Product name Sodium dithionite for analysis EMSURE®

National legislation

Storage class 4.2

15.2 Chemical safety assessment

For this product a chemical safety assessment was not carried out.

SECTION 16. Other information

Full text of H-Statements referred to under sections 2 and 3.

H228 Flammable solid.

H251 Self-heating: may catch fire.

H302 Harmful if swallowed.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

Training advice

Provide adequate information, instruction and training for operators.

Key or legend to abbreviations and acronyms used in the safety data sheet

Used abbreviations and acronyms can be looked up at www.wikipedia.org.

Regional representation

This information is given on the authorised Safety Data Sheet for your country.

The information contained herein is based on the present state of our knowledge. It characterises the product with regard to the appropriate safety precautions. It does not represent a guarantee of any properties of the product.

according to Regulation (EC) No. 1907/2006

Catalogue No. 106507

Product name Sodium dithionite for analysis EMSURE®

EXPOSURE SCENARIO 1 (Industrial use)

1. Industrial use Reagent for analysis)

Sectors of end-use

SU 3 Industrial uses: Uses of substances as such or in preparations at industrial sites

SU9 Manufacture of fine chemicals

SU 10 Formulation [mixing] of preparations and/ or re-packaging (excluding alloys)

Chemical product category

PC21 Laboratory chemicals

Process categories

PROC1 Use in closed process, no likelihood of exposu
--

PROC2 Use in closed, continuous process with occasional controlled exposure

PROC3 Use in closed batch process (synthesis or formulation)

PROC4 Use in batch and other process (synthesis) where opportunity for exposure arises

PROC5 Mixing or blending in batch processes for formulation of preparations and articles

(multistage and/ or significant contact)

PROC8a Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large

containers at non-dedicated facilities

PROC8b Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large

containers at dedicated facilities

PROC9 Transfer of substance or preparation into small containers (dedicated filling line, including

weighing)

PROC10 Roller application or brushing

PROC15 Use as laboratory reagent

Environmental Release Categories

ERC1 Manufacture of substances
ERC2 Formulation of preparations

ERC6a Industrial use resulting in manufacture of another substance (use of intermediates)

ERC6b Industrial use of reactive processing aids

2. Contributing scenarios: Operational conditions and risk management measures

according to Regulation (EC) No. 1907/2006

Catalogue No. 106507

Product name Sodium dithionite for analysis EMSURE®

2.1 Contributing scenario controlling worker exposure for: PROC1, PROC2, PROC3, PROC4, PROC8b, PROC15, PROC5

Product characteristics

Concentration of the Substance in Covers the percentage of the substance in the product up to

Mixture/Article 100 %.

Physical Form (at time of use) Solid, high dustiness

Frequency and duration of use

Frequency of use 8 hours/day
Frequency of use 5 days/week

Other operational conditions affecting workers exposure

Outdoor / Indoor Indoor without local exhaust ventilation (LEV)

Organisational measures to prevent /limit releases, dispersion and exposure

Covers daily exposures up to 8 hours.

Conditions and measures related to personal protection, hygiene and health evaluation

Wear suitable gloves (tested to EN374) and eye protection.

2.2 Contributing scenario controlling worker exposure for: PROC9, PROC14, PROC10

Product characteristics

Concentration of the Substance in Covers the percentage of the substance in the product up to

Mixture/Article 100 %.

Physical Form (at time of use) Solid, high dustiness

Frequency and duration of use

Frequency of use 8 hours/day
Frequency of use 5 days/week

Other operational conditions affecting workers exposure

Outdoor / Indoor Indoor with local exhaust ventilation (LEV)

according to Regulation (EC) No. 1907/2006

Catalogue No. 106507

Product name Sodium dithionite for analysis EMSURE®

Technical conditions and measures

Use only in area provided with appropriate exhaust ventilation. Provide extraction ventilation at points where emissions occur. Provide extract ventilation to material transfer points and other openings. (Effectiveness (of a measure): 78 %)

Organisational measures to prevent /limit releases, dispersion and exposure

Covers daily exposures up to 8 hours.

Conditions and measures related to personal protection, hygiene and health evaluation

Wear suitable gloves (tested to EN374) and eye protection.

3. Exposure estimation and reference to its source

Environment

A chemical safety assessment was performed according REACH Article 14(3), Annex I, sections 3 (Environmental Hazard Assessment) and 4 (PBT/vPvB Assessment). As no hazard was identified, an exposure assessment and risk characterisation is not necessary (REACH Annex I section 5.0).

Workers

CS	Use descriptor	Exposure duration, route, effect	RCR	Exposure Assessment Method
2.1	PROC1	longterm, inhalative, systemic	0,001	MEASE
2.1	PROC2	longterm, inhalative, systemic	0,1	MEASE
2.1	PROC3	longterm, inhalative, systemic	0,1	MEASE
2.1	PROC4	longterm, inhalative, systemic	0,55	MEASE
2.1	PROC5	longterm, inhalative, systemic	0,55	MEASE
2.1	PROC8b	longterm, inhalative, systemic	0,55	MEASE
2.1	PROC15	longterm, inhalative, systemic	0,5	MEASE
2.2	PROC9	longterm, inhalative, systemic	0,44	MEASE
2.2	PROC10	longterm, inhalative, systemic	0,22	MEASE
2.2	PROC14	longterm, inhalative, systemic	0,22	MEASE

The default parameters and -efficiencies of the applied exposure assessment model were used for the calculation (unless stated differently).

For (other) acute effects risk management measures are based on qualitative risk characterisation.

according to Regulation (EC) No. 1907/2006

Catalogue No. 106507

Product name Sodium dithionite for analysis EMSURE®

4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the Exposure Scenario

Please refer to the following documents: ECHA Guidance on information requirements and chemical safety assessment Chapter R.12: Use descriptor system; ECHA Guidance for downstream users; ECHA Guidance on information requirements and chemical safety assessment Part D: Exposure Scenario Building, Part E: Risk Characterisation and Part G: Extending the SDS; VCI/Cefic REACH Practical Guides on Exposure Assessment and Communications in the Supply Chain; CEFIC Guidance Specific Environmental Release Categories (SPERCs).

according to Regulation (EC) No. 1907/2006

Catalogue No. 106507

Product name Sodium dithionite for analysis EMSURE®

EXPOSURE SCENARIO 2 (Professional use)

1. Professional use Reagent for analysis)

Sectors of end-use

SU 22 Professional uses: Public domain (administration, education, entertainment, services,

craftsmen)

Chemical product category

PC21 Laboratory chemicals

Process categories

PROC15 Use as laboratory reagent

Environmental Release Categories

ERC2 Formulation of preparations

ERC6a Industrial use resulting in manufacture of another substance (use of intermediates)

ERC6b Industrial use of reactive processing aids

2. Contributing scenarios: Operational conditions and risk management measures

2.1 Contributing scenario controlling worker exposure for: PROC15

Product characteristics

Concentration of the Substance in Covers the percentage of the substance in the product up to

Mixture/Article 100 %.

Physical Form (at time of use) Solid, high dustiness

Frequency and duration of use

Frequency of use 8 hours/day
Frequency of use 5 days/week

Other operational conditions affecting workers exposure

Outdoor / Indoor Indoor without local exhaust ventilation (LEV)

Organisational measures to prevent /limit releases, dispersion and exposure

Covers daily exposures up to 8 hours.

according to Regulation (EC) No. 1907/2006

Catalogue No. 106507

Product name Sodium dithionite for analysis EMSURE®

Conditions and measures related to personal protection, hygiene and health evaluation

Wear suitable gloves (tested to EN374) and eye protection.

3. Exposure estimation and reference to its source

Environment

A chemical safety assessment was performed according REACH Article 14(3), Annex I, sections 3 (Environmental Hazard Assessment) and 4 (PBT/vPvB Assessment). As no hazard was identified, an exposure assessment and risk characterisation is not necessary (REACH Annex I section 5.0).

Workers

CS	Use descriptor	Exposure duration, route, effect	RCR	Exposure Assessment Method
2.1	PROC15	longterm, inhalative, systemic	0,5	MEASE

The default parameters and -efficiencies of the applied exposure assessment model were used for the calculation (unless stated differently).

For (other) acute effects risk management measures are based on qualitative risk characterisation.

4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the Exposure Scenario

Please refer to the following documents: ECHA Guidance on information requirements and chemical safety assessment Chapter R.12: Use descriptor system; ECHA Guidance for downstream users; ECHA Guidance on information requirements and chemical safety assessment Part D: Exposure Scenario Building, Part E: Risk Characterisation and Part G: Extending the SDS; VCI/Cefic REACH Practical Guides on Exposure Assessment and Communications in the Supply Chain; CEFIC Guidance Specific Environmental Release Categories (SPERCs).