

FP90-SL HighTech SL/HL Ultra-Low Refrigerated-Heating Circulator

The Ultra-Low Refrigerated Circulators of the HighTech Series with HL or SL circulator feature powerful pressure and suction pumps. The instruments provide the entire variety of functions of the professional HighTech Series of circulators.

Your advantages

- VFD COMFORT DISPLAY
- LCD DIALOG DISPLAY backlit for convenient interactive operation
- ICC (Intelligent Cascade Control), self-optimizing temperature control
- TCF Temperature Control Features to optimize the control behavior
- ATC3 3-Point-Calibration
- SMART PUMP, electronically adjustable pump stages
- Adjustable high temperature cut-out, visible via display
- RS232/RS485 interface for online communication
- Integrated programmer for 6 x 60 program steps
- Connections for solenoid valve and HSP booster pump
- Proportional cooling control



Technical data

Available voltage versions		Bath	
Order No.	9 352 790N	Bath cover	integrated
Available voltage versions:			
9 352 790N.06	230V/3PPE/50Hz (Without Plug)		
9 352 790N.07	400V/3PNPE/50Hz (Plug 32A CEE)		
9 352 790N.16	208V/3PPE/60Hz (Without Plug)		
Cooling		Other	
Cooling of compressor	2-stage Air	Classification	Classification III (FL)
		IP Code	IP 21
Electronics		Dimensions and volumes	
Digital interface	Profibus optional	Weight kg	201
External pt100 sensor connection	integrated	Dimensions cm (W x L x H)	59 x 76 x 116
Integrated programmer	6x60 steps	Filling volume l	22
Temperature control	ICC	Pump connections	M16x1 male
Absolute temperature calibration	3 Point Calibration		
Temperature display	VFD		
Temperature setting	Keypad		
Temperature values			
Setting the resolution of the temperature display °C	0.01		
Temperature display resolution °C	0.01		

Performance values

230V/3PPE/50Hz (Without Plug)

230V/3PPE/50Hz						
Heating capacity kW	3					
Cooling capacity (Ethanol)						
°C	20	0	-20	-40	-60	-80
kW	1.8	1.7	1.6	1.35	0.75	0.15
Viscosity max. cST	70					
Refrigerant	R404A					
Filling volume g	850					
Global Warming Potential for R404A	3922					
Carbon dioxide equivalent t	3.334					
Refrigerant	R23					
Filling volume g	380					
Global Warming Potential for R23	14800					
Carbon dioxide equivalent t	5.624					
Pump capacity flow rate l/min	22 ... 26					
Pump capacity flow pressure bar	0.4 ... 0.7					
Maximum suction bar	0.2 ... 0.4					

400V/3PNPE/50Hz (Plug 32A CEE)

400V/3PNPE/50Hz						
Heating capacity kW	3					
Cooling capacity (Ethanol)						
°C	20	0	-20	-40	-60	-80
kW	1.8	1.7	1.6	1.35	0.75	0.15
Viscosity max. cST	70					
Refrigerant	R404A					
Filling volume g	850					
Global Warming Potential for R404A	3922					
Carbon dioxide equivalent t	3.334					
Refrigerant	R23					
Filling volume g	380					
Global Warming Potential for R23	14800					
Carbon dioxide equivalent t	5.624					
Pump capacity flow rate l/min	22 ... 26					
Pump capacity flow pressure bar	0.4 ... 0.7					
Maximum suction bar	0.2 ... 0.4					

208V/3PPE/60Hz (Without Plug)

208V/3PPE/60Hz		230V/3PPE/50Hz	
Heating capacity kW	3	Heating capacity kW	3

Cooling capacity (Ethanol)							Cooling capacity (Ethanol)						
°C	20	0	-20	-40	-60	-80	°C	20	0	-20	-40	-60	-80
kW	1.8	1.7	1.6	1.35	0.75	0.15	kW	1.8	1.7	1.6	1.35	0.75	0.15
Viscosity max. cST	70						Viscosity max. cST	70					
Refrigerant	R404A						Refrigerant	R404A					
Filling volume g	850						Filling volume g	850					
Global Warming Potential for R404A	3922						Global Warming Potential for R404A	3922					
Carbon dioxide equivalent t	3.334						Carbon dioxide equivalent t	3.334					
Refrigerant	R23						Refrigerant	R23					
Filling volume g	380						Filling volume g	380					
Global Warming Potential for R23	14800						Global Warming Potential for R23	14800					
Carbon dioxide equivalent t	5.624						Carbon dioxide equivalent t	5.624					
Pump capacity flow rate l/min	22 ... 26						Pump capacity flow rate l/min	22 ... 26					
Pump capacity flow pressure bar	0.4 ... 0.7						Pump capacity flow pressure bar	0.4 ... 0.7					
Maximum suction bar	0.2 ... 0.4						Maximum suction bar	0.2 ... 0.4					

Benefits



JULABO. Quality.
Highest standards of quality for a long product life.



Green technology.
Development consistently applied environmentally friendly materials and technologies.



Satisfied customers.
11 subsidiaries and more than 100 partners worldwide guarantee fast and qualified JULABO support.



100% Checked.
100% testing. 100% quality. Each JULABO Circulator undergoes thorough quality testing before leaving the factory.



Quick start.
Individual JULABO consultation and comprehensive manuals at your disposal.



Services 24/7.
Around the clock availability. You can find suitable accessories, data sheets, manuals, case studies, and more at www.julabo.com.



Intelligent temperature control.
Intelligent cascade control - automatic and self-optimizing adaptation of the PID control parameters with external stability of +/- 0.05 °C.



Connection of additional equipment
Stakei connections for solenoid valve, HSP booster pump and HST booster heater



Early warning system for high/low temperature limits
Maximum safety for applications, optical and audible alarm, convertible to automated cut-off function



Clever pump system
Reliable and consistent pump capacity, electronically adjustable pump stages



Control from the external application
External Pt100 sensor connection for precise measurement and control directly in the external application



For flammable bath fluid
Classification III (FL) according to DIN 12876-1



ATC3. Calibration.
'Absolute Temperature Calibration' for compensating a physically caused temperature difference, 3-point calibration.



Process. Under control.
Full regulation of the dynamics control, access to all important control parameters for individual process optimization.



100 % Cooling capacity
'Active Cooling Control' for cooling available throughout the entire working temperature range, fast cool-down even at higher temperatures



Energy saving cooling
Proportional cooling control for automatic adjustment of cooling power or temporary switch-off of compressor as needed to save up to 90 % energy in comparison to unregulated cooling machines



Condensation and ice protection
A heated cover plate prevents condensation or ice build-up in the bath