

# Safety Data Sheet

according to Regulations 1907/2006/EC (REACH) and 2015/830/EU

|                           |                                    |           |
|---------------------------|------------------------------------|-----------|
| REF: 915005               | VISOCOLOR HE Total Hardness H 20 F | Page: 1/9 |
| Printing date: 02.06.2020 | Date of issue: 12.02.2019          |           |

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1 Product identifier

REF 915005  
 Product name VISOCOLOR HE Total Hardness H 20 F

REACH Registration number(s): see SECTION 3.1/3.2 or  
 A registration number for the substance(s) does not exist because the annual tonnage does not require registration or the substance or its use is excluded from registration.

1 x 15 mL Indicator H 20 F  
 1 x 100 mL TL H 20

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

**Relevant identified uses**  
 Product for analytical use.  
 Exposure Scenario Classification according REACH, RIP 3.2 Codes: SU 0-2, PC 21, PROC 15, AC 0  
 The exposure scenario is integrated into sections 1-16.

**Uses advised against**  
 not described

### 1.3 Details of the supplier of the safety data sheet

**Manufactured by:**  
 MACHEREY-NAGEL GmbH & Co. KG  
 Neumann-Neander-Str. 6-8, 52355 Dueren, GERMANY  
 Tel.: +49 2421 969 0

E-mail: [sds@mn-net.com](mailto:sds@mn-net.com) ([msds@mn-net.com](mailto:msds@mn-net.com))

### 1.4 Emergency telephone number

Outside Germany (DE): Call your regional Poisons Information Service or call local Life Saving Service.  
 DE: Gemeinsames Giftinformationszentrum (GGIZ) 99089 Erfurt tel. +49 361 730 730

You find our current versions of SDS (22 languages) in Internet: <http://www.mn-net.com/SDS>

## SECTION 2: Hazard identification

### 2.0 Classification of the complete product



GHS02 GHS07

Signal word WARNING

| Hazard identification | Hazard classes/categories |
|-----------------------|---------------------------|
| H226                  | Flam. Liq. 3              |
| H315                  | Skin Irrit. 2             |
| H319                  | Eye Irrit. 2              |

### 2.1 Classification of the substance or mixture

15 mL Indicator H 20 F



GHS02 GHS07

# Safety Data Sheet

according to Regulations 1907/2006/EC (REACH) and 2015/830/EU

|                           |                                    |           |
|---------------------------|------------------------------------|-----------|
| REF: 915005               | VISOCOLOR HE Total Hardness H 20 F | Page: 2/9 |
| Printing date: 02.06.2020 | Date of issue: 12.02.2019          |           |

|                              |                                  |
|------------------------------|----------------------------------|
| Signal word                  | WARNING                          |
| <b>Hazard identification</b> | <b>Hazard classes/categories</b> |
| H226                         | Flam. Liq. 3                     |
| H315                         | Skin Irrit. 2                    |
| H319                         | Eye Irrit. 2                     |

**100 mL TL H 20**

|                 |                                    |
|-----------------|------------------------------------|
| Signal word     | Do not need labelling as hazardous |
| No hazard class | -                                  |

## 2.2 Label elements

According **CLP directive** inner packages must be only labelled with GHS symbol(s) and product identifier(s) (EU 1272/2008 Annex I - 1.5.1.2).

Harmful chemicals/mixtures with signal word: **WARNING** and highly flammable chemicals/mixtures must not be labelled with H and P phrases **until 125 mL** (EU 1272/2008 Annex I - 1.5.2).

**15 mL Indicator H 20 F**



Signal word: WARNING

**100 mL TL H 20**

Do not need labelling as hazardous  
Signal word: -

## 2.3 Other hazards

**Possible hazards from physicochemical properties**

In the case of pH values are less than 5 or higher than 9 then it is irritant. Flammable properties. ---

**Information pertaining to particular risks to human and possible symptoms**

---

**Information pertaining to particular risks to the environment**

---

**Other hazards**

---

## SECTION 3: Composition/information on ingredients

### 3.1 Substances or 3.2 Mixtures

**15 mL Indicator H 20 F**

|                  |   |          |          |
|------------------|---|----------|----------|
| Chemical:        | <i>triethanolamine</i>  | CAS No.: | 102-71-6 |
| Classification:  | H315, Skin Irrit. 2, H319, Eye Irrit. 2, H335, STOT SE 3  |          |          |
| Formula:         | C <sub>6</sub> H <sub>15</sub> NO <sub>3</sub>  |          |          |
| Pseudonym:       | 2,2',2"-nitrioltriethanol; tris(2-hydroxyethyl)amine  |          |          |
| TSCA Inventory:  | listed  |          |          |
| REACH Reg. No.:  | 01-2119486482-31-xxxx   |          |          |
| <b>Dual-use:</b> | The application of this chemical is exempt from the regulation 2017/2268/EU (see IC350 remark 4). |          |          |
| EC No.:          | 203-049-8   |          |          |
| RTECS:           | KL9275000   |          |          |
| KE No.:          | KE-25940  |          |          |
| Concentration:   | 20 - <45 %  |          |          |
| acc. CLP (GHS):  | H315, Skin Irrit. 2, H319, Eye Irrit. 2   |          |          |

# Safety Data Sheet

according to Regulations 1907/2006/EC (REACH) and 2015/830/EU

REF: 915005

VISOCOLOR HE Total Hardness H 20 F

Page: 3/9

Printing date: 02.06.2020

Date of issue: 12.02.2019

|                 |   |             |              |
|-----------------|---|-------------|--------------|
| Chemical:       | <i>ethanol</i><br>(denatured with 1%IPA/1%MEK, acc.2016/1867/EU)  | CAS No.:    | 64-17-5      |
| Classification: | H225, Flam. Liq. 2  |             |              |
| Formula:        | C <sub>2</sub> H <sub>6</sub> O; C <sub>2</sub> H <sub>5</sub> OH |             |              |
| Pseudonym:      | ethyl alcohol, methylated spirit                                  |             |              |
| TSCA Inventory: | listed  |             |              |
| REACH Reg. No.: | 01-2119457610-43-xxxx   |             |              |
| EC No.:         | 200-578-6   | Indice No.: | 603-002-00-5 |
| RTECS:          | KQ6300000   | MFCID:      | 00003568     |
| KE No.:         | KE-13217  |             |              |
| Concentration:  | 20 - <35 %  |             |              |
| acc. CLP (GHS): | H226, Flam. Liq. 3  |             |              |

|                 |  |          |   |
|-----------------|--|----------|---|
| Chemical:       | <i>indicator dye(s)</i>  | CAS No.: | - |
| Classification: | No criteria for classification or naming of chemical not required. |          |   |
| TSCA Inventory: | all listed, <1%  |          |   |
| Concentration:  | 0.1 - <1 %   |          |   |
| acc. CLP (GHS): | The criteria for classification are not fulfilled.                 |          |   |

### 100 mL TL H 20

|                 |  |          |           |
|-----------------|--|----------|-----------|
| Chemical:       | <i>ethylenedinitrilo tetraacetic acid, di Na-salt (EDTA-Na)</i>                                  | CAS No.: | 6381-92-6 |
| Classification: | H332, Acute Tox. 4 inh., H373, STOT RE 2   |          |           |
| Formula:        | C <sub>10</sub> H <sub>14</sub> N <sub>2</sub> Na <sub>2</sub> O <sub>8</sub> ·2H <sub>2</sub> O |          |           |
| TSCA Inventory: | listed (CAS 139-33-3)  |          |           |
| EC No.:         | 205-358-3  |          |           |
| RTECS:          | AH4410000; AH4375000   | MFCID:   | 00150037  |
| Concentration:  | 0.1 - <1 %   |          |           |
| acc. CLP (GHS): | The criteria for classification are not fulfilled.   |          |           |

### 3.3 Remarks

When not listed, mixtures are added with water [CAS No. 7732-18-5] to 100%.

List of H and P phrases: see section 16.1

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

Place insured person out of danger zone to fresh air immediately. Ensure quiet, warmth, and provide resuscitation if necessary. If necessary contact medical advice.

#### 4.1.1 After SKIN Contact

Remove contaminated clothing. Rinse the affected skin or mucous membrane thoroughly under running water. (If possible) use soap.

#### 4.1.2 After EYE Contact

After contact with the eyes rinse thoroughly under running water with the eyelid wide open with eye washing bottle, eye douche or running water (protect intact eye).

#### 4.1.3 After INHALATION of vapours

After inhalation of foam or vapour fresh air should be inhaled. Keep airways free. ---

#### 4.1.4 After ORAL Intake

After oral intake lots of water should be drunk after it has been ingested. ---

### 4.2 Most important symptoms and effects, both acute and delayed

---

### 4.3 Indication of any immediate medical attention and special treatment needed

No additionally recommendations. ---

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

Fire extinguishers appropriate to the fire classification, and, if applicable, a fire blanket must be available in a prominent location in the work area. All extinguishers like FOAM, WATER SPRAY, DRY POWDER, CARBON DIOXIDE can be used.

# Safety Data Sheet

according to Regulations 1907/2006/EC (REACH) and 2015/830/EU

REF: 915005

VISOCOLOR HE Total Hardness H 20 F

Page: 4/9

Printing date: 02.06.2020

Date of issue: 12.02.2019

## 5.2 Special hazards arising from the substance or mixture

WARNING: Flammable (GHS regulation). May form explosive vapour-air mixtures. Formation of hazardous and caustic vapour-air mixtures possible. ---

## 5.3 Advice for firefighters

No, for listed product. Product package burns like paper or plastic.

## 5.4 Additional information

---

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Do not breathe vapours. Regular staff training is necessary.

### 6.2 Environmental precautions

not necessary

### 6.3 Methods and material for containment and cleaning up

Bind any escaping liquid with inert absorbent.  
Collect small amounts of leaked liquid and flush with water into drains.

### 6.4 Reference to other sections

---

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

Handling in accordance with the test instruction, that comes with the product.

### 7.2 Conditions for safe storage, including any incompatibilities

The original product package of MACHEREY-NAGEL allows a safe storage.

Storage class (VCI): 3

Water hazard class (DE): 2

#### 7.2.1 Requirements for stock rooms and containers

Keep original product packages tightly closed during handling and storage.

### 7.3 Specific end use(s)

Product for analytical use.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### 15 mL Indicator H 20 F

Chemical: *triethanolamine*

CAS No.: 102-71-6

DNEL: [derm] 6.3; [inh] 5 mg/m<sup>3</sup>

DNEL = Derived No-Effect Level (for workers)

PNEC(fresh water): 0.32 mg/L

PNEC = Predicted No Effect Concentration

TRGS 900 (DE): - DFG: 5 E mg/m<sup>3</sup>

E/e respirable

Short-term exposure factor: 1, (2)

skin resorptive (H), respiratory sensitizable (Sa), skin sensitizable (Sh), teratogenic (Z) not securely excluded / (Y) certainly excluded

SUVA(CH) MAK value: [MAK] 5 e/[STEL] 10 e mg/m<sup>3</sup>

NIOSH: not listed

[TWA] Time-weighted average to a reference period of 8 hours, [STEL] Short-term exposure limit related to a 15-minute period

OSHA: not listed

Chemical: *ethanol*

CAS No.: 64-17-5

DNEL: [derm] 343 mg/kg; [inh] 950 mg/m<sup>3</sup>

DNEL = Derived No-Effect Level (for workers)

PNEC(fresh water): 0.96 mg/L

PNEC = Predicted No Effect Concentration

TRGS 900 (DE): 200 mL/m<sup>3</sup> / 380 mg/m<sup>3</sup>

E/e respirable

Short-term exposure factor: 4 (II), Y

skin resorptive (H), respiratory sensitizable (Sa), skin sensitizable (Sh), teratogenic (Z) not securely excluded / (Y) certainly excluded

www.mn-net.com



MACHEREY-NAGEL GmbH & Co. KG · Neumann-Neander-Str. 6-8 · 52355 Düren · Germany

DE/international:

CH:

FR:

US:

Tel.: +49 24 21 969-0

Tel.: +41 62 388 55 00

Tel.: +33 388 68 22 68

Tel.: +1 484 821 0984

Fax: +49 24 21 969-199

Fax: +41 62 388 55 05

Fax: +33 388 51 76 88

Fax: +1 484 821 1272

E-mail: info@mn-net.com

E-mail: sales-ch@mn-net.com

E-mail: sales-fr@mn-net.com

E-mail: sales-us@mn-net.com

# Safety Data Sheet

according to Regulations 1907/2006/EC (REACH) and 2015/830/EU

REF: 915005

VISOCOLOR HE Total Hardness H 20 F

Page: 5/9

Printing date: 02.06.2020

Date of issue: 12.02.2019

SUVA(CH) MAK value: 500 ppm / 960 mg/m<sup>3</sup>  
 NIOSH: [TWA] 1000 ppm / 1900 mg/m<sup>3</sup>  
 [TWA] Time-weighted average to a reference period of 8 hours, [STEL] Short-term exposure limit related to a 15-minute period  
 OSHA: [TWA] 1000 ppm / 1900 mg/m<sup>3</sup>

Chemical: *indicator dye(s)*

CAS No.: -

### 100 mL TL H 20

Chemical: *ethylendinitrilo tetraacetic acid, di Na-salt (EDTA-Na)*

CAS No.: 6381-92-6

DNEL: [inh] 1.5 mg/m<sup>3</sup>  
 DNEL = Derived No-Effect Level (for workers)

PNEC<sub>(fresh water)</sub>: 2.2 mg/L  
 PNEC = Predicted No Effect Concentration

## 8.2 Exposure controls

Good ventilation and extraction system in the room, floor resistant to chemicals with floor drainage and washing facilities. The highest level of cleanliness must be maintained at the workplace.

### 8.2.1 Respiratory protection

No additional recommendations.

### 8.2.2 Hand protection

Yes, gloves according EN 374 (permeation time >30 min - level 2), consist of PVC, natural latex, Neopren, or Nitril (f.ex. from Ansell or KCL). Use for short times chemical resistant latex gloves with code EN 374-3 level 1.

### 8.2.3 Eye protection

Yes, safety glasses according EN 166 with integrated side shields or wrap-around protection.

### 8.2.4 Skin protection

Not necessary.

### 8.2.5 Personal hygiene

Eating, drinking, smoking, taking snuff and storage of food in work areas and at outdoor workplaces is prohibited. Avoid contact with the skin, eyes and clothing. Rinse any clothing on which the substance has been spilled, and soak it in water. Wash hands thoroughly with soap and water when stopping work and before eating, and then apply protective skin cream.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

#### 15 mL Indicator H 20 F

|                    |               |              |
|--------------------|---------------|--------------|
| Appearance: liquid | Colour: green | Odor: aminic |
| pH:                | 10-11         |              |
| Flash point:       | 29 °C         |              |

#### 100 mL TL H 20

|                      |                    |              |
|----------------------|--------------------|--------------|
| Appearance: liquid   | Colour: colourless | Odor: aminic |
| pH:                  | 9-10               |              |
| Solubility in water: | 0-100 %            |              |

### 9.2 Other information

Data for the other parameters of the mixtures are not available, because no registration and no chemical safety report is required.

#### Relevant Properties of Substance Group

---

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

no further data available.

### 10.2 Chemical stability

No known instability.

### 10.3 Possibility of hazardous reactions



# Safety Data Sheet

according to Regulations 1907/2006/EC (REACH) and 2015/830/EU

REF: 915005

VISOCOLOR HE Total Hardness H 20 F

Page: 7/9

Printing date: 02.06.2020

Date of issue: 12.02.2019

## SECTION 12: Ecological information

### 12.1 Toxicity

Following information is valid for pure substances.

#### 15 mL Indicator H 20 F

|   |                           |          |          |
|---|---------------------------|----------|----------|
| Chemical:   | <i>triethanolamine</i>    | CAS No.: | 102-71-6 |
| PNEC <sub>(fresh water)</sub> :                     | 0.32 mg/L                 |          |          |
| PNEC = Predicted No Effect Concentration            |                           |          |          |
| LC50 <sub>fish/96h</sub> :                          | >1000 mg/L                |          |          |
| EC50 <sub>daphnia/48h</sub> :                       | >1000 <sub>24h</sub> mg/L |          |          |
| Water hazard class (DE):                            | 1                         | WGK No.: | 0201     |
| Dispersion coefficient <sub>(octanol-water)</sub> : | -2.3                      |          |          |
| Storage class (VCI):                                | 12                        |          |          |

|   |                    |          |         |
|---|--------------------|----------|---------|
| Chemical:   | <i>ethanol</i>     | CAS No.: | 64-17-5 |
| PNEC <sub>(fresh water)</sub> :                     | 0.96 mg/L          |          |         |
| PNEC = Predicted No Effect Concentration            |                    |          |         |
| LC50 <sub>daphnia magna/48h</sub> :                 | >100 mg/L          |          |         |
| LC50 <sub>pimephales promelas/96h</sub> :           | 13400 - 15100 mg/L |          |         |
| LC50 <sub>leuciscus idus/96h</sub> :                | [48h] 8140 mg/L    |          |         |
| LC50 <sub>fish/96h</sub> :                          | 13 g/L             |          |         |
| EC50 <sub>daphnia/48h</sub> :                       | 9.3-14.2 g/L       |          |         |
| IC50 <sub>scenedesmus quadricauda/72h</sub> :       | [7d] 5000 mg/L     |          |         |
| EC10 <sub>pseudomonas putita/16h</sub> :            | [EC5] 6500 mg/L    |          |         |
| Water hazard class (DE):                            | 1                  | WGK No.: | 0096    |
| Dispersion coefficient <sub>(octanol-water)</sub> : | -0.31              |          |         |
| Storage class (VCI):                                | 3                  |          |         |

|                      |                         |          |   |
|----------------------|-------------------------|----------|---|
| Chemical:            | <i>indicator dye(s)</i> | CAS No.: | - |
| Storage class (VCI): | 12-13                   |          |   |

#### 100 mL TL H 20

|   |  |          |           |
|---|--|----------|-----------|
| Chemical:   | <i>ethylendinitrilo tetraacetic acid, di Na-salt (EDTA-Na)</i> | CAS No.: | 6381-92-6 |
| PNEC <sub>(fresh water)</sub> :                     | 2.2 mg/L   |          |           |
| PNEC = Predicted No Effect Concentration            |  |          |           |
| LC50 <sub>fish/96h</sub> :                          | [4d] 41-1592 mg/L  |          |           |
| EC50 <sub>daphnia/48h</sub> :                       | 140 mg/L   |          |           |
| IC50 <sub>scenedesmus quadricauda/72h</sub> :       | [72h] 2.77-1000 mg/L   |          |           |
| EC10 <sub>pseudomonas putita/16h</sub> :            | [EC10, 30h] 500 mg/L   |          |           |
| Water hazard class (DE):                            | 2  |          |           |
| Dispersion coefficient <sub>(octanol-water)</sub> : | -4.3   |          |           |
| Storage class (VCI):                                | 12-13  |          |           |

### 12.2 Persistence and degradability

not necessary

### 12.3 Bioaccumulative potential

not necessary

### 12.4 Mobility in soil

not necessary

### 12.5 Results of PBT and vPvB assessment

no data available

### 12.6 Other adverse effects

no additional data available

## SECTION 13: Disposal considerations

Please observe local regulations for collection and disposal of hazardous waste and contact waste disposal company, where you will obtain information on laboratory waste disposal (waste code number 16 05 06).

### 13.1 Waste treatment methods

Normally it is possible to empty small amounts (diluted!) into drains.

# Safety Data Sheet

according to Regulations 1907/2006/EC (REACH) and 2015/830/EU

REF: 915005

VISOCOLOR HE Total Hardness H 20 F

Page: 8/9

Printing date: 02.06.2020

Date of issue: 12.02.2019

## SECTION 14: Transport information

14.1. UN number: 3316 14.2. UN proper shipping name: Chemical Kit  
14.3. Class: 9 14.4. Packing group: II

### Road transport

Classification code: M11 Tunnel restriction code: E  
Limited Quantity: acc. ADR 3.3.1/251: see LQ in Alternative declaration for transportation

### Air transport

PAX: 960 max. weight PAX: 10 KG  
CAO: 960 max. weight CAO: 10 KG

### Maritime transport

EmS: F-A, S-P Storage category: A

### Or use Alternative declaration for transportation:

UN 1993 class 3 III, Excepted Quantities ( $\leq 30$  mL/ $\Sigma \leq 1$  L) = ADR/ IATA E1

or

14.1 UN number: 1993 14.2 UN proper shipping name: Flammable liquid, n.o.s. (ethanol mixture)  
14.3 Class: 3 14.4 Packing group: III

### Road transport

Classification code: F1 Tunnel restriction code: E  
Limited Quantity: 5 L Special instructions: 640E  
Excepted Quantity: E 1

### Air transport

PAX: 355 max. weight PAX: 60 L  
CAO: 366 max. weight CAO: 220 L

### Maritime transport

EmS: F-E, S-E Storage category: A

## 14.5 Environmental hazards

none, contains only small quantities of hazardous substances

## 14.6 Special precautions for user

not necessary

## 14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code

not applicable

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

German act governing protection from hazardous substances (Chemicals Act / Chemikaliengesetz- ChemG), revised on August 2013  
German order governing protection from hazardous substances (Ordinance on Hazardous Substances / Gefahrstoffverordnung - GefStoffV), revised on November 2010, according to Directive 98/24/EC  
TRGS 200, German engineering rules governing the classification and labelling of hazardous substances, preparations and products, updated October 2011  
MN Leaflet/User manual, also see www.mn-net.com  
Look for your country-specific regulations.

### 15.2 Chemical safety assessment

not necessary for these small amounts ---

## SECTION 16: Other information

### 16.1 List of H and P phrases

#### 16.1.1 List of relevant H phrases

H226 Flammable liquid and vapour.  
H315 Causes skin irritation.  
H319 Causes serious eye irritation.

#### 16.1.2 List of relevant P phrases

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.  
P280sh Wear protective gloves/eye protection.

### 16.2 Training advice

Regular safety training.



# Safety Data Sheet

according to Regulations 1907/2006/EC (REACH) and 2015/830/EU

REF: 915005

VISOCOLOR HE Total Hardness H 20 F

Page: 9/9

Printing date: 02.06.2020

Date of issue: 12.02.2019

## 16.3 Recommended restriction on use

Only for professional user.

An individual package of this product or test kit has a moderate hazardous potential.

## 16.4 Further information

MACHEREY-NAGEL GmbH & Co. KG provides the information contained herein in good faith being up-to-date of own realizations at revision time. This document is intended only as a guide to the appropriate precautionary handling of the material by a properly trained person using this product. Individuals receiving the information must exercise their independent judgement in determining its appropriateness for a particular purpose.

MACHEREY-NAGEL GmbH & Co. KG makes NO REPRESENTATIONS or WARRANTIES, either expressed or implied, including without limitation any warranties of merchantability, fitness for a particular purpose with respect to the information set forth herein or the product to which the information refers. Accordingly MACHEREY-NAGEL GmbH & Co. KG will not be responsible for damages resulting from use of or reliance upon this information. See terms and conditions at the end of our price lists for additional information.

## 16.5 Sources of key data

Regulation 453/2010/EU REACH - REQUIREMENTS FOR THE COMPILATION OF SAFETY DATA SHEETS

Regulation 487/2013/EU, 4<sup>th</sup> adaptation of CLP regulation to technical and scientific progress

Regulation 669/2018/EU, 4<sup>th</sup> adaptation of CLP regulation to technical and scientific progress

Regulation 1480/2018/EU, 4<sup>th</sup> adaptation of CLP regulation to technical and scientific progress

TRGS 900, German engineering rules governing limits in air at work, updated 03/2019

SUVA .CH, Limits in air at work 2009, revised on 01.2009

KÜHN, BIRETT Merkblätter Gefährliche Arbeitsstoffe (Data Sheets of Hazardous Substances)

### Revisions/Updates

Reason for Revision: 2016-03 Adaptation of regulation 1221/2015/EU

2017-08 Adaption of new ethanol denaturation 2016/1867/EU