


AUSSCHWINGROTOR, 4-FACH | 5699-R



Rotor	
max. RPM max. RCF	4.600 min ⁻¹ 5.063
max. Kapazität	4x 750 ml
An- Auslaufzeit gebremst in s	90 95
Winkel	90°
Temperatur in °C ¹⁾	+7
Bestell-Nr.	5699-R

Gehänge mit Bügelverschluss



Deckel biodicht ⁹⁾	4883
Bestell-Nr.	4890

Gehänge ohne Verschluss¹⁴⁾



Bestell-Nr.	4895
--------------------	-------------



Gefäße

Kapazität in ml	1,5	2,0	5	7	8	9	15	25	50	100	2,6–2,9	2,7–3	4–5,5	4,5–5	4,9
Ø x L in mm	11 x 38	11 x 38	12 x 75	12 x 100	16 x 81	14 x 100	17 x 100	24 x 100	34 x 100	44 x 100	13 x 65	11 x 66	15 x 75	11 x 92	13 x 90
max. RCF ²⁾	3.407 / 4.542	3.407 / 4.542	4.471	4.471	4.637	4.637	4.637	4.353	4.424	4.400	4.471	4.471	4.637	4.471	4.471
Radius in mm	144 / 192	144 / 192	189	189	196	196	196	184	187	186	189	189	196	189	189
Bestell-Nr.	Mikrolitergefäße			Röhrchen²⁾						Blutabnahmegefäße / Uringefäße					

Adapter

Bohrung Ø x L in mm	11,5 x 38	11,5 x 38	13 x 58	13 x 58	17,5 x 53	17,5 x 53	17,5 x 53	26 x 72	36 x 79	45 x 78	13,5 x 58	13 x 58	17,5 x 53	13 x 58	13,5 x 58
Gefäße pro Rotor	168	168	120	120	76	76	76	28	16	8	84	120	76	120	84
Bestell-Nr.	4432	4432	4433	4433	4434	4434	4434	4438	4439	4442	4435	4433	4434	4433	4435

Gefäße

Kapazität in ml	7,5–8,2	9–10	10	1,6–5	4–7	4–7	8	8,5–10	10	15	50	25	30	50	50
Ø x L in mm	15 x 92	16 x 92	15 x 102	13 x 75	13 x 100	16 x 75	16 x 125	16 x 100	16 x 80	17 x 120	29 x 115	25 x 90	25 x 110	29 x 115	29 x 107
max. RCF ²⁾	4.637	4.637	4.637	4.471	4.471	4.637	4.637	4.637	4.637	4.755	4.613	4.566	4.566	4.613	4.613
Radius in mm	196	196	196	189	189	196	196	196	196	201	195	193	193	195	195
Bestell-Nr.	Blutabnahmegefäße / Uringefäße										Gefäße mit Schraubverschluss				

Adapter

Bohrung Ø x L in mm	17,5 x 60	17,5 x 60	17,5 x 60	13,5 x 58	13,5 x 58	17,5 x 60	17,5 x 60	17,5 x 60	17,5 x 60	17,5 x 60	17 x 102	31 x 96	26 x 72	26 x 72	31 x 96	31 x 96
Gefäße pro Rotor	76	76	76	84	84	76	76	76	76	76	56	28	28	28	28	28
Bestell-Nr.	4434	4434	4434	4435	4435	4434	4434	4434	4434	4434	4469	4468	4438	4438	4468⁴⁾	4468

Gefäße

Kapazität in ml	250	600	750	175	175	200	225	250	500	450	750	450			
Ø x L in mm	61 x 122	93 x 134	97 x 152	61 x 118	62 x 144	60 x 130	61 x 137	60 x 172	96 x 147	97 x 110	96 x 135	3-fach-System ohne Filter			
max. RCF ²⁾	4.873	4.873	4.873	5.063	5.063	5.063	5.063	5.063	5.063	5.063	5.063	5.063			
Radius in mm	206	206	206	214	214	214	214	214	214	214	214	214			
Bestell-Nr.	5127²⁴⁾	0551²⁴⁾	0512²⁴⁾	Falcon®	Nalgene®	Nunc®	Falcon®	Corning®	Corning®	4447	4234-A	Blutbeutel²⁶⁾			

Adapter

Bohrung Ø x L in mm	62 x 92	98,4 x 116	98,4 x 116	61 x 105	61 x 105	61 x 105	61 x 105	61 x 105	-	98,4 x 116	98,4 x 116	-			
Gefäße pro Rotor	4	4	4	4	4	4	4	4	4	4	4	4			
Bestell-Nr.	4443	4451	4451	4440	4430	4430	4440	4430	4449	4451	4451	-			