

KERN ALJ 250-4A

KERN

Analytical balance with high weighing capacity, graphic display and convenient recipe function



USP Minimum weight of sample (k = 2, U = 0.1%) 200 mg

Automatic adjustment - Standard time interval	3 h
Default unit	g
Readability carat [d] (ct)	0,001 ct
Weighing capacity [Max] (ct)	1250 ct
Maximum creep (30 minutes)	2 mg
Construction type of the scale	Single-range balance
Maximum creep (15 minutes)	1 mg

Approval

CE mark	✓
---------	---

Display

Display type	LCD graphic
Display backlight	✓
Display screen size	132×38 mm
Display digit height - smallest digit	4 mm
Display digit height	15 mm
Languages of the user interface	English

Construction

Dimension housing (W×D×H)	210×340×330 mm
Dimensions rectangular draught shield - inner (W×D×H)	160×170×225 mm
Dimensions rectangular draught shield - outer (W×D×H)	172×185×245 mm
Dimensions completely mounted (W×D×H)	210×340×330 mm
Material display housing	Plastics
Material housing	plastic
Material weighing plate	stainless steel
Material platform	Stainless steel
Material draught shield	glass
Dimensions weighing surface (Ø)	80 mm
Transport safety lock - bolt torque	0,1 Nm
Levelling feet adjustable	✓
Level indicator	✓

Functions

PreTare function	✓
Recipe/summing level	Rez B (Net-total, memory with plain text designations + setpoint, also for printout)
Recipe weighing - number of database entries	99

Category

Brand	KERN
Product category	Laboratory balance
Product group	Analytical balance
Product family	ALJ

Measuring System

Weighing system	Force compensation
Weighing capacity [Max]	250 g
Readability [d]	0,0001 g
Resolution	2.500.000
Linearity	± 0,0003 g
Reproducibility	0,0001 g

Units	g
	mg
	gn
	dwt
	tl (Tw)
	tl (HK)
	ozt
	tl (Singap, Malays)
	ct
	mo
	lb
	oz

Automatic adjustment - Standard temperature deviation	1,2 °C
Adjustment options	Internal calibration (automatic)
Recommended adjusting weight	250 g (E2)
Stabilization time	4 s
Warm-up time	8 h
Eccentric loading at 1/3 [Max]	0,0003 g

KERN ALJ 250-4A



Analytical balance with high weighing capacity, graphic display and convenient recipe function

Recipe weighing - number of ingredients per database entry	20
Percentage determination	✓
Dispensing function	✓
Density determination	✓
Tolerance weighing	✓
Tolerance weighing - type of signal	acoustically visual
Underfloor weighing	None
Function for averaging under unstable weighing conditions	✓
Capacity - Display	✓
Standby function	✓
Counting function	✓
Counting resolution (laboratory conditions)	250.000
Counting reference weight can be entered	✓
Smallest piece weight when piece counting - laboratory conditions	1 mg
Smallest piece weight when piece counting - normal conditions	10 mg
Reference quantity	10, 25, 50, 100, n (any number of pieces)
	off
Auto-off interval(s) in mains power mode	5 min 2 min 15 min
Tare function	manual (multi)
Number of keys for operation	6

Power Supply

Supplied power supply	Power supply unit
Plug-in power supply type	Power adapter
	EURO
Plug-in power supply / adapter for countries - included with the delivery	AUS UK US CH
	EURO
Plug-in power supply / adapter for countries - optional	UK US CH
Input voltage power supply / power [Max]	country dependent
Input voltage device / power [Max]	24 V 1 A

Environmental conditions

Ambient temperature [Min]	5 °C
Ambient temperature [Max]	35 °C

Humidity of environment [Max]	80 %
Storage temperature [Min]	-10 °C
Storage temperature [Max]	40 °C

Packing & Shipping

Delivery time	1 d
Dimensions packaging (W×D×H)	400×515×615 mm
Net weight	6,5 kg
Shipping method	Parcel service
Net weight approx.	7 kg
Gross weight approx.	9 kg
Shipping weight	25,3 kg

Services (optional)

Article number for DAkkS calibration	963-101
Article number for certificate of conformity (verification)	969-517

Interface

Interfaces	RS-232 standard
EasyTouch (ET) - Connection type	über alle verfügbare Schnittstellen möglich

Pictograms

STANDARD



OPTION

