

SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006 Revision Date 27.05.2019

Version 14.5

SECTION 1. Identification of the substance/mixture and of the company/undertaking **1.1 Product identifier**

	Catalogue No.	102827
	Product name	Cyclohexane for liquid chromatography LiChrosolv ${ m I\!R}$
	REACH Registration Number	01-2119463273-41-XXXX
	CAS-No.	110-82-7
1.2 Relevant identified uses of the substance or mixture and uses advised against		

Identified uses	Analytical and preparative chromatography
	In compliance with the conditions described in the annex to
	this safety data sheet.

1.3 Details of the supplier of the safety data sheet

Company	Merck KGaA * 64271 Darmstadt * Germany * Phone:+49 6151 72-0
Responsible Department	LS-QHC * e-mail: prodsafe@merckgroup.com

1.4 Emergency telephone Please contact the regional company representation in number your country.

SECTION 2. Hazards identification

2.1 Classification of the substance or mixture Classification (REGULATION (EC) No 1272/2008)

Flammable liquid, Category 2, H225 Skin irritation, Category 2, H315 Specific target organ toxicity - single exposure, Category 3, Central nervous system, H336 Aspiration hazard, Category 1, H304 Short-term (acute) aquatic hazard, Category 1, H400 Long-term (chronic) aquatic hazard, Category 1, H410

For the full text of the H-Statements mentioned in this Section, see Section 16.

Page 1 of 23



Catalogue No. Product name

2.2 Label elements Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms



Signal word Danger

Hazard statements
H225 Highly flammable liquid and vapour.
H304 May be fatal if swallowed and enters airways.
H315 Causes skin irritation.
H336 May cause drowsiness or dizziness.
H410 Very toxic to aquatic life with long lasting effects.

Precautionary statements

Prevention

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P240 Ground/bond container and receiving equipment.

P273 Avoid release to the environment.

Response

P301 + P330 + P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P302 + P352 IF ON SKIN: Wash with plenty of soap and water.

Storage

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

Reduced labelling (≤125 ml)



Signal word Danger

Hazard statements H304 May be fatal if swallowed and enters airways.

Precautionary statements P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P301 + P330 + P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

Index-No. 601-017-00-1

2.3 Other hazards

None known.

Page 2 of 23



Catalogue No.102827Product nameCyclohexane for liquid chromatography LiChrosolv®

SECTION 3. Composition/information on ingredients

3.1 Substance

Formula	C6H12 (Hill)
Index-No.	601-017-00-1
EC-No.	203-806-2
Molar mass	84,16 g/mol

Hazardous components (REGULATION (EC) No 1272/2008)

Chemical name (Concentration) CAS-No. Registration Classification number Cyclohexane (<= 100 %) Substance does not meet the criteria for PBT or vPvB according to Regulation (EC) No 1907/2006, Annex XIII.

110-82-7 01-2119463273-41-XXXX

Flammable liquid, Category 2, H225 Skin irritation, Category 2, H315 Specific target organ toxicity - single exposure, Category 3, H336 Aspiration hazard, Category 1, H304 Short-term (acute) aquatic hazard, Category 1, H400 Long-term (chronic) aquatic hazard, Category 1, H410

For the full text of the H-Statements mentioned in this Section, see Section 16.

3.2 Mixture

Not applicable

SECTION 4. First aid measures

4.1 Description of first aid measures

After inhalation: fresh air. Call in physician.

After skin contact: wash off with plenty of water. Remove contaminated clothing.

In case of skin contact: Take off immediately all contaminated clothing. Rinse skin with water/ shower.

After eye contact: rinse out with plenty of water with the eyelid held wide open. Call in ophthalmologist if necessary. Remove contact lenses.

After eye contact: rinse out with plenty of water. Remove contact lenses.

If swallowed Caution Aspiration hazard Keep respiratory tract clear. Call a physician immediately. In case of spontaneous vomiting: Risk of aspiration. Pulmonary failure possible. Call in physician.

4.2 Most important symptoms and effects, both acute and delayed

irritant effects, Cough, Nausea, Vomiting, Dizziness, Drowsiness, Stomach/intestinal disorders, gastric pain, respiratory paralysis, somnolence, Unconsciousness, collapse

Page 3 of 23



Catalogue No. Product name

4.3 Indication of any immediate medical attention and special treatment needed

No information available.

SECTION 5. Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media Carbon dioxide (CO2), Foam, Dry powder

Water, Foam, Carbon dioxide (CO2), Dry powder

Unsuitable extinguishing media For this substance/mixture no limitations of extinguishing agents are given.

5.2 Special hazards arising from the substance or mixture

Combustible. Vapours are heavier than air and may spread along floors. Forms explosive mixtures with air at ambient temperatures. Pay attention to flashback. Development of hazardous combustion gases or vapours possible in the event of fire.

5.3 Advice for firefighters

Special protective equipment for firefighters Stay in danger area only with self-contained breathing apparatus. Prevent skin contact by keeping a safe distance or by wearing suitable protective clothing.

Further information

Cool closed containers exposed to fire with water spray. Prevent fire extinguishing water from contaminating surface water or the ground water system.

Remove container from danger zone and cool with water. Prevent fire extinguishing water from contaminating surface water or the ground water system.

SECTION 6. Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Advice for non-emergency personnel: Do not breathe vapours, aerosols. Avoid substance contact. Ensure adequate ventilation. Keep away from heat and sources of ignition. Evacuate the danger area, observe emergency procedures, consult an expert.

Advice for emergency responders:

Protective equipment see section 8.

6.2 Environmental precautions

Do not let product enter drains. Risk of explosion.

6.3 Methods and materials for containment and cleaning up

Cover drains. Collect, bind, and pump off spills. Observe possible material restrictions (see sections 7 and 10). Take up carefully with liquid-absorbent material (e.g. Chemizorb®). Dispose of properly. Clean up affected area.

Page 4 of 23



Catalogue No.102827Product nameCyclohexane for liquid chromatography LiChrosolv®

6.4 Reference to other sections

Indications about waste treatment see section 13.

SECTION 7. Handling and storage 7.1 Precautions for safe handling

Advice on safe handling Work under hood. Do not inhale substance/mixture. Avoid generation of vapours/aerosols.

Observe label precautions.

Advice on protection against fire and explosion Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharge.

Hygiene measures

Immediately change contaminated clothing. Apply preventive skin protection. Wash hands and face after working with substance.

7.2 Conditions for safe storage, including any incompatibilities

Storage conditions

Keep container tightly closed in a dry and well-ventilated place. Keep away from heat and sources of ignition.

Recommended storage temperature see product label.

7.3 Specific end use(s)

See exposure scenario in the Annex to this MSDS.

SECTION 8. Exposure controls/personal protection

8.1 Control parameters



Catalogue No. Product name

102827 Cyclohexane for liquid chromatography LiChrosolv®

Derived No Effect Level (DNEL)

Worker DNEL, acute	Local effects	inhalation	700 mg/m ³
Worker DNEL, acute	Systemic effects	inhalation	700 mg/m³
Worker DNEL, longterm	Systemic effects	inhalation	700 mg/m ³
Worker DNEL, longterm	Systemic effects	dermal	2016 mg/kg Body weight
Worker DNEL, longterm	Local effects	inhalation	700 mg/m ³
Consumer DNEL, acute	Local effects	inhalation	412 mg/m ³
Consumer DNEL, acute	Systemic effects	inhalation	412 mg/m ³
Consumer DNEL, longterm	Local effects	inhalation	206 mg/m ³
Consumer DNEL,	Systemic effects	inhalation	206 mg/m ³
longterm Consumer DNEL,	Systemic effects	dermal	1186 mg/kg Body weight
longterm Consumer DNEL, longterm	Systemic effects	oral	59,4 mg/kg Body weight

Predicted No Effect Concentration (PNEC)

PNEC Fresh water	0,207 mg/l
PNEC Fresh water sediment	3,627 mg/kg
PNEC Marine water	0,207 mg/l
PNEC Aquatic intermittent release	0,207 mg/l
PNEC Sewage treatment plant	3,24 mg/l
PNEC Soil	2,99 mg/kg

8.2 Exposure controls

Engineering measures

Technical measures and appropriate working operations should be given priority over the use of personal protective equipment.

See section 7.1.

Individual protection measures

Protective clothing needs to be selected specifically for the workplace, depending on concentrations and quantities of the hazardous substances handled. The chemical resistance of the protective equipment should be enquired at the respective supplier.

Eye/face protection Safety glasses

Hand protection full contact:

Glove material: Glove thickness: Nitrile rubber 0,40 mm

Page 6 of 23



Catalogue No.	102827
Product name	Cyclohexane for liquid chromatography LiChrosolv®

Break through time: > 480 min

splash contact:

Glove material:	Nitrile rubber
Glove thickness:	0,11 mm
Break through time:	> 30 min

The protective gloves to be used must comply with the specifications of EC Directive 89/686/EEC and the related standard EN374, for example KCL 730 Camatril® - Velours (full contact), KCL 741 Dermatril® L (splash contact).

The breakthrough times stated above were determined by KCL in laboratory tests acc. to EN374 with samples of the recommended glove types.

This recommendation applies only to the product stated in the safety data sheet, supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

Other protective equipment

Flame retardant antistatic protective clothing.

Respiratory protection

required when vapours/aerosols are generated.

Recommended Filter type: Filter A (acc. to DIN 3181) for vapours of organic compounds

The entrepeneur has to ensure that maintenance, cleaning and testing of respiratory protective devices are carried out according to the instructions of the producer. These measures have to be properly documented.

Environmental exposure controls

Do not let product enter drains. Risk of explosion.

SECTION 9. Physical and chemical properties 9.1 Information on basic physical and chemical properties

Form	liquid
Colour	colourless
Odour	sweet
Odour Threshold	0,5 ppm
рН	Not applicable
Melting point	6,5 °C
Boiling point/boiling range	81 °C at 1.013 hPa



Page 7 of 23

Catalogue No. Product name	102827 Cyclohexane for liquid chromatography LiChrosolv®
Flash point	-18 °C Method: DIN 51755 Part 1
Evaporation rate	No information available.
Flammability (solid, gas)	No information available.
Lower explosion limit	1,2 %(V)
Upper explosion limit	8,3 %(V)
Vapour pressure	124 hPa at 24 °C
Relative vapour density	2,9
Density	0,78 g/cm3 at 20 °C
Relative density	No information available.
Water solubility	0,05 g/l at 20 °C
Partition coefficient: n- octanol/water	log Pow: 3,44 (25 °C) (experimental) Bioaccumulation is not expected.
Auto-ignition temperature	No information available.
Decomposition temperature	No information available.
Viscosity, dynamic	0,98 mPa.s at 20 °C
Explosive properties	Not classified as explosive.
Oxidizing properties	none
9.2 Other data	
Ignition temperature	260 °C
Viscosity, kinematic	1,26 mm2/s at 20 °C

SECTION 10. Stability and reactivity

10.1 Reactivity

Vapours may form explosive mixture with air.

Page 8 of 23



Catalogue No.102827Product nameCyclohexane for liquid chromatography LiChrosolv®

10.2 Chemical stability

The product is chemically stable under standard ambient conditions (room temperature) .

10.3 Possibility of hazardous reactions

Risk of explosion with:

nitrogen dioxide

Risk of ignition or formation of inflammable gases or vapours with: Strong oxidizing agents

10.4 Conditions to avoid

Warming.

10.5 Incompatible materials

rubber, various plastics

10.6 Hazardous decomposition products

no information available

SECTION 11. Toxicological information 11.1 Information on toxicological effects

Acute oral toxicity LD50 Rat: > 5.000 mg/kg OECD Test Guideline 401

Symptoms: gastric pain, Stomach/intestinal disorders Acute inhalation toxicity

LC50 Rat: > 33,88 mg/l; 4 h ; vapour OECD Test Guideline 403

Symptoms: Possible damages:, Irritation symptoms in the respiratory tract., Inhalation may lead to the formation of oedemas in the respiratory tract.

Acute dermal toxicity LD50 Rabbit: > 2.000 mg/kg OECD Test Guideline 402

Skin irritation Causes skin irritation.

Eye irritation Rabbit Result: No eye irritation OECD Test Guideline 405

Sensitisation Buehler Test Guinea pig Result: Does not cause skin sensitisation. Method: OECD Test Guideline 406

The life science business of Merck operates as MilliporeSigma in the US and Canada





Catalogue No. Product name

Germ cell mutagenicity Genotoxicity in vivo Chromosome aberration test Rat male and female inhalation (vapour) Bone marrow Result: negative Method: OECD Test Guideline 475

Genotoxicity in vitro Ames test Salmonella typhimurium Result: negative

(National Toxicology Program) In vitro mammalian cell gene mutation test Mouse lymphoma test Result: negative

(ECHA)

Carcinogenicity This information is not available.

Reproductive toxicity This information is not available.

Teratogenicity Application Route: Inhalation Rat Method: OECD Test Guideline 414

Application Route: Inhalation Rabbit Method: OECD Test Guideline 414

Specific target organ toxicity - single exposure May cause drowsiness or dizziness.

Specific target organ toxicity - repeated exposure This information is not available.

Aspiration hazard Aspiration may cause pulmonary oedema and pneumonitis.

11.2 Further information

After uptake of large quantities: Cough, Nausea, Vomiting, Dizziness, respiratory paralysis, Unconsciousness, collapse Damage to: Lungs

Page 10 of 23



The life science business of Merck operates as MilliporeSigma in the US and Canada

Catalogue No.102827Product nameCyclohexane for liquid chromatography LiChrosolv®

Other dangerous properties can not be excluded. Handle in accordance with good industrial hygiene and safety practice.

SECTION 12. Ecological information

12.1 Toxicity

Toxicity to fish flow-through test LC50 Pimephales promelas (fathead minnow): 4,53 mg/l; 96 h Analytical monitoring: yes OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates static test EC50 Daphnia magna (Water flea): 0,9 mg/l; 48 h Analytical monitoring: yes OECD Test Guideline 202

Toxicity to algae EC50 Pseudokirchneriella subcapitata (green algae): 3,4 mg/l; 72 h Analytical monitoring: yes OECD Test Guideline 201

Toxicity to bacteria IC50 Bacteria: 29 mg/l; 15 h (ECHA)

12.2 Persistence and degradability

Biodegradability 77 %; 28 d; aerobic OECD Test Guideline 301F Readily biodegradable

Theoretical oxygen demand (ThOD) 3.425 mg/g

(IUCLID)

12.3 Bioaccumulative potential

Partition coefficient: n-octanol/water log Pow: 3,44 (25 °C) (experimental)

Bioaccumulation is not expected.

12.4 Mobility in soil

No information available.

12.5 Results of PBT and vPvB assessment

Substance does not meet the criteria for PBT or vPvB according to Regulation (EC) No 1907/2006, Annex XIII.

12.6 Other adverse effects

Henry constant 19600 Pa*m³/mol (IUCLID) Distribution preferentially in air.

Additional ecological information Biological effects:

Page 11 of 23



Catalogue No.	102827
Product name	Cyclohexane for liquid chromatography LiChrosolv®

Endangers drinking-water supplies if allowed to enter soil and/or waters in large quantities. Change in the flavour characteristics of fish protein. Discharge into the environment must be avoided.

SECTION 13. Disposal considerations

Waste treatment methods See www.retrologistik.com for processes regarding the return of chemicals and containers, or contact us there if you have further questions.

SECTION 14. Transport information

Land transport (ADR/RID)			
14.1 UN number	UN 1145		
14.2 Proper shipping name	CYCLOHEXANE		
14.3 Class	3		
14.4 Packing group	II		
14.5 Environmentally hazardous	yes		
14.6 Special precautions for user	yes		
Tunnel restriction code	D/E		
Inland waterway transport (ADN) Not relevant			
Air transport (IATA)			
14.1 UN number	UN 1145		
14.2 Proper shipping name	CYCLOHEXANE		
14.3 Class	3		
14.4 Packing group	II		
14.5 Environmentally hazardous	yes		
14.6 Special precautions for user	no		
Sea transport (IMDG)			
14.1 UN number	UN 1145		
14.2 Proper shipping name	CYCLOHEXANE		
14.3 Class	3		
14.4 Packing group	II		
14.5 Environmentally hazardous	yes		

Page 12 of 23

The life science business of Merck operates as MilliporeSigma in the US and Canada



Catalogue No.102827Product nameCyclohexane for liquid chromatography LiChrosolv®

S-D

14.6 Special precautions	yes
for user	
EmS	F-E

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not relevant

SECTION 15. Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

<i>EU regulations</i> Major Accident Hazard Legislation	SEVESO III FLAMMABLE LIQUII P5c Quantity 1: 5.000 t Quantity 2: 50.000	:
	SEVESO III ENVIRONMENTAL H E1 Quantity 1: 100 t Quantity 2: 200 t	IAZARDS
Occupational restrictions	Take note of Dir 94 people at work.	/33/EC on the protection of young
Regulation (EC) No 1005/ that deplete the ozone lay		not regulated
Regulation (EC) No 850/2 European Parliament and April 2004 on persistent o and amending Directive 7	of the Council of 29 organic pollutants	not regulated
Substances of very high o	oncern (SVHC)	This product does not contain substances of very high concern according to Regulation (EC) No 1907/2006 (REACH), Article 57 above the respective regulatory concentration limit of ≥ 0.1 % (w/w).
<i>National legislation</i> Storage class	3	

15.2 Chemical safety assessment

For this product a chemical safety assessment was not carried out.



Catalogue No.102827Product nameCyclohexane for liquid chromatography LiChrosolv®

SECTION 16. Other information

Full text of H-Statements referred to under sections 2 and 3.

H225	Highly flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.

Training advice

Provide adequate information, instruction and training for operators.

Labelling

Hazard pictograms



Signal word Danger

Hazard statements H225 Highly flammable liquid and vapour. H304 May be fatal if swallowed and enters airways. H315 Causes skin irritation. H336 May cause drowsiness or dizziness. H410 Very toxic to aquatic life with long lasting effects.

Precautionary statements

Prevention P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking. P240 Ground/bond container and receiving equipment. P273 Avoid release to the environment. Response P301 + P330 + P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. P302 + P352 IF ON SKIN: Wash with plenty of soap and water. P313 Get medical advice/ attention. Storage P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

Key or legend to abbreviations and acronyms used in the safety data sheet

Used abbreviations and acronyms can be looked up at www.wikipedia.org.

Page 14 of 23



Catalogue No. Product name 102827 Cyclohexane for liquid chromatography LiChrosolv®

Regional representation

This information is given on the authorised Safety Data Sheet for your country.

The information contained herein is based on the present state of our knowledge. It characterises the product with regard to the appropriate safety precautions. It does not represent a guarantee of any properties of the product.



Catalogue No. Product name

EXPOSURE SCENARIO 1 (Industrial use)

1. Industrial use Analytical and preparative chromatography)

Sectors of end-use

- *SU 3* Industrial uses: Uses of substances as such or in preparations at industrial sites
- SU9 Manufacture of fine chemicals
- *SU 10* Formulation [mixing] of preparations and/ or re-packaging (excluding alloys)

Chemical product category

- PC19 Intermediate
- PC21 Laboratory chemicals

Process categories

- *PROC1* Use in closed process, no likelihood of exposure
- *PROC2* Use in closed, continuous process with occasional controlled exposure
- *PROC3* Use in closed batch process (synthesis or formulation)
- *PROC4* Use in batch and other process (synthesis) where opportunity for exposure arises
- *PROC5* Mixing or blending in batch processes for formulation of preparations and articles (multistage and/ or significant contact)
- *PROC8a* Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at non-dedicated facilities
- *PROC8b* Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at dedicated facilities
- *PROC9* Transfer of substance or preparation into small containers (dedicated filling line, including weighing)
- PROC10 Roller application or brushing
- PROC15 Use as laboratory reagent

Environmental Release Categories

- *ERC1* Manufacture of substances
- *ERC2* Formulation of preparations
- *ERC4* Industrial use of processing aids in processes and products, not becoming part of articles
- *ERC6a* Industrial use resulting in manufacture of another substance (use of intermediates)

2. Contributing scenarios: Operational conditions and risk management measures 2.1 Contributing scenario controlling environmental exposure for: ERC1, ERC4, SpERC ESVOC 2

Environment factors not influenced by risk management

Dilution Factor ((River)	10
Dilution Factor ((Coastal Areas)	100

Other given operational conditions affecting environmental exposure

Number of emission days per 300

Page 16 of 23



Catalogue No.	102827
Product name	Cyclohexane for liquid chromatography LiChrosolv®
year Fraincian an Dalagan Fratam	0.2.0/
Emission or Release Factor: Air	0,2 %
Emission or Release Factor: Water	0,03 %
Emission or Release Factor:	0,1 %
Soil	
Technical conditions and meas	sures / Organizational measures
Air	Use of air emission abatement equipments.
	Effectiveness (of a measure): 90 %
Conditions and measures relat	ed to municipal sewage treatment plant
Type of Sewage Treatment Plant	Municipal sewage treatment plant
Effectiveness (of a measure)	96,6 %
Sludge Treatment	Sewage sludge should not be applied to natural soils.
2.2 Contributing cooperio cont	rolling environmental exposure for: ERC2, SpERC ESVOC 4
2.2 Contributing Scenario Cont	
Amount used	
Annual amount per site	1.714 kg
(Msafe)	
Environment factors not influe	enced by risk management
Dilution Factor (River)	10
Dilution Factor (Coastal Areas)	100
Other given operational condit	tions affecting environmental exposure
Number of emission days per	300
year	
Emission or Release Factor: Air	2,5 %
Emission or Release Factor:	0,02 %
Water Emission or Release Factor:	0,01 %
Soil	0,01 /0
Conditions and measures relat	ed to municipal sewage treatment plant
Type of Sewage Treatment	Municipal sewage treatment plant
Plant	
Effectiveness (of a measure)	96,6 %
Sludge Treatment	Sewage sludge should not be applied to natural soils.
2.3 Contributing scenario cont	rolling environmental exposure for: ERC6a, SpERC ESVOC
43	

Environment factors not influenced by risk management Dilution Factor (River) 10

Page 17 of 23



Catalogue No. Product name	102827 Cyclohexane for liquid chromatography LiChrosolv®
Troduct fiame	
Dilution Factor (Coastal Areas)	100
Other given operational condit	ions affecting environmental exposure
Number of emission days per year	300
Émission or Release Factor: Air	0,2 %
Emission or Release Factor: Water	0,03 %
Emission or Release Factor: Soil	0,01 %
Conditions and measures relat	ed to municipal sewage treatment plant
Type of Sewage Treatment Plant	Municipal sewage treatment plant
Effectiveness (of a measure)	96,6 %
Sludge Treatment	Sewage sludge should not be applied to natural soils.

2.4 Contributing scenario controlling worker exposure for: PROC1, PROC2, PROC3, PROC4, PROC8b, PROC15

Product characteristics

Concentration of the	Covers the percentage of the substance in the product
Substance in Mixture/Article	up to 100 % (unless stated differently).
Physical Form (at time of use)	High volatile liquid

Frequency and duration of use

Frequency of use

8 hours/day

Other operational conditions affecting workers exposure

Outdoor / Indoor Indoor Indoor without local exhaust ventilation (LEV)

Organisational measures to prevent /limit releases, dispersion and exposure Covers daily exposures up to 8 hours.

Additional good practice advice beyond the REACH Chemical Safety Assessment

Additional good practice Wear suitable gloves tested to EN374. advice

2.5 Contributing scenario controlling worker exposure for: PROC5, PROC8a, PROC9, PROC10

Product characteristics	
Concentration of the	Covers the percentage of the substance in the product
Substance in Mixture/Article	up to 100 % (unless stated differently).
Physical Form (at time of use)	High volatile liquid

Frequency and duration of use Frequency of use

8 hours/day

Page 18 of 23

The life science business of Merck operates as $\ensuremath{\mathsf{MilliporeSigma}}$ in the US and Canada



Catalogue No.	102827
Product name	Cyclohexane for liquid chromatography LiChrosolv®

Other operational conditions affecting workers exposure

Outdoor / Indoor

Indoor with local exhaust ventilation (LEV)

Organisational measures to prevent /limit releases, dispersion and exposure Covers daily exposures up to 8 hours.

Additional good practice advice beyond the REACH Chemical Safety Assessment

Additional good practice Wear suitable gloves tested to EN374. advice

3. Exposure estimation and reference to its source

Environment

CS	Use descriptor	Msafe	Compartment	RCR	Exposure Assessment Method
2.1	ERC1, ERC4		All compartments	< 1	EUSES
2.2	ERC2	1714 kg/day	All compartments	< 1	EUSES
2.3	ERC6a		All compartments	< 1	EUSES

Workers

CS	Use descriptor	Exposure duration, route, effect	RCR	Exposure Assessment Method
2.4	PROC1	longterm, combined, systemic	< 1	ECETOC TRA
2.4	PROC2	longterm, combined, systemic	< 1	ECETOC TRA
2.4	PROC3	longterm, combined, systemic	< 1	ECETOC TRA
2.4	PROC4	longterm, combined, systemic	< 1	ECETOC TRA
2.4	PROC8b	longterm, combined, systemic	< 1	ECETOC TRA
2.4	PROC15	longterm, combined, systemic	< 1	ECETOC TRA
2.5	PROC5	longterm, combined, systemic	< 1	ECETOC TRA
2.5	PROC8a	longterm, combined, systemic	< 1	ECETOC TRA
2.5	PROC9	longterm, combined, systemic	< 1	ECETOC TRA
2.5	PROC10	longterm, combined, systemic	< 1	ECETOC TRA

The default parameters and -efficiencies of the applied exposure assessment model were used for the calculation (unless stated differently).



Catalogue No. Product name

4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the Exposure Scenario

Please refer to the following documents: ECHA Guidance on information requirements and chemical safety assessment Chapter R.12: Use descriptor system; ECHA Guidance for downstream users; ECHA Guidance on information requirements and chemical safety assessment Part D: Exposure Scenario Building, Part E: Risk Characterisation and Part G: Extending the SDS; VCI/Cefic REACH Practical Guides on Exposure Assessment and Communications in the Supply Chain; CEFIC Guidance Specific Environmental Release Categories (SPERCs).

For scaling of worker exposure assessments performed with ECETOC TRA, please consult the Merck tool ScIDeEx® at www.merckmillipore.com/scideex.



Catalogue No.102827Product nameCyclohexane for liquid chromatography LiChrosolv®

EXPOSURE SCENARIO 2 (Professional use)

1. Professional use Analytical and preparative chromatography)

Sectors of end-use

SU 22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Chemical product category

PC21 Laboratory chemicals

Process categories

PROC15 Use as laboratory reagent

Environmental Release Categories

ERC2 Formulation of preparationsERC6a Industrial use resulting in manufacture of another substance (use of intermediates)

2. Contributing scenarios: Operational conditions and risk management measures

2.1 Contributing scenario controlling environmental exposure for: ERC2, SpERC ESVOC 4

Amount used

Annual amount per site 1.714 kg (Msafe)

Environment factors not influenced by risk management

Dilution Factor (River)	10
Dilution Factor (Coastal Areas)	100

Other given operational conditions affecting environmental exposure

Number of emission days per	300
year	
Emission or Release Factor:	2,5 %
Air Emission or Release Factor:	
Water	0,02 %
Emission or Release Factor:	0,01 %
Soil	-,

Conditions and measures related to municipal sewage treatment plant

Type of Sewage Treatment Plant	Municipal sewage treatment plant
Effectiveness (of a measure)	96,6 %
Sludge Treatment	Sewage sludge should not be applied to natural soils.

2.2 Contributing scenario controlling environmental exposure for: ERC6a, SpERC ESVOC 43

Environment factors not influenced by risk management

Page 21 of 23



Catalogue No. Product name	102827 Cyclohexane for liquid chromatography LiChrosolv®		
Dilution Factor (River)	10		
Dilution Factor (Coastal Areas)	100		
Other given operational conditions affecting environmental exposure			
Number of emission days per	300		
year			
Emission or Release Factor: Air	0,2 %		
Emission or Release Factor: Water	0,03 %		
Emission or Release Factor:	0,01 %		
Soil			
Conditions and measures relat	ed to municipal sewage treatment plant		
Type of Sewage Treatment Plant	Municipal sewage treatment plant		
Effectiveness (of a measure)	96,6 %		
Sludge Treatment	Sewage sludge should not be applied to natural soils.		

2.3 Contributing scenario controlling worker exposure for: PROC15

Product characteristics

Concentration of the	Covers the percentage of the substance in the product
Substance in Mixture/Article	up to 100 % (unless stated differently).
Physical Form (at time of use)	High volatile liquid

Frequency and duration of use

Frequency of use 8	hours/day
--------------------	-----------

Other operational conditions affecting workers exposure

Outdoor / Indoor Indoor Indoor without local exhaust ventilation (LEV)

Organisational measures to prevent /limit releases, dispersion and exposure Covers daily exposures up to 8 hours.

Additional good practice advice beyond the REACH Chemical Safety Assessment

Additional good practice Wear suitable gloves tested to EN374. advice

3. Exposure estimation and reference to its source

Environment

CS	Use descriptor	Msafe	Compartment	RCR	Exposure Assessment Method
2.1	ERC2	1714 kg/day	All compartments	< 1	EUSES
2.2	ERC6a		All compartments	< 1	EUSES

Page 22 of 23



	ogue No. Ict name	102827 Cyclohexane for liquid chromatography LiChrosolv®		
Workers				
CS	Use descriptor	Exposure duration, route, effect	RCR	Exposure Assessment Method
2.3	PROC15	longterm, combined, systemic	< 1	ECETOC TRA

4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the Exposure Scenario

Please refer to the following documents: ECHA Guidance on information requirements and chemical safety assessment Chapter R.12: Use descriptor system; ECHA Guidance for downstream users; ECHA Guidance on information requirements and chemical safety assessment Part D: Exposure Scenario Building, Part E: Risk Characterisation and Part G: Extending the SDS; VCI/Cefic REACH Practical Guides on Exposure Assessment and Communications in the Supply Chain; CEFIC Guidance Specific Environmental Release Categories (SPERCs).

For scaling of worker exposure assessments performed with ECETOC TRA, please consult the Merck tool ScIDeEx $\mbox{\ensuremath{\mathbb{R}}}$ at www.merckmillipore.com/scideex.

The branding on the header and/or footer of this document may temporarily not visually match the product purchased as we transition our branding. However, all of the information in the document regarding the product remains unchanged and matches the product ordered. For further information please contact mlsbranding@sial.com.

