

Page 1/11

Tel: 800-227-9770

# Safety Data Sheet acc. to OSHA HCS

Printing date 10/23/2020 Reviewed on 10/23/2020

### 1 Identification

- · Product identifier
- · Product name: Arsenic Standard: 1000 µg/mL As in 5% HNO3 [500ml bottle]
- · Part number: 5190-8247

**Agilent Technologies** 

- · Application of the substance / the mixture Reagents and Standards for Analytical Chemical Laboratory Use
- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Agilent Technologies, Inc. 5301 Stevens Creek Blvd Santa Clara, CA 95051,

USA

- · Information department: e-mail: pdl-msds\_author@agilent.com
- · Emergency telephone number: CHEMTREC®: 1-800-424-9300

# 2 Hazard(s) identification

· Classification of the substance or mixture



GHS08 Health hazard

Carc. 1A H350 May cause cancer.



GHS05 Corrosion

Met. Corr.1 H290 May be corrosive to metals.

Eye Dam. 1 H318 Causes serious eye damage.



Skin Irrit. 2 H315 Causes skin irritation.

- · Label elements
- · GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms





GHS05

GHS08

- · Signal word Danger
- · Hazard-determining components of labeling:

Nitric acid

Arsenic

· Hazard statements

H290 May be corrosive to metals.

H315 Causes skin irritation.

(Contd. on page 2)





Printing date 10/23/2020 Reviewed on 10/23/2020

# Product name: Arsenic Standard: 1000 µg/mL As in 5% HNO3 [500ml bottle]

(Contd. of page 1)

H318 Causes serious eye damage.

H350 May cause cancer.

· Precautionary statements

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P310 Immediately call a poison center/doctor. P321 Specific treatment (see on this label).

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

- · Classification system:
- · NFPA ratings (scale 0 4)



Health = 3 Fire = 0Reactivity = 0

· HMIS-ratings (scale 0 - 4)



- · Other hazards
- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.

### 3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · Description: Aqueous solution.

· Dangerous components:		
	Nitric acid	<5%
RTECS: QU5775000	🕸 Ox. Liq. 2, H272; <page-header></page-header>	
CAS: 7440-38-2	Arsenic	<0.25%
RTECS: CG 0525000	Acute Tox. 3, H301; Acute Tox. 3, H331; <b>&amp;</b> Carc. 1A, H350; Aquatic Acute 1, H400; Aquatic Chronic 1, H410	

### · Additional information:

The concentration of the acid stated in this SDS is calculated as an absolute mass concentration (%w/v). This is less than the acid concentration stated on the product label and COA, which reflects a percent value of the commercially available concentrated aqueous form of the acid.

### 4 First-aid measures

- · Description of first aid measures
- General information: Immediately remove any clothing soiled by the product.
- · After inhalation: Supply fresh air; consult doctor in case of complaints.

(Contd. on page 3)





Printing date 10/23/2020 Reviewed on 10/23/2020

# Product name: Arsenic Standard: 1000 µg/mL As in 5% HNO3 [500ml bottle]

(Contd. of page 2)

· After skin contact:

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

- · After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- · After swallowing: Rinse mouth. Do not induce vomiting.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed No further relevant information available.

### 5 Fire-fighting measures

- · Extinguishing media
- $\cdot \textit{Suitable extinguishing agents: } \textit{Use fire fighting measures that suit the environment.}$
- · Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

- · Advice for firefighters
- · Protective equipment: Wear self-contained respiratory protective device.

### 6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

· Environmental precautions:

Dilute with plenty of water.

Do not allow to enter sewers/ surface or ground water.

· Methods and material for containment and cleaning up:

Use neutralizing agent.

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

Absorb liquid components with liquid-binding material.

DO NOT USE SAWDUST.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

· Protective Action Criteria for Chemicals

· Froiective Action Crueria for Chemicais	
· PAC-1:	
CAS: 7697-37-2 Nitric acid	0.16 ppm
CAS: 7440-38-2 Arsenic	1.5 mg/m <sup>3</sup>
· PAC-2:	
CAS: 7697-37-2 Nitric acid	24 ppm
CAS: 7440-38-2 Arsenic	17 mg/m <sup>3</sup>
· PAC-3:	
CAS: 7697-37-2 Nitric acid	92 ppm
'	(Contd. on page





Printing date 10/23/2020 Reviewed on 10/23/2020

Product name: Arsenic Standard: 1000 µg/mL As in 5% HNO3 [500ml bottle]

 CAS: 7440-38-2
 Arsenic
 (Contd. of page 3)

 100 mg/m³
 100 mg/m³

### 7 Handling and storage

- · Handling:
- · Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Store in cool, dry place in tightly closed receptacles.

Open and handle receptacle with care.

- · Information about protection against explosions and fires: Keep respiratory protective device available.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles:

Please refer to the manufacturers certificate for specific storage and transport temperature conditions.

Store only in the original receptacle unless other advice is given on the CoA.

Keep container in a well-ventilated place. Keep away from sources of ignition and heat.

- · Information about storage in one common storage facility: Store away from foodstuffs.
- · Further information about storage conditions: Keep receptacle tightly sealed.
- $\cdot$  *Specific end use*(s) *No further relevant information available.*

### 8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters

· Components with limit values	that require mon	itoring at th	e workplace:
--------------------------------	------------------	---------------	--------------

# CAS: 7697-37-2 Nitric acid

PEL Long-term value: 5 mg/m³, 2 ppm

REL Short-term value: 10 mg/m<sup>3</sup>, 4 ppm

Long-term value: 5 mg/m³, 2 ppm

TLV Short-term value: 10 mg/m³, 4 ppm

Long-term value: 5.2 mg/m³, 2 ppm

### CAS: 7440-38-2 Arsenic

PEL Long-term value: 0.5 0.01 mg/m<sup>3</sup>

as As; organicinorg. compds.; 29 CFR 1910.1018

REL Ceiling limit value: 0.002 mg/m³

as As; 15min; See Pocket Guide App. A

TLV Long-term value: 0.01 mg/m<sup>3</sup>

as As; BEI

### · Ingredients with biological limit values:

### CAS: 7440-38-2 Arsenic

BEI 35 µg As/L

Medium: urine

Time: end of workweek

Parameter: Inorganic arsenic plus methylated metabolites (background)

· Additional information: The lists that were valid during the creation were used as basis.

(Contd. on page 5)





Printing date 10/23/2020 Reviewed on 10/23/2020

Product name: Arsenic Standard: 1000 µg/mL As in 5% HNO3 [500ml bottle]

(Contd. of page 4)

- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the skin.

Avoid contact with the eyes and skin.

#### · Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

#### · Protection of hands:

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

The protective gloves to be used must comply with the specifications of EC Directive 89/686/EEC and the related standard EN374



Protective gloves

#### · Material of gloves

PVC gloves

Neoprene gloves

#### · Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

### 9 Physical and chemical properties

- · Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form: Liquid
Color: Colorless

Odor: Odorless

Odor threshold: Not determined.

· pH-value at 20 °C (68 °F): < 2

· Change in condition

Melting point/Melting range: Not determined.
Not determined.

(Contd. on page 6)





Printing date 10/23/2020 Reviewed on 10/23/2020

Product name: Arsenic Standard: 1000 µg/mL As in 5% HNO3 [500ml bottle]

	(Contd. of I	page
Boiling point/Boiling range:	100 °C (212 °F)	
· Flash point:	Not applicable.	
· Flammability (solid, gaseous):	Not determined.	
· Ignition temperature:	Not determined	
· Decomposition temperature:	Not determined.	
· Auto igniting:	Product is not selfigniting.	
· Danger of explosion:	Not determined.	
· Explosion limits:		
Lower:	Not determined.	
Upper:	Not determined.	
· Vapor pressure at 20 °C (68 °F):	23 hPa (17.3 mm Hg)	
· Density at 20 °C (68 °F):	1.02736 g/cm³ (8.57332 lbs/gal)	
· Relative density	Not determined.	
· Vapor density	Not determined.	
· Evaporation rate	Not determined.	
· Solubility in / Miscibility with		
Water:	Fully miscible.	
· Partition coefficient (n-octanol/wate	er): Not determined.	
· Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
· Other information	No further relevant information available.	

# 10 Stability and reactivity

· Reactivity

Stable under normal conditions.

No further relevant information available.

- · Chemical stability Stable under normal conditions.
- · Thermal decomposition / conditions to be avoided:

Formation of toxic gases is possible during heating or in case of fire.

- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid Heat.
- · Incompatible materials:

Strong oxidizing agents.

Metals.

· Hazardous decomposition products: Formation of toxic gases is possible during heating or in case of fire.

US





Printing date 10/23/2020 Reviewed on 10/23/2020

Product name: Arsenic Standard: 1000 µg/mL As in 5% HNO3 [500ml bottle]

(Contd. of page 6)

### 11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- · LD/LC50 values that are relevant for classification:

CAS: 7697-37-2 Nitric acid

Inhalative LC50/4 h 130 mg/l (rat)

- · Primary irritant effect:
- · on the skin: Irritant to skin and mucous membranes.
- · on the eye: Strong irritant with the danger of severe eye injury.
- · Sensitization: Based on available data, the classification criteria are not met.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

Irritant

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)	
CAS: 7440-38-2   Arsenic	1
· NTP (National Toxicology Program)	
CAS: 7440-38-2   Arsenic	K
· OSHA-Ca (Occupational Safety & Health Administration)	
CAS: 7440-38-2   Arsenic	

## 12 Ecological information

- · Toxicity
- · Aquatic toxicity:

CAS: 7697-37-2 Nitric acid

LC50/48 180 mg/l (crustacean)

- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 3 (Self-assessment): extremely hazardous for water

Do not allow product to reach ground water, water course or sewage system, even in small quantities.

Must not reach bodies of water or drainage ditch undiluted or unneutralized.

Danger to drinking water if even extremely small quantities leak into the ground.

Rinse off of bigger amounts into drains or the aquatic environment may lead to decreased pH-values. A low pH-value harms aquatic organisms. In the dilution of the use-level the pH-value is considerably increased, so that after the use of the product the aqueous waste, emptied into drains, is only low water-dangerous.

- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.

(Contd. on page 8)





Printing date 10/23/2020 Reviewed on 10/23/2020

Product name: Arsenic Standard: 1000 µg/mL As in 5% HNO3 [500ml bottle]

(Contd. of page 7)

· Other adverse effects No further relevant information available.

### 13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · Recommendation: Dispose in accordance with national regulations.
- · Recommended cleansing agent: Water, if necessary with cleansing agents.

### 14 Transport information

	TTAT	<b>A</b> 7 .	1	
•	UN-	/VU	mr	ver

· DOT, ADR, IMDG, IATA UN3264

• **DOT** Corrosive liquid, acidic, inorganic, n.o.s. (Nitric acid)

· ADR 3264 CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S.

(NITRIC ACID)

· IMDG, IATA CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (NITRIC

ACID)

- · Transport hazard class(es)
- $\cdot DOT$



· Class 8 Corrosive substances

· Label

· ADR, IMDG, IATA



· Class 8 Corrosive substances

· Label

· Packing group

· DOT, ADR, IMDG, IATA III

• Environmental hazards: Not applicable.

· Special precautions for user Warning: Corrosive substances

· Danger code (Kemler): 80

• EMS Number: F-A,S-B
• Segregation groups Acids

· Stowage Category

(Contd. on page 9)





Printing date 10/23/2020 Reviewed on 10/23/2020

Product name: Arsenic Standard: 1000 µg/mL As in 5% HNO3 [500ml bottle]

· Stowage Code	SW2 Clear of living quarters.
· Transport in bulk according to Annex MARPOL73/78 and the IBC Code	II of Not applicable.
· Transport/Additional information:	ног аррисанс.
· ADR · Excepted quantities (EQ)	Code: E1
(	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
· UN ''Model Regulation'':	UN 3264 CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O (NITRIC ACID), 8, III

# 15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Sara
- · Section 355 (extremely hazardous substances):

CAS: 7697-37-2 Nitric acid

· Section 313 (Specific toxic chemical listings):

CAS: 7697-37-2 Nitric acid

CAS: 7440-38-2 Arsenic

· TSCA (Toxic Substances Control Act):

All components have the value ACTIVE.

· Hazardous Air Pollutants

None of the ingredients is listed.

- · Proposition 65
- · Chemicals known to cause cancer:

CAS: 7440-38-2 Arsenic

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

- · Carcinogenic categories
- · EPA (Environmental Protection Agency)

CAS: 7440-38-2 Arsenic

 $\boldsymbol{A}$ 

· TLV (Threshold Limit Value established by ACGIH)

CAS: 7440-38-2 Arsenic

A1

· NIOSH-Ca (National Institute for Occupational Safety and Health)

CAS: 7440-38-2 Arsenic

(Contd. on page 10)



Page 10/11

# Safety Data Sheet acc. to OSHA HCS

Printing date 10/23/2020 Reviewed on 10/23/2020

Product name: Arsenic Standard: 1000 µg/mL As in 5% HNO3 [500ml bottle]

(Contd. of page 9)

### · Hazard pictograms





**Agilent Technologies** 

GHS05 GHS0

- · Signal word Danger
- · Hazard-determining components of labeling:

Nitric acid

Arsenic

#### · Hazard statements

H290 May be corrosive to metals.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H350 May cause cancer.

#### · Precautionary statements

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P310 Immediately call a poison center/doctor. P321 Specific treatment (see on this label).

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

#### · National regulations:

#### · Information about limitation of use:

Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation. Exceptions can be made by the authorities in certain cases.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

## 16 Other information

The information contained in this document is based on Agilent's state of knowledge at the time of preparation. No warranty as to its accurateness, completeness or suitability for a particular purpose is expressed or implied.

#### · Date of preparation / last revision 10/23/2020 / -

#### · Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

(Contd. on page 11)



Page 11/11

# Safety Data Sheet acc. to OSHA HCS

Printing date 10/23/2020 Reviewed on 10/23/2020

# Product name: Arsenic Standard: 1000 µg/mL As in 5% HNO3 [500ml bottle]

(Contd. of page 10)

vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health
TLV: Threshold Limit Value
PEL: Permissible Exposure Limit
REL: Recommended Exposure Limit
BEI: Biological Exposure Limit
Ox. Liq. 2: Oxidizing liquids — Category 2
Met. Corr.1: Corrosive to metals — Category 1

**Agilent Technologies** 

Met. Corr.1: Corrosive to metals – Category 1 Acute Tox. 3: Acute toxicity – Category 3 Skin Corr. 1A: Skin corrosion/irritation – Category 1A Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

Carc. 1A: Carcinogenicity - Category 1A

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1 Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1

· Sources

Tables 3.1 and 3.2 from Annex 6 of EC 1272/2008, EC 1907/2006, EH40/2005 as amended 2011, Registry of Toxic Effects of Chemical Substances (RTECS), The Dictionary of Substances and their Effects, 1st Edition, IUCLID.

· Data compared to the previous version altered. All sections have been updated.

US