

according to Regulations 1907/2006/EC (REACh) and 2015/830/EU

NANOCOLOR Nitrite Page: 1/10

Printing date: 01.10.2019 Date of issue: 15.03.2019

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 **Product identifier**

REF 91867

Product name NANOCOLOR Nitrite

REACH Registration number(s): see SECTION 3.1/3.2 or
A registration number for the substance(s) does not exist because the annual tonnage does not require registration or

the substance or its use is excluded from registration.

2 x 100 mL Nitrite R1 2 x 100 mL Nitrite R2

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses

Product for analytical use.

Exposure Scenario Classification according REACh, RIP 3.2 Codes: SU 0-2, PC 21, PROC 15, AC 0

The exposure scenario is integrated into sections 1-16.

Uses advised against

not described

1.3 Details of the supplier of the safety data sheet

Manufactured by:

MACHEREY-NAGEL GmbH & Co. KG

Neumann-Neander-Str. 6-8, 52355 Dueren, GERMANY

Tel.: +49 2421 969 0 E-mail: sds@mn-net.com (msds@mn-net.com)

1.4 Emergency telephone number

Outside Germany (DE): Call your regional Poisons Information Service or call local Life Saving Service. DE: Gemeinsames Giftinformationszentrum (GGIZ) 99089 Erfurt tel. +49 361 730 730

You find our current versions of SDS (22 languages) in Internet: http://www.mn-net.com/SDS

SECTION 2: Hazard identification

2.0 Classification of the complete product





GHS05 GHS07

DANGER Signal word

Hazard identification	Hazard classes/categories
H314	Skin Corr. 1B
H315	Skin Irrit. 2
H317	Skin Sens. 1
H319	Eye Irrit. 2

2.1 Classification of the substance or mixture

100 mL Nitrite R1



www.mn-net.com

US:

ACHEREY-NAGE (MN

MACHEREY-NAGEL GmbH & Co. KG · Neumann-Neander-Str. 6-8 · 52355 Düren · Germany

DE/international: CH: FR:

Tel.: +49 24 21 969-0 Tel.: +41 62 388 55 00 Tel.: +33 388 68 22 68 Tel.: +1 484 821 0984 Fax: +49 24 21 969-199 Fax: +41 62 388 55 05 Fax: +33 388 51 76 88 Fax: +1 484 821 1272 Version: M V 4.10.1 E-mail: info@mn-net.com E-mail: sales-ch@mn-net.com E-mail: sales-fr@mn-net.com E-mail: sales-us@mn-net.com



according to Regulations 1907/2006/EC (REACh) and 2015/830/EU

NANOCOLOR Nitrite Page: 2/10 Printing date: 01.10.2019 Date of issue: 15.03.2019

> Signal word WARNING

Hazard identification	Hazard classes/categories
H315	Skin Irrit. 2
H317	Skin Sens. 1
H319	Eye Irrit. 2

100 mL Nitrite R2



DANGER

Hazard identification Hazard classes/categories H314 Skin Corr. 1B

2.2 Label elements

According CLP directive inner packages must be only labelled with GHS symbol(s) and product identificator(s) (EU 1272/2008 Annex I - 1.5.1.2).

Harmful chemicals/mixtures with signal word: WARNING must not be labelled with H and P phrases until 125 mL (EU 1272/2008 Annex I - 1.5.2). This labelling exemption is NOT valid for sensibilizing substances.

100 mL Nitrite R1



Signal word

GHS07

Signal word: WARNING

May cause an allergic skin reaction.

Avoid breathing dust/vapours. Wear protective gloves/eye protection.

100 mL Nitrite R2



Signal word: DANGER

H314

Causes severe skin burns and eye damage.

P260sh, P280sh, P303+361+353, P305+351+338, P310

Do not breathe dust/vapours. Wear protective gloves/eye protection. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower]. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/doctor.

2.3 Other hazards

Possible hazards from physicochemical properties

Generally in the case of pH values are less than 2 or higher than 11.5 then it is corrosive. In the case of pH values are less than 5 or higher than 9 then it is irritant. ---

www.mn-net.com

US:



MACHEREY-NAGEL GmbH & Co. KG · Neumann-Neander-Str. 6-8 · 52355 Düren · Germany

DE/international: CH: FR:

Tel.: +49 24 21 969-0 Tel.: +41 62 388 55 00 Tel.: +33 388 68 22 68 Tel.: +1 484 821 0984 Fax: +49 24 21 969-199 Fax: +41 62 388 55 05 Fax: +33 388 51 76 88 +1 484 821 1272 Version: M V 4.10.1 E-mail: info@mn-net.com E-mail: sales-ch@mn-net.com E-mail: sales-fr@mn-net.com E-mail: sales-us@mn-net.com



according to Regulations 1907/2006/EC (REACh) and 2015/830/EU

NANOCOLOR Nitrite Page: 3/10

Printing date: 01.10.2019 Date of issue: 15.03.2019

Information pertaining to particular risks to human and possible symptoms

Causes varying degrees of acid burns on the skin, to the eyes and to the mucous membranes and wounds which do not heal quickly depending on the concentration, temperature and the exposure time. Vapours especially which steam from hot liquids and mist can have a severe irritant effect upon the eyes and the respiratory organs.

Cause after skin contact, impairments of health when ingested in small quantities. May cause sensitization by skin contact, also in repeated contact of small amounts.

Information pertaining to particular risks to the environment

Avoid contact of substance/mixture to environment.

not applicable vPvB: not applicable

Other hazards

SECTION 3: Composition/information on ingredients

Substances or 3.2 Mixtures

100 mL Nitrite R1

Chemical: sulfanilic acid CAS No.: 121-57-3

Classification: H315, Skin Irrit. 2, H317, Skin Sens. 1, H319, Eye Irrit. 2

Formula: C₆ H₇ NO₃ S

Pseudonym: 4-aminobenzene sulfonic acid

TSCA Inventory: listed

REACH Reg. No.: 01-2119541820-45-xxxx

204-482-5 EC No.: Indice No.: 612-014-00-X RTECS: WP3895500 MFCD: 00007886

KF-01192 KF No . Concentration: 0.1 - <1 % acc. CLP (GHS): H317, Skin Sens. 1

Chemical: CAS No.: 64-19-7 acetic acid

Classification: H226, Flam. Liq. 3, H314, Skin Corr. 1B

Formula: C₂ H₄ O₂; CH₃-COOH

TSCA Inventory: listed

REACH Reg. No.: 01-2119475328-30-xxxx

EC No.: 200-580-7 Indice No.: 607-002-00-6 RTECS: MFCD: AF1225000 00036152

KE No.: KE-00013

Concentration: 10 - < 25 %

acc. CLP (GHS): H315, Skin Irrit. 2, H319, Eye Irrit. 2

100 mL Nitrite R2

Chemical: CAS No.: 134-32-7 1-naphthylamine

Classification: No criteria for classification or naming of chemical not required. Formula:

 $C_{10}\,H_9\,N$ 1-naphthalenamine Pseudonym:

TSCA Inventory: listed

REACH Reg. No.: as intermediate

EC No.: 612-020-00-2 205-138-7 Indice No.: RTECS: QM1400000 MFCD: 00004016

KE No.: KE-25544 Concentration: < 0.10 %

acc. CLP (GHS): The criteria for classification are not fulfilled.

Chemical: acetic acid CAS No.: 64-19-7

Classification: H226, Flam. Liq. 3, H314, Skin Corr. 1B

Formula: C₂ H₄ O₂; CH₃-COOH TSCA Inventory: listed

REACH Reg. No.: 01-2119475328-30-xxxx

200-580-7 607-002-00-6 EC No.: Indice No.: RTECS: AF1225000 00036152 MFCD:

KE No .: KE-00013 Concentration: 25 - < 50 % acc. CLP (GHS): H314, Skin Corr. 1B

www.mn-net.com

US:

MACHEREY-NAGE **(MN)**

MACHEREY-NAGEL GmbH & Co. KG · Neumann-Neander-Str. 6-8 · 52355 Düren · Germany

DE/international: CH: FR:

Tel.: +49 24 21 969-0 Tel.: +41 62 388 55 00 Tel.: +33 388 68 22 68 Tel.: +1 484 821 0984 Fax: +49 24 21 969-199 Fax: +41 62 388 55 05 Fax: +33 388 51 76 88 Fax: +1 484 821 1272

Version: M V 4.10.1 E-mail: info@mn-net.com E-mail: sales-ch@mn-net.com E-mail: sales-fr@mn-net.com E-mail: sales-us@mn-net.com

MACHEREY-NAGEL



Safety Data Sheet

according to Regulations 1907/2006/EC (REACh) and 2015/830/EU

 REF: 91867
 NANOCOLOR Nitrite
 Page: 4/10

 Printing date: 01.10.2019
 Date of issue: 15.03.2019

3.3 Remarks

When not listed, mixtures are added with water [CAS No. 7732-18-5] to 100%.

List of H and P phrases: see section 16.1

SECTION 4: First aid measures

4.1 Description of first aid measures

Place insured person out of danger zone to fresh air immediately. Ensure quiet, warmth, and provide resuscitation if necessary. If necessary contact medical advice. Remove contaminated clothing. Show product package, packing insert and this material safety data sheet to the doctor.

4.1.1 After SKIN Contact

Remove contaminated clothing immediately. Rinse the affected skin or mucous membrane thoroughly for min. 15 minutes under running water. (If possible) use soap. Avoid neutralisation. Then apply a loose bandage.

4.1.2 After EYE Contact

After contact with the eyes rinse thoroughly under running water with the eyelid wide open for min. 10 minutes with eye washing bottle, eye douche or running water (protect intact eye). Before (if possible) apply eye drops Proxymetacaine 0.5%, if the opening the eyelid convulsion is painful. Further treatment to be carried out by an eye specialist.

4.1.3 After INHALATION of vapours

After inhalation of foam or vapour fresh air should be inhaled. Keep airways free. If vomiting and if insensible place patient in recovery position and keep airways free. ---

4.1.4 After ORAL Intake

After oral intake lots of water with activated charcoal supplement should be drunk after it has been ingested. Do not induce vomiting under any circumstances. Do not make any efforts to neutralise it. Contact medical advice for possible consequences. ---

4.2 Most important symptoms and effects, both acute and delayed

May cause sensitization by skin contact, also in repeated contact of small amounts. ---

4.3 Indication of any immediate medical attention and special treatment needed

CORROSIVE DAMAGE: After SKIN CONTACT rinse with water for a long time. Efforts to neutralise the substance can frequently make matters worse. Apply glucocorticosteroides following inflammatory reactions. After EYE CONTACT rinse immediately with plenty of water for a long time. Eyelid convulsion measures. Name the corrosive chemical. Further treatment must to be carried out by an eye specialist. After INTAKE administer aluminium oxide drug suspensions. Administer a prophylaxis to counter pulmonary oedema following the INGESTION of corrosive aerosols. In the event of RESPIRATORY DISTREES ensure that the patient inhales oxygen. Inform patient respectively further measures and the possibility of long-term damages. ---

SECTION 5: Firefighting measures

5.1 Extinguishing media

Fire extinguishers appropriate to the fire classification, and, if applicable, a fire blanket must be available in a prominent location in the work area. All extinguishers like FOAM, WATER SPRAY, DRY POWDER, CARBON DIOXIDE can be used.

5.2 Special hazards arising from the substance or mixture

Formation of hazardous and caustic vapour-air mixtures possible. ---

5.3 Advice for firefighters

No, for listed product. Product package burns like paper or plastic. Spray any vapours released with water. Retent fire water. Use only acid-resistant safety equipment.

For great amount - if necessary - protective breathing apparatus which is independent of the ambient air (isolated equipment), and sealed protective clothing is necessary in the event of a large-scale formation of toxic substances.

5.4 Additional information

Danger for environment only in the event of a large-scale leakage or formation of hazardous substances. ---

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Do not breathe vapours. Wear suitable protective gloves (see 8.2.2). Wear eye protection, respectively face protection. Regular staff training is necessary, indicating hazards and precautions on the basis of operating instructions. Restrictions on activity must be observed.

6.2 Environmental precautions

www.mn-net.com

US:

ISO 9001 CERTIFIED MACHEREY-NAGEL GmbH & Co. KG \cdot Neumann-Neander-Str. 6–8 \cdot 52355 Düren \cdot Germany

DE/international: CH: FR:

Tel.: +49 24 21 969-0 Tel.: +41 62 388 55 00 Tel.: +33 388 68 22 68 Tel.: +1 484 821 0984 Fax: +49 24 21 969-199 Fax: +41 62 388 55 05 Fax: +33 388 51 76 88 Fax: +1 484 821 1272

Version: M V 4.10.1 E-mail: info@mn-net.com

E-mail: sales-ch@mn-net.com

E-mail: sales-fr@mn-net.com

E-mail: sales-us@mn-net.com



according to Regulations 1907/2006/EC (REACh) and 2015/830/EU

NANOCOLOR Nitrite Page: 5/10

Printing date: 01.10.2019 Date of issue: 15.03.2019

not necessary

6.3 Methods and material for containment and cleaning up

Bind any escaping liquid with inert absorbent. And dispose in accordance to local regulations for the disposal of hazardous chemicals. Clean any contaminated equipment and floors with plenty of water. Collect small amounts of leaked liquid and flush with water into drains.

6.4 Reference to other sections

see information in section 5.4 ---

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Handling in accordance with the test instruction, that comes with the product.

7.2 Conditions for safe storage, including any incompatibilities

The original product package of MACHEREY-NAGEL allows a safe storage.

Storage class (VCI): Water hazard class (DE):

Requirements for stock rooms and containers 7.2.1

Keep original product packages tightly closed during handling and storage. Use inbreakable container for transport of glass bottles.

7.3 Specific end use(s)

Product for analytical use.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

100 mL Nitrite R1

Chemical: CAS No.: 121-57-3 sulfanilic acid

[inh] 1,3 mg/m³ DNFL = Derived No-Effect evel (for workers) TRGS 900 (DE): AGW -E/e respirable

not listed NIOSH: [TWA] Time-weighted average to a reference period of 8 hours, [STEL] Short-term exposure limit related to a 15-minute period

OSHA: not listed

Chemical: CAS No : 64-19-7 acetic acid

[loc, inh] 25 mg/m³ DNEL: DNEL = Derived No-Effect Level (for workers) PNEC (fresh water): 3.058 mg/L PNEC = Predicted No Effected Concentration

[TWA] 25 / [STEL] 50 mg/m³ 10 mL/m³ / 25 mg/m³ EU value: TRGS 900 (DE):

E/e respirable Short-term exposure factor: 2(I), Y

skin resorptive (H), respiratory sensitizable (Sa), skin sensitizable (Sh), teratogenic (Z) not securely excluded / (Y) certainly excluded

SUVA(CH) MAK value: 10 ppm / 25 mg/m³

NIOSH:

[TWA] 10 ppm / 25 mg/m³; [STEL] 15 ppm / 37 mg/m³ [TWA] Time-weighted average to a reference period of 8 hours, [STEL] Short-term exposure limit related to a 15-minute period

OSHA: [TWA] 10 ppm / 25 mg/m³

100 mL Nitrite R2

Chemical: 1-naphthylamine CAS No.: 134-32-7

TRGS 900 (DE): 0,17 mL/m3 / 1 E mg/m3

4 (II), H Short-term exposure factor:

skin resorptive (H), respiratory sensitizable (Sa), skin sensitizable (Sh), teratogenic (Z) not securely excluded / (Y) certainly excluded

Occupational Carcinogen List Yes

[TWA] Time-weighted average to a reference period of 8 hours, [STEL] Short-term exposure limit related to a 15-minute period

OSHA: 29 CFR 1910.1004 (1986): carcinogen

Chemical: acetic acid CAS No.: 64-19-7

[loc, inh] 25 mg/m³ DNEL = Derived No-Effect Level (for workers) PNEC(fresh water): 3.058 mg/L

www.mn-net.com

MACHEREY-NAGE (MN)

MACHEREY-NAGEL GmbH & Co. KG · Neumann-Neander-Str. 6-8 · 52355 Düren · Germany

DE/international: CH: FR: US:

Tel.: +49 24 21 969-0 Tel.: +41 62 388 55 00 Tel.: +33 388 68 22 68 Tel.: +1 484 821 0984 Fax: +49 24 21 969-199 Fax: +41 62 388 55 05 Fax: +33 388 51 76 88 +1 484 821 1272 Fax: Version: M V 4.10.1 E-mail: info@mn-net.com E-mail: sales-ch@mn-net.com E-mail: sales-fr@mn-net.com E-mail: sales-us@mn-net.com



according to Regulations 1907/2006/EC (REACh) and 2015/830/EU

NANOCOLOR Nitrite Page: 6/10

Printing date: 01.10.2019 Date of issue: 15.03.2019

PNEC = Predicted No Effected Concentration

[TWA] 25 / [STEL] 50 mg/m³ EU value: TRGS 900 (DE): 10 mL/m³ / 25 mg/m³ E/e respirable

Short-term exposure factor: 2(I), Y

skin resorptive (H), respiratory sensitizable (Sa), skin sensitizable (Sh), teratogenic (Z) not securely excluded / (Y) certainly excluded

10 ppm / 25 mg/m³ SUVA(CH) MAK value:

NIOSH:

E: [TWA] 10 ppm / 25 mg/m³; [STEL] 15 ppm / 37 mg/m³ [TWA] Time-weighted average to a reference period of 8 hours, [STEL] Short-term exposure limit related to a 15-minute period

OSHA: [TWA] 10 ppm / 25 mg/m³

8.2 Exposure controls

Good ventilation and extraction system in the room, floor resistant to chemicals with floor drainage and washing facilities. The highest level of cleanliness must be maintained at the workplace.

8.2.1 Respiratory protection

No additional recommendations.

8.2.2 Hand protection

Yes, gloves according EN 374 (permeation time >30 min - level 2), consist of PVC, natural latex, Neopren, or Nitril (f.ex. from Ansell or KCL). Use for short times chemical resistant latex gloves with code EN 374-3 level 1.

8.2.3

Yes, safety glasses according EN 166 with integrated side shields or wrap-around protection or face protection.

Skin protection 8.2.4

Recommended to avoid clothing damage, and to avoid contamination with these hazards.

8.2.5 Personal hygiene

Eating, drinking, smoking, taking snuff and storage of food in work areas and at outdoor workplaces is prohibited. Avoid contact with the skin, eyes and clothing. Rinse any clothing on which the substance has been spilled, and soak it in water. Wash hands thoroughly with soap and water when stopping work and before eating, and then apply protective skin cream.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

100 mL Nitrite R1

Odor: acetic Appearance: liquid Colour colourless

2-3 pH: Specific gravity: 1,03 g/cm³ Solubility in water: 0-100 %

100 mL Nitrite R2

Appearance: liquid Colour: rose Odor: acetic

2-3 Specific gravity: 1,03 g/cm³ Solubility in water: 0-100 %

9.2 Other information

Data for the other parameters of the mixtures are not available, because no registration and no chemical safety report is required. Relevant Properties of Substance Group

SECTION 10: Stability and reactivity

10.1 Reactivity

no further data available.

10.2 Chemical stability

No known instability.

10.3 Possibility of hazardous reactions

Can react violently with organic material. No further data available.

www.mn-net.com

US:



MACHEREY-NAGEL GmbH & Co. KG · Neumann-Neander-Str. 6-8 · 52355 Düren · Germany

DE/international: CH: FR:

Tel.: +49 24 21 969-0 Tel.: +41 62 388 55 00 Tel.: +33 388 68 22 68 Tel.: +1 484 821 0984 Fax: +49 24 21 969-199 +41 62 388 55 05 +33 388 51 76 88 +1 484 821 1272 Fax: Fax: Version: M V 4.10.1 E-mail: info@mn-net.com E-mail: sales-ch@mn-net.com E-mail: sales-fr@mn-net.com E-mail: sales-us@mn-net.com

MACHEREY-NAGEL



Safety Data Sheet

according to Regulations 1907/2006/EC (REACh) and 2015/830/EU

NANOCOLOR Nitrite Page: 7/10

Printing date: 01.10.2019 Date of issue: 15.03.2019

10.4 Conditions to avoid

Not necessary. Observe labeled storage temperature. ---

10.5 Incompatible materials

Avoid contact with strong acids or alkalines.

10.6 Hazardous decomposition products

In the original package all parts/all reagents are safety and separated stored. Decompositions are not observed during the expiration period under recommended conditions

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Following information is valid for pure substances. Quantitative data on the toxicity of this product are not available.

100 mL Nitrite R1

Chemical: sulfanilic acid CAS No.: 121-57-3

TSCA Inventory listed California Proposition 65 List: not listed Australia NICNAS: Canada CEPA 1999: DSL Yes not listed

Japan CSCL/PRTR: not listed, Japan PDSCL: not listed

Japan ISHL: not listed South Korea TCCA: not listed Korea Exist.Chem.Inventory: KE-01192 LD50_{orl rat}: 12.3 g/kg

Acute Effects: Cause after skin contact, impairments of health when ingested in small quantities. May cause sensitization by skin

contact, also in repeated contact of small amounts.

Chemical: acetic acid CAS No.: 64-19-7

TSCA Inventory: California Proposition 65 List: not listed

Exposure Routes: inhalation, skin and/or eye contact Target Organs: Eyes, skin, respiratory system, teeth

Symptoms: irritation eyes, skin, nose, throat; eye, skin burns; skin sensitization; dental erosion; black skin,

hyperkeratosis; conjunctivitis, lacrimation (di

Canada CEPA 1999: DSL Yes Australia NICNAS: not listed

not listed, Japan PDSCL: not listed Japan CSCL/PRTR:

Japan ISHL: listed ≥1,0%/≥1,0%, Article 57-2 (SDS required)

South Korea TCCA: not listed Korea Exist.Chem.Inventory: KE-00013 LD50_{orl rat}: 3310 mg/kg [4h] 8.5-12,7 mg/L LC50_{inh rat}: LD50_{drm rbt}: 1060 mg/kg LD50_{oral mouse}: 4960 mg/kg

100 mL Nitrite R2

Chemical: 1-naphthylamine CAS No.: 134-32-7

TSCA Inventory: California Proposition 65 List: listed cancer listed Target Organs: Carcinogen Australia NICNAS: not listed Canada CEPA 1999: DSL yes

Japan CSCL/PRTR: not listed, Japan PDSCL: not listed

Japan ISHL: listed ≥1,0%/≥1,0%, Article 56 (Permission required)

South Korea TCCA: not listed Korea Exist.Chem.Inventory: KE-25544 LD50_{orl rat}: 680 mg/kg

Chemical: acetic acid CAS No.: 64-19-7

TSCA Inventory: California Proposition 65 List: not listed

Exposure Routes: inhalation, skin and/or eye contact Target Organs: Eyes, skin, respiratory system, teeth

Symptoms: irritation eyes, skin, nose, throat; eye, skin burns; skin sensitization; dental erosion; black skin,

hyperkeratosis; conjunctivitis, lacrimation (di

Australia NICNAS: Canada CEPA 1999: DSL Yes

Japan CSCL/PRTR: not listed, Japan PDSCL: not listed

Japan ISHL: listed ≥1,0%/≥1,0%, Article 57-2 (SDS required)

South Korea TCCA: not listed Korea Exist.Chem.Inventory: KE-00013 LD50_{orl rat}: 3310 mg/kg

www.mn-net.com



MACHEREY-NAGEL GmbH & Co. KG · Neumann-Neander-Str. 6-8 · 52355 Düren · Germany

DE/international: CH: FR: US:

Tel.: +49 24 21 969-0 Tel.: +41 62 388 55 00 Tel.: +33 388 68 22 68 Tel.: +1 484 821 0984 Fax: +49 24 21 969-199 Fax: +41 62 388 55 05 Fax: +33 388 51 76 88 +1 484 821 1272 Fax: Version: M V 4.10.1 E-mail: info@mn-net.com E-mail: sales-ch@mn-net.com E-mail: sales-fr@mn-net.com E-mail: sales-us@mn-net.com



CAS No.: 64-19-7

Safety Data Sheet

according to Regulations 1907/2006/EC (REACh) and 2015/830/EU

NANOCOLOR Nitrite Page: 8/10

Printing date: 01.10.2019 Date of issue: 15.03.2019

> LC50_{inh rat}: [4h] 8.5-12,7 mg/L LD50_{drm rbt}: 1060 mg/kg LD50_{oral mouse}: 4960 mg/kg

SECTION 12: Ecological information

12.1 **Toxicity**

Following information is valid for pure substances.

100 mL Nitrite R1

sulfanilic acid CAS No.: 121-57-3 Chemical:

Water hazard class (DE): WGK No.: VwVwS 12-13

Storage class (VCI):

Chemical: acetic acid

PNEC (fresh water):
PNEC = Predicted No Effected Concentration 3.058 mg/L

LC50fish/96h: [4d] 301-1000 mg/L 301-1000 mg/L EC50_{daphnia/48h}: 301-1000 mg/L IC50_{scenedesmus} quadricauda/72h:

Water hazard class (DE): WGK No.: 0093

Dispersion coefficient_(octanol-water): -0.17Storage class (VCI): 8 B

100 mL Nitrite R2

Chemical: 1-naphthylamine CAS No.: 134-32-7

Bio Toxicity: 3/4.8-5.2/<4.0

Water hazard class (DE): WGK No.: 0822

Dispersion coefficient(octanol-water): Storage class (VCI):

CAS No.: 64-19-7 Chemical: acetic acid

Avoid contact of substance/mixture to environment. PNEC (fresh water):
PNEC = Predicted No Effected Concentration 3.058 mg/L

[4d] 301-1000 mg/L LC50fish/96h: EC50_{daphnia/48h}: 301-1000 mg/L 301-1000 mg/L IC50_{scenedesmus} quadricauda/72h: WGK No.: 0093 Water hazard class (DE):

Dispersion coefficient(octanol-water): -0,17

Storage class (VCI):

12.2 Persistence and degradability

not necessary

12.3 Bioaccumulative potential

not necessary

12.4 Mobility in soil

not necessary

Results of PBT and vPvB assessment 12.5

no data available

12.6 Other adverse effects

no additional data available

www.mn-net.com

US:

MACHEREY-NAGE **(MN)**

MACHEREY-NAGEL GmbH & Co. KG · Neumann-Neander-Str. 6-8 · 52355 Düren · Germany

DE/international: CH: FR:

Tel.: +49 24 21 969-0 Tel.: +41 62 388 55 00 Tel.: +33 388 68 22 68 Tel.: +1 484 821 0984 Fax: +49 24 21 969-199 Fax: +41 62 388 55 05 Fax: +33 388 51 76 88 Fax: +1 484 821 1272 Version: M V 4.10.1 E-mail: info@mn-net.com E-mail: sales-ch@mn-net.com E-mail: sales-fr@mn-net.com E-mail: sales-us@mn-net.com

MACHEREY-NAGEL



Safety Data Sheet

according to Regulations 1907/2006/EC (REACh) and 2015/830/EU

REF: 91867 NANOCOLOR Nitrite Page: 9/10

Printing date: 01.10.2019 Date of issue: 15.03.2019

SECTION 13: Disposal considerations

Please observe local regulations for collection and disposal of hazardous waste and contact waste disposal company, where you will obtain information on laboratory waste disposal (waste code number 16 05 06).

13.1 Waste treatment methods

Normally it is possible to empty small amounts (diluted!) into drains. Empty containers of corrosive reagents prior to disposal, rinse with water

SECTION 14: Transport information

14.1. UN number: 3316 14.2. UN proper shipping name: Chemical Kit

14.3. Class: 9 14.4. Packing group:

Road transport

Classification code: M11 Tunnel restriction code: E

Limited Quantity: acc. ADR 3.3.1/251: see LQ in Alternative declaration for transportation

Air transport

PAX: 960 max. weight PAX: 10 KG CAO: 960 max. weight CAO: 10 KG

Maritime transport

EmS: F-A, S-P Storage category: A

Or use Alternative declaration for transportation:

F 1

14.1 UN number: 3265 14.2 UN proper shipping name: Corrosive liquid, acidic, organic, n.o.s. (acetic acid mixture)

14.3 Class: 8 14.4 Packing group: III

Road transport

Classification code: C3

Limited Quantity: 5 L Tunnel restriction code: E

Excepted Quantity:

Air transport

PAX: 852 max. weight PAX: 5 L CAO: 856 max. weight CAO: 60 L

Maritime transport

EmS: F-A, S-B Storage category: A

14.5 Environmental hazards

none, contains only small quantities of hazardous substances

14.6 Special precautions for user

not necessary

14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code

not applicable

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

German act governing protection from hazardous substances (Chemicals Act / Chemikaliengesetz- ChemG), revised on August 2013 German order governing protection from hazardous substances (Ordinance on Hazardous Substances / Gefahrstoffverordnung - GefStoffV), revised on November 2010, according to Directive 98/24/EC

TRGS 200, German engineering rules governing the classification and labelling of hazardous substances, preparations and products, updated October 2011

MN Leaflet/User manual, also see www.mn-net.com

Look for your country-specific regulations.

15.2 Chemical safety assessment

not necessary for these small amounts ---

SECTION 16: Other information

16.1 List of H and P phrases

16.1.1 List of relevant H phrases

H314 Causes severe skin burns and eye damage.

www.mn-net.com

US:



MACHEREY-NAGEL GmbH & Co. KG \cdot Neumann-Neander-Str. 6–8 \cdot 52355 Düren \cdot Germany

DE/international: CH: FR:

Tel.: +49 24 21 969-0 Tel.: +41 62 388 55 00 Tel.: +33 388 68 22 68 Tel.: +1 484 821 0984 Fax: +49 24 21 969-199 +41 62 388 55 05 +33 388 51 76 88 +1 484 821 1272 Fax: Fax: Fax:

Version: M V 4.10.1 E-mail: info@mn-net.com

E-mail: sales-ch@mn-net.com

E-mail: sales-fr@mn-net.com

E-mail: sales-us@mn-net.com

ACHEREY-NAGEL



Safety Data Sheet

according to Regulations 1907/2006/EC (REACh) and 2015/830/EU

NANOCOLOR Nitrite Page: 10/10 Printing date: 01.10.2019 Date of issue: 15.03.2019

> H315 Causes skin irritation

May cause an allergic skin reaction. H317 H319 Causes serious eye irritation.

16.1.2 List of relevant P phrases

> Do not breathe dust/vapours. P260sh P261sh Avoid breathing dust/vapours. P280sh Wear protective gloves/eye protection.

P303+361+353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower]. P305+351+338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to

do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

16.2 Training advice

Multiple safety training of staffs about danger and protection by using hazards in working area. Additionally training and introduction of staffs for using these products

16.3 Recommended restriction on use

Only for professional user.

Look about employee restrictions for young people (f. ex. 94/33/EC or DE § 22 JArbSchG)!

Look about employee restrictions for pregnant women and nursing women (f.ex. 92/85/EEC or for DE §§ 11-13 MuSchG 2017)! An individual package of this product or test kit has a moderate hazardous potential.

16.4 Further information

MACHEREY-NAGEL GmbH & Co. KG provides the information contained herein in good faith being up-to-date of own realizations at revision time. This document is intended only as a guide to the appropriate precautionary handling of the material by a properly trained person using this product. Individuals receiving the information must exercise their independent judgement in determining its appropriateness for a particular purpose.

MACHEREY-NAGEL GmbH & Co. KG makes NO REPRESENTATIONS or WARRANTIES, either expressed or implied, including without limitation any warranties of merchantability, fitness for a particular purpose with respect to the information set forth herein or the product to which the information refers. Accordingly MACHEREY-NAGEL GmbH & Co. KG will not be responsible for damages resulting from use of or reliance upon this information. See terms and conditions at the end of our price lists for additional information.

16.5 Sources of key data

Regulation 453/2010/EU REACH - REQUIREMENTS FOR THE COMPILATION OF SAFETY DATA SHEETS

Regulation 487/2013/EU, 4th adaptation of CLP regulation to technical and scientific progress Regulation 669/2018/EU, 4th adaptation of CLP regulation to technical and scientific progress

TRGS 900, German engineering rules governing limits in air at work, updated 03/2018

SUVA .CH, Limits in air at work 2009, revised on 01.2009

TRGS 907, German engineering rules governing listing of substances and causes of sensitizations, updated November 2011

KÜHN, BIRETT Merkblätter Gefährliche Arbeitsstoffe (Data Sheets of Hazardous Substances)

Revisions/Updates

Reason for Revision: 2016-03 Adaptation of regulation 1221/2015/EU

www.mn-net.com

ACHEREY-NAGE MN

MACHEREY-NAGEL GmbH & Co. KG · Neumann-Neander-Str. 6-8 · 52355 Düren · Germany

DE/international: CH: FR: US:

Tel.: +49 24 21 969-0 Tel.: +41 62 388 55 00 Tel.: +33 388 68 22 68 Tel.: +1 484 821 0984 Fax: +49 24 21 969-199 Fax: +41 62 388 55 05 Fax: +33 388 51 76 88 Fax: +1 484 821 1272 Version: M V 4.10.1 E-mail: info@mn-net.com E-mail: sales-ch@mn-net.com E-mail: sales-fr@mn-net.com E-mail: sales-us@mn-net.com