

according to Regulation (EC) No 1907/2006

STAMMOPUR DR 8

Revision date: 20.02.2018 No: 83005 Page 1 of 11

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

STAMMOPUR DR 8

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

disinfectants. Disinfection and intensive cleaning of instruments, concentrate. Restricted to professional users.

1.3. Details of the supplier of the safety data sheet

Company name: DR.H.STAMM GmbH Chemische Fabrik

Street: Heinrichstr. 3 – 4
Place: 12207 Berlin, GERMANY

Telephone: +49 30 76880-280 e-mail: info@dr-stamm.de Internet: www.dr-stamm.de

Responsible Department: sdb@dr-stamm.de, Tel.: +49 30 76880-258

1.4. Emergency telephone 24-hours-emergency: Giftnotruf Berlin: +49 30 30686700 (german, english)

number:

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No. 1272/2008

Hazard categories:

Acute toxicity: Acute Tox. 4

Skin corrosion/irritation: Skin Corr. 1A

Serious eye damage/eye irritation: Eye Dam. 1 Respiratory or skin sensitisation: Resp. Sens. 1 Respiratory or skin sensitisation: Skin Sens. 1

Reproductive toxicity: Repr. 2

Specific target organ toxicity - single exposure: STOT SE 3 Hazardous to the aquatic environment: Aquatic Chronic 2

Hazard Statements: Harmful if swallowed.

Causes severe skin burns and eye damage.

May cause an allergic skin reaction.

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

May cause drowsiness or dizziness.

Suspected of damaging fertility. Suspected of damaging the unborn child.

Toxic to aquatic life with long lasting effects.

2.2. Label elements

Regulation (EC) No. 1272/2008

Hazard components for labelling

Butane-1,4-diol

N,N-Bis(3-aminopropyl)dodecylamine Didecylmethylammoniumpropionate

piperazine

Signal word: Danger

Pictograms:











according to Regulation (EC) No 1907/2006

STAMMOPUR DR 8

Revision date: 20.02.2018 No: 83005 Page 2 of 11

Hazard statements

H302 Harmful if swallowed.

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H336 May cause drowsiness or dizziness.

H361fd Suspected of damaging fertility. Suspected of damaging the unborn child.

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P308+P313 IF exposed or concerned: Get medical advice/attention.

P310 Immediately call a POISON CENTER/doctor.

SECTION 3: Composition/information on ingredients

3.2. Mixtures



according to Regulation (EC) No 1907/2006

STAMMOPUR DR 8

Revision date: 20.02.2018 No: 83005 Page 3 of 11

Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification according to Regulat	ion (EC) No. 1272/2008 [C	CLP]	
7732-18-5	Water			20-30 %
	213-791-2			
			-	
110-63-4	Butane-1,4-diol			15-25 %
	203-786-5		01-2119471849-20	
	Acute Tox. 4, STOT SE 3; H302 H3	336		
112-34-5	2-(2-butoxyethoxy)ethanol, diethyle	ene glycol monobutyl ether		10-20 %
	203-961-6		01-2119475104-4	
	Eye Irrit. 2; H319		•	
2372-82-9	N,N-Bis(3-aminopropyl)dodecylam		9,9 %	
	219-145-8		01-2119980592-29	
	Acute Tox. 3, Skin Corr. 1A, STOT			
94667-33-1	Didecylmethylammoniumpropionat	8,4 %		
	619-057-3		01-2119950327-36	
	Acute Tox. 4, Skin Corr. 1B, Aquati			
79-33-4	Lacitc acid		2-7 %	
	201-196-2		01-2119474164-39	
	Skin Irrit. 2, Eye Dam. 1; H315 H3			
68920-66-1	C16-C18 Fatty alcohol, ethoxylated	2-7 %		
	-		*	
			·	
110-85-0	piperazine			<5 %
	203-808-3	612-057-01-1	01-2119480384-35	
	Repr. 2, Skin Corr. 1B, Resp. Sens			
60-00-4	Ethylenediaminetetraacetic acid	1-5 %		
	200-449-4		01-2119486399-18	
	Acute Tox. 4, Eye Dam. 1; H302 H			
68515-73-1	Alkylpolyglycosid			1-5 %
	-		01-2119488530-36	
	Eye Dam. 1; H318			

Full text of H and EUH statements: see section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Take off immediately all contaminated clothing.

After inhalation

In case of inhalation of aerosols/spray mist/splash spots: Consult physician. Provide fresh air.

After contact with skin

After contact with skin, wash immediately with: Water and soap. In case of skin irritation, seek medical treatment.



according to Regulation (EC) No 1907/2006

STAMMOPUR DR 8

Revision date: 20.02.2018 No: 83005 Page 4 of 11

After contact with eyes

Immediately flush eyes with plenty of flowing water for 10 to 15 minutes holding eyelids apart. Consult an opthalmologist.

After ingestion

Rinse mouth immediately and drink large quantities of water. Do not induce vomiting. Consult physician.

4.2. Most important symptoms and effects, both acute and delayed

No symptoms known up to now.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Water. Foam. Atomized water.

Unsuitable extinguishing media

High power water jet.

5.2. Special hazards arising from the substance or mixture

Can be released in case of fire: Nitrogen oxides (NOx). Carbon dioxide (CO2).

5.3. Advice for firefighters

Special protective equipment for fire-fighters: Use appropriate respiratory protection. In case of fire and/or explosion do not breathe fumes.

Additional information

Material is not combustible. Extinguishing materials should be selected according to the surrounding area.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Keep away from unprotected people. Keep upwind. Wear respiratory protection when in the presence of vapour, dust, and aerosols. Guide people to safety.

6.2. Environmental precautions

Do not empty into drains or the aquatic environment. Prevent spreading over great surfaces (e.g. by damming or installing oil booms).

6.3. Methods and material for containment and cleaning up

Clean contaminated articles and floor according to the environmental legislation. Treat the assimilated material according to the section on waste disposal. Suitable absorbing material: Sand Universal binding agent. earth. Sawdust.

6.4. Reference to other sections

See protective measures under point 7 and 8.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

It is recommended to organise all working processes in order to exclude the following: skin contact. Eye contact.

Advice on protection against fire and explosion

Product is not: Oxidizing. Flammable. Explosive.

Further information on handling

Use only in well-ventilated areas.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Store only in original container.



according to Regulation (EC) No 1907/2006

STAMMOPUR DR 8

Revision date: 20.02.2018 No: 83005 Page 5 of 11

Keep away from food, drink and animal feedingstuffs.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m³	fibres/ml	Category	Origin
112-34-5	2-(2-Butoxyethoxy)ethanol	10	67.5		TWA (8 h)	WEL
		15	101.2		STEL (15 min)	WEL
110-85-0	Piperazine	-	0.1		TWA (8 h)	WEL
		_	0.3		STEL (15 min)	WEL

DNEL/DMEL values

CAS No	Substance			
DNEL type		Exposure route	Effect	Value
112-34-5	2-(2-butoxyethoxy)ethanol, diethylene glycol monobutyl eth	er		
Consumer DN	EL, long-term	oral	systemic	1,25 mg/kg bw/day
Worker DNEL,	long-term	dermal	systemic	20 mg/kg bw/day
68515-73-1 Alkylpolyglycosid				
Worker DNEL, long-term		dermal	systemic	595000 mg/kg bw/day
Worker DNEL,	long-term	inhalation	systemic	420 mg/m³
Consumer DNEL, long-term		dermal	systemic	357000 mg/kg bw/day
Consumer DN	EL, long-term	oral	systemic	35,7 mg/kg bw/day
Consumer DN	EL, long-term	inhalation	systemic	124 mg/m³

PNEC values

CAS No	Substance					
Environmental	compartment	Value				
110-63-4 Butane-1,4-diol						
Marine water	Marine water 0					
Marine water (i	ntermittent releases)	8,13 mg/l				
Freshwater sec	Freshwater sediment					
Marine sedime	Marine sediment					
79-33-4	Lacitc acid					
Freshwater		1,3 mg/l				
68515-73-1	Alkylpolyglycosid					
Freshwater		0,175 mg/l				
Marine water	Marine water					
Freshwater sec	1516 mg/kg					
Marine sedime	Marine sediment 0					
Soil		0,654 mg/kg				

8.2. Exposure controls

Appropriate engineering controls

Refer to chapter 7. No further action is necessary.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

STAMMOPUR DR 8

Revision date: 20.02.2018 No: 83005 Page 6 of 11

Protective and hygiene measures

Do not eat, drink, smoke or sneeze at the workplace.

Take off immediately all contaminated clothing.

Wash hands before breaks and at the end of work.

Eve/face protection

Wear eye/face protection.

Hand protection

Suitable material: PE (polyethylene). CR (polychloroprenes, Chloroprene rubber). NBR (Nitrile rubber). Butyl rubber. FKM (Fluoroelastomer (Viton)).

penetration time (maximum wearing period): >480 min. Breakthrough times and swelling characteristics of the material must be taken into consideration.

Recommended protective gloves brand: Camapren 722, Manufacturer: KCL, or comparable makes from other companies.

Skin protection

Lab apron.

Respiratory protection

Respiratory protection not required.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: liquid

Colour: clear, yellow Odour: characteristic

Test method

pH-Value (at 20 °C): in delivery condition: 10,0 DGF H-III 1

Changes in the physical state

Melting point: -20 °C
Initial boiling point and boiling range: 100 °C
Flash point: non-flammable

Explosive properties

not Explosive.

Oxidizing properties

not oxidizing.

Density (at 20 °C): 1,02 g/cm³ DIN 12791

Water solubility: complete miscible

(at 20 °C)

SECTION 10: Stability and reactivity

10.1. Reactivity

None, in case of proper use.

10.2. Chemical stability

The product is chemically stable under normal ambient conditions.

10.3. Possibility of hazardous reactions

None, in case of proper use.

10.4. Conditions to avoid

Thermal decomposition can lead to the escape of irritating gases and vapors.

10.5. Incompatible materials

acid, concentrated.



according to Regulation (EC) No 1907/2006

STAMMOPUR DR 8

Revision date: 20.02.2018 No: 83005 Page 7 of 11

10.6. Hazardous decomposition products

None, in case of proper use.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity

Harmful if swallowed.

Acute toxicity, oral LD50: 2000-5000 mg/kg Rat.

ATEmix calculated

ATE (oral) 618,0 mg/kg

CAS No	Chemical name									
	Exposure route	Dose		Species	Source	Method				
110-63-4	Butane-1,4-diol									
	oral	LD50 mg/kg	1525	rat	RTECS					
	dermal	LD50 mg/kg	>2000	rabbit	RTECS					
112-34-5	2-(2-butoxyethoxy)ethan	ol, diethyler	ne glycol mon	obutyl ether						
	oral	LD50 mg/kg	3305	rat						
	dermal	LD50 mg/kg	2764	rabbit						
2372-82-9	N,N-Bis(3-aminopropyl)d	lodecylamir	e							
	oral	LD50 mg/kg	261	rat		OECD 401				
	dermal	LD50 mg/kg	>600	rat		OECD 402				
94667-33-1	Didecylmethylammoniumpropionate									
	oral	ATE mg/kg	500							
79-33-4	Lacitc acid									
	oral	LD50 mg/kg	3730	rat						
	dermal	LD50 mg/kg	>2000	rabbit						
	inhalative (4 h) vapour	LC50 mg/l	>7.94	rat						
68920-66-1	C16-C18 Fatty alcohol, e	thoxylated								
	oral	LD50 mg/kg	>2000	Ratte						
60-00-4	Ethylenediaminetetraace	tic acid								
	oral	ATE mg/kg	500							
68515-73-1	Alkylpolyglycosid									
	oral	LD50 mg/kg	>5000							

Irritation and corrosivity

Causes severe skin burns and eye damage.

Irritant effect on the skin: irritant. Irritant effect on the eye: corrosive.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

STAMMOPUR DR 8

Revision date: 20.02.2018 No: 83005 Page 8 of 11

Sensitising effects

May cause an allergic skin reaction. (piperazine)

May cause allergy or asthma symptoms or breathing difficulties if inhaled. (piperazine)

May cause sensitization by inhalation and skin contact.

Carcinogenic/mutagenic/toxic effects for reproduction

Suspected of damaging fertility, Suspected of damaging the unborn child, (piperazine)

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

STOT-single exposure

May cause drowsiness or dizziness. (Butane-1,4-diol)

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

12.1. Toxicity

Technically correct releases of minimal concentrations to adapted biological sewage treatment facility, will not disturb the biodegradability of activated sludge.

	distain the biodegradability of activated studge.								
CAS No	Chemical name								
	Aquatic toxicity	Dose	Dose		Species	Source	Method		
79-33-4	Lacitc acid								
	Acute fish toxicity	LC50	130 mg/l	96 h	Oncorhynchus mykiss				
68920-66-1	-1 C16-C18 Fatty alcohol, ethoxylated								
	Acute fish toxicity	toxicity LC50 30 mg/l		96 h					
	Acute crustacea toxicity	EC50 mg/l	>1000	48 h					
68515-73-1	l Alkylpolyglycosid								
	Acute fish toxicity	LC50 mg/l	>100	96 h					

12.2. Persistence and degradability

The surfactants contained in this preparation comply with the biodegradability criteria as laid down in Regulation (EC) No.648/2004 on detergents. Data to support this assertion are held at the disposal of the competent authorities of the Member States and will be made available to them, at their direct request or at the request of a detergent manufacturer.

CAS No	Chemical name			
	Method	Value	d	Source
	Evaluation			
68920-66-1	C16-C18 Fatty alcohol, ethoxylated			
	OECD 301D	>70 %	28	
	Leicht biologisch abbaubar			

12.3. Bioaccumulative potential

On the basis of existing data about disposal/decomposition and bio-accumulation potential, long term environmental damage is unlikely.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
79-33-4	Lacitc acid	-0,62

Safety Data Sheet

according to Regulation (EC) No 1907/2006

STAMMOPUR DR 8

Revision date: 20.02.2018 No: 83005 Page 9 of 11

BCF

CAS No	Chemical name	BCF	Species	Source
	2-(2-butoxyethoxy)ethanol, diethylene glycol monobutyl ether	<100		

12.4. Mobility in soil

No data available

12.5. Results of PBT and vPvB assessment

not applicable

12.6. Other adverse effects

No data available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Advice on disposal

According to EAKV, allocation of waste identity numbers/waste descriptions must be carried out in a specific way for every industry and process.

Waste disposal number of waste from residues/unused products

200129 MUNICIPAL WASTES (HOUSEHOLD WASTE AND SIMILAR COMMERCIAL, INDUSTRIAL AND

INSTITUTIONAL WASTES) INCLUDING SEPARATELY COLLECTED FRACTIONS; separately collected fractions (except 15 01); detergents containing hazardous substances; hazardous waste

Waste disposal number of used product

180106 WASTES FROM HUMAN OR ANIMAL HEALTH CARE AND/OR RELATED RESEARCH (EXCEPT

KITCHEN AND RESTAURANT WASTES NOT ARISING FROM IMMEDIATE HEALTH CARE); wastes from natal care, diagnosis, treatment or prevention of disease in humans; chemicals

consisting of or containing hazardous substances; hazardous waste

Contaminated packaging

Completely emptied packings can be re-cycled.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number: UN1903

14.2. UN proper shipping name: DISINFECTANT, LIQUID, CORROSIVE, N.O.S. (Polyamines,

Didecylmethylammoniumpropionate, solution)

14.3. Transport hazard class(es): 8
14.4. Packing group: |||

Hazard label:

Classification code:

Special Provisions:

Limited quantity:

Transport category:

Hazard No:

Tunnel restriction code:

8

8

C9

C9

Special Provisions:

274

Limited quantity:

5 L

Transport category:

80

Tunnel restriction code:

Marine transport (IMDG)

14.1. UN number: UN1903

14.2. UN proper shipping name: DISINFECTANT, LIQUID, CORROSIVE, N.O.S. (POLYAMINES,

DIDECYLMETHYLAMMONIUMPROPIONATE, SOLUTION)

14.3. Transport hazard class(es): 8

14.4. Packing group:IIIHazard label:8Marine pollutant:no

Safety Data Sheet

according to Regulation (EC) No 1907/2006

STAMMOPUR DR 8

Revision date: 20.02.2018 No: 83005 Page 10 of 11

Special Provisions: 223, 274
Limited quantity: 5 L
EmS: F-A, S-B

Other applicable information (marine transport)

Excepted Quantity: E1

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number: UN1903

14.2. UN proper shipping name: DISINFECTANT, LIQUID, CORROSIVE, N.O.S. (POLYAMINES,

DIDECYLMETHYLAMMONIUMPROPIONATE, SOLUTION)

14.3. Transport hazard class(es):814.4. Packing group:IIIHazard label:8Special Provisions:A3 A803Limited quantity Passenger:1 L

IATA-packing instructions - Passenger:852IATA-max. quantity - Passenger:5 LIATA-packing instructions - Cargo:856IATA-max. quantity - Cargo:60 L

Other applicable information (air transport)

Excepted Quantity: E1 Passenger-LQ: Y841

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 55: 2-(2-butoxyethoxy)ethanol, diethylene glycol monobutyl ether

2004/42/EC (VOC): 35 % (357 g/l)

National regulatory information

Water contaminating class (D): 2 - clearly water contaminating

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Changes

Data changed from previous versions: 2.1., 3.2., 8.1., 11.1., 12.1., 12.2., 12.3., 13.1., 15.1., 16.

Relevant H and EUH statements (number and full text)

H301 Toxic if swallowed. H302 Harmful if swallowed.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.
H319 Causes serious eye irritation.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H336 May cause drowsiness or dizziness.

H361fd Suspected of damaging fertility. Suspected of damaging the unborn child. H373 May cause damage to organs through prolonged or repeated exposure.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.
H411 Toxic to aquatic life with long lasting effects.



according to Regulation (EC) No 1907/2006

STAMMOPUR DR 8

Revision date: 20.02.2018 No: 83005 Page 11 of 11

Further Information

Training instructions: Notice the directions for use on the label.

The information is based on present level of our knowledge. It does not, however, give assurances of product properties and establishes no contract legal rights.

Identified uses

No	Short title	LCS	SU	PC	PROC	ERC	AC	TF	Specification
1	STAMMOPUR DR 8	PW	-	0	8a, 9, 13	8a	0	121	

LCS: Life cycle stages
PC: Product categories
ERC: Environmental release categories

SU: Sectors of use PROC: Process categories AC: Article categories

TF: Technical functions

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)