

S a f e t y D a t a S h e e t According to Regulation (EC) 1907/2006 and (EU) 453/2010

1007 Acetone

1. Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Name: Acetone

Synonym:

2-Propanone, ÄŸ-Ketopropane, Dimethylketone, Pyroacetic Ether

CAS: [67-64-1]

REACH Registration Number: 01-2119471330-49-XXXX **1.2 Relevant identified uses of the substance or mixture:**

Production of the substance.

Distribution of Substance.

Mixing, preparation and repackaging.

Use as laboratory chemicals.

Use in coatings.

Use as binders and release agents.

Production and processing of Rubber.

Manufacture of polymers.

Polymer processing.

Blowing agents.

Mining chemicals.

Agrochemical use.

De-icing and anti-icing applications.

1.3 Identification of the company or firm:

PANREAC QUIMICA S.L.U.

C/Garraf 2

PolÃgono Pla de la Bruguera

E-08211 Castellar del VallA"s

(Barcelona) Spain

Tel. (+34) 937 489 400

e-mail: product.safety@panreac.com

1.4 Emergency telephone:

Single telephone number for emergency calls: 112 (EU)

Tel.: (+34) 937 489 499

2. Identification of dangers

2.1 Classification of the substance or the mixture.

Classification Regulation (CE) nº 1272/2008.

Flam. Liq. 2 Eye Irrit. 2 STOT SE 3

Classification (67/548/CEE or 1999/45/CE).

F Highly flammable R11
Xi Irritant R36
R66

2.2 Label elements:

Hazard Pictograms



Signal word Danger

Hazard statements

H225 Highly flammable liquid and vapour.

H319 Causes serious eve irritation.

EUH066 Repeated exposure may cause skin dryness or cracking.

H336 May cause drowsiness or dizziness.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P233 Keep container tightly closed.

P241 Use explosion-proof electrical/ventilating/lighting/equipment.

P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

P304+P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P501 Dispose of contents/container according to Directive 94/62/CE or 2008/98/CE.

For the full text of the R-phrases mentioned in this section, see section 16.

2.3 Other hazards:

No further relevant information available.

3. Composition/information on ingredients

Name: Acetone

Formula: CH3COCH3 M.= 58,08 CAS [67-64-1]

EC number (EINECS): 200-662-2 EC index number: 606-001-00-8

REACH Registration Number: 01-2119471330-49-XXXX

4. First aid measures

4.1 General indications:

Never provide drink or induce vomiting in the event of loss of consciousness.

4.2 Inhaling:

Take the person out into the fresh air. In the event of suffocation, proceed immediately to provide artificial respiration. Seek immediate medical assistance.

4.3 Contact with the skin:

Wash with plenty of soap and water. Remove contaminated clothing.

4.4 Eves:

Wash with plenty of water, keeping eyelids open. Seek medical assistance.

4.5 Swallowing:

Wash mouth out immediately. Drink large amounts of water. Do not induce vomiting. Seek immediate medical assistance.

· Most important symptoms and effects, both acute and delayed:

See Section 11 for more information.

$\hat{A}^{\boldsymbol{.}}$ Indication of any immediate medical attention and special treatment needed:

No further relevant information available.

5. Firefighting measures

5.1 Suitable extinguishing media:

Alcohol resistant foam. Dry powder.

5.2 Unsuitable extinguishing media:

Running water.

5.3 Special hazards arising from the substance or mixture:

Combustible. Keep away from sources of ignition. The fumes are heavier than air, so they may spread at floor level. Auf $R\tilde{A}^{1}_{4}ckz\tilde{A}^{1}_{4}ndung$ achten Risk of inflammation due to accumulation of electrostatic charges. In the event of fire, toxic fumes may form: CO y CO2.

5.4 Advice for firefighters:

Use complete protective equipment. Self-contained breathing equipment. Cool the recipients with water.

6. Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures:

Do not inhale the fumes. Protect the respiratory tracts. Ensure adequate ventilation. Use personal protective equipment as required. Evacuate all non-essential personnel. Avoid sources of ignition. Do not smoke.

6.2 Environmental precautions:

Do not allow it to enter the drainage system. Avoid pollution of the soil, water supplies and drains.

6.3 Methods and material for containment and cleaning up:

Collect up with absorbent materials (Panreac General Absorbent, Kieselguhr, etc.) or, if none available, dry sand or earth, and deposit in waste containers for subsequent elimination in accordance with current legislation. Clean any remains with plenty of water.

7. Handling and storage

7.1 Precautions for safe handling:

Avoid the formation of electrostatic charges. Ensure good ventilation and renewal of the air in the premises. Possible formation of pressure inside the container. Avoid breathing dust, fume, gas, mist, vapours or spray. Avoid contact with the skin, eyes or clothing. Use personal protective equipment as required.

7.2 Conditions for safe storage, including any incompatibilities:

Well sealed containers. In well ventilated premises. Away from sources of ignition and heat. Restricted access, only authorized to technicians.

Recommended storage temperature: Room temperature.

· Storage class: 3

Technical instructions (air): Highly flammable.

7.3 Specific end use(s):

No further relevant information available.

8. Exposure controls/personal protection

8.1 Exposure controls:

Ensure good ventilation and renewal of the air in the premises.

8.2 Control parameters:

VLA-ED: 500 ppm = 1.210 mg/m 3 ECTLV: 500 ppm = 1.210 mg/m 3

Derived No Effect Level (DNEL)

Workers Dermal, long exposure (local): 186mg/kg bw/24hWorkers Inhalation, acute (local): 2.420 mg/m3 Workers Inhalation, long term (local): 1.210 mg/m3 Population, oral, long term (systemic): 62mg/kg bw/24hPopulation, Dermal, long exposure (systemic): 62mg/kg bw/24hPopulation Inhalation, long term (systemic): 200 mg/m3

Predicted No Effect Concentration (PNEC)

Marine water: 1.06mg/lFreshwater: 10.6mg/lFreshwater Sediment: 30.4mg/lMarine water Sediment: 3.04mg/lSoil: 0.112mg/lSewage treatment plant: 29.5mg/l

8.3 Respiratory protection:

In the event of fumes forming/aerosols, use suitable respiratory protection. Filter AX. Filter P3.

8.4 Hand protection:

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

$\hat{A}\cdot$ For the permanent contact gloves made of the following materials are suitable:

Material: Butyl rubber. Recommended thickness of the material: >= 0.7 mm Breakthrough time: >= 480 min.

$\hat{A}\cdot$ As protection from splashes gloves made of the following materials are suitable:

Material: Natural rubber latex. Recommended thickness of the material: >= 0.7 mm Breakthrough time: >= 10 min.

8.5 Eye/face protection:

Use safety glasses.

8.6 Individual hygiene measures:

Remove contaminated clothing. Use suitable work clothing. Wash hands before breaks and when the job is done.

8.7 Environmental exposure controls:

Avoid pollution of the soil, water supplies and drains.

9. Physical and chemical properties

Appearance: liquid

Colour: N/A

Granulometry: N/A
Odour: Characteristic.

pH: N/A

Melting point/freezing point: -94 °C

Initial boiling point and boiling range: 56,5 °C

Flash point: - 20 ŰC Flammability (solid, gas):

NI/Δ

Upper/lower flammability or explosive limits: 12,8 %(V) / 2,2 %(V)

Vapour pressure: 233 hPa (20 ŰC)

Vapour density: N/A Relative density:

Insertar Aquà Grupo de repeticion

(20/4) 0,791 g/ml

Solubility: in water () () Miscible with water and most of the solvents

Partition coefficient: n-octanol/water:

N/A

Auto-ignition temperature: 465 ŰC

Decomposition temperature: N/A

Kinematic viscosity: N/A

Dynamic viscosity: 0,31 mPa.s (25 ŰC)

10. Stability and reactivity

10.1 Conditions to avoid:

High temperatures.

10.2 Incompatible materials:

Strong oxidant agents.

10.3 Hazardous decomposition products:

No specific data.

10.4 Chemical stability:

Exposure to light and air encourages the formation of peroxides. The gases/fumes can form explosive mixtures with the air.

11. Toxicological information

11.1 Acute toxicity:

LD50 oral rat : 5.800 mg/kg

11.2 Dangerous effects for health:

Skin corrosion/irritation: irritations, slight Serious eye damage/irritation: Strongly irritant in rabbits. Respiratory or skin sensitisation: Data not available. Germ cell mutagenicity: No evidence. Carcinogenicity: Data not available. Reproductive toxicity: Conclusions are lacking regarding evaluation of a damaging effect on the foetus. STOT- single exposure: narcosis STOT-repeated exposure: Data not available. Aspiration hazard: Data not available. ·Most important symptoms and effects acute: Irritations to the skin and eyes., Irritations of the mucosae in the mouth, throat, oesophagus and intestinal tract., drowsiness, vertigo, nausea, vomiting, headaches, effects on the central nervous system, Upon contact with the skin:, Can de-moisturize and dehydrate it, producing irritation and dermatitis.

12. Environmental information

12.1 Toxicity:

Acute toxicity for Algae:

(Ulva pertusa) EC50 20,565 mg/l (96h)

Acute toxicity for aquatic invertebrates:

(Gammarus pulex) LC50 6000000 ug/l (48h)

(Daphnia magna) LC50 10000 ug/l (48h)

Acute toxicity for fish:

(Pimephales Promelas) LC50 >100000 ug/l (96h)

Chronic toxicity for aquatic invertebrates:

(Daphnia magna) NOEC 0,1 mg/l (21d)

12.2 Persistence and Degradability:

Easily biodegradable product.

12.3 Bioaccumulative potential:

Low

12.4 Mobility in soil:

Product has a low potential for adsorption.

12.5 Assessment PBT and MPMB:

According to Annex XIII of Regulation (EC) No. 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH): Does not meet the criteria for PBT (persistent / bioaccumulative / toxic). According to Annex XIII of Regulation (EC) No. 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH): Does not meet the criteria vPvB (very persistent / very bioaccumulative).

12.6 Other adverse effects:

Environmental risks cannot be excluded if used and/or disposed of inappropriately.

12.7 General notes:

A. Water hazard class:

(German Regulation) (Assessment by list):

1 slightly hazardous for water.

(Dutch Regulation):

10 May cause long-term adverse effects in the aquatic environment.

13. Disposal considerations

13.1 Waste treatment methods:

In the European Union, there are no homogeneous standards established for elimination of chemical waste, which is waste of a special nature, and treatment and elimination of same is subject to the domestic legislation in each country. In view of this, in each case, you should contact the competent authority or those companies legally authorized for elimination of waste.

2001/573/EC: Council Decision of 23 July 2001 amending Commission Decision 2000/532/EC as regards the list of wastes. Council Directive 91/156/EEC of 18 March 1991 amending Directive 75/442/EEC on waste.

.

13.2 Contaminated containers:

Contaminated containers and packaging of dangerous substances or preparations must be treated in the same manner as the actual products contained in them. European Parliament and Council Directive 94/62/EC of 20 December 1994 on packaging and packaging waste.

•

14. Transport information

Overland (ADR):

Technical name: ACETONE

UN 1090 Class: 3 Packaging group: II (D/E)

By sea (IMDG):

Technical name: ACETONE

UN 1090 Class: 3 Packaging group: II

By air (ICAI-IATA): Technical name: Acetone

UN 1090 Class: 3 Packaging group: II Packaging instructions: CAO 364 PAX 353

15. Regulatory information

The substance is subject to Regulation (EC) No 273/2004 of the European Parliament and of the Council, of 11 February 2004 on drug precursors, Council Regulation (EC) No 111/2005 of 22 December 2004 laying down rules for the monitoring of trade between the Community and third countries in drug precursors, Commission Regulation (EC) No 1277/2005 of 27 July 2005 laying down implementing rules for Regulation (EC) No 273/2004 of the European Parliament and of the Council on drug precursors and for Council Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors. For this product a chemical safety assessment was carried out.

16. Other information

Other precautionary statements

P235 Keep cool.

Labelling (65/548/CEE or 1999/45/CE)

R-phrase(s): **R11** Highly flammable.

R36 Irritating to eyes.

R66 Repeated exposure may cause skin dryness

or cracking.

R67 Vapours may cause drowsiness and

dizziness.

S-phrase(s): **S9** Keep container in a well-ventilated place.

S16 Keep away from sources of ignition - No

smoking.

S26 In case of contact with eyes, rinse immediately with plenty of water and seek

medical advice.

S46 If swallowed, seek medical advice

immediately and show this container or lable.

Version and revision date: 5 07.10.2013

Remplaced: 15.09.2011

In respect of the previous review, changes have been made to the following

sections: 1,2,4,5,6,7,8,10,11,12,15

The information included in this Safety Data Sheet is based on our most up-to-date knowledge, and is solely intended to inform regarding aspects of safety; the properties and characteristics indicated herein are not guaranteed.