## KERN **EHA 500-2**



The compact all-round model with robust stainless steel weighing plate for use in laboratories, industries, and for teaching



Category	
Brand	KERN
Product categoriy	Laboratory balance
Product group	School balance
Product family	EHA

Measuring System	
Weighing system	Strain gauge
Weighing capacity [Max]	500 g
Readability [d]	0,01 g
Resolution	50.000
Linearity	± 0,03 g
Reproducibility	0,03 g
Tare range	500 g
Units	g gn dwt ct oz
Adjustment options	Adjusting with external weight
Recommended adjusting weight	200 g (F2); 500 g (F2)
Possible calibration points	200 g; 500 g
Stabilization time	3 s
Warm-up time	120 min
Eccentric loading at 1/3 [Max]	0,03 g
Default unit	g
Maximum creep (30 minutes)	80 mg
Construction type of the scale	Single-range balance
Maximum creep (15 minutes)	40 mg
Approval	

CE mark

Display	
Display type	LCD
Display backlight	✓
Display screen size	75×32 mm
Display segments	6
Display digit height	22 mm
Languages of the user interface	Symbol language

Construction	
Dimension housing (W×D×H)	225×160×50 mm
Material display housing	Plastics
Material housing	ABS plastic
Material weighing plate	stainless steel
Material platform	Plastics
Dimensions weighing surface (Ø)	105 mm
Material load cell(s)	aluminium
Load cells - number	1
Levelling feet adjustable	✓
Level indicator	✓

✓
50.000
10 mg
100 mg
5 min
manual (multi)
5

Power Supply	
Supplied power supply	Power supply & battery function (battery not included)
Plug-in power supply / adapter for countries - included with the delivery	EURO UK CH
Plug-in power supply / adapter for countries - optional	EURO UK CH
Input voltage device / power [Max]	9 V, 600 mA
Battery / accumulator type	Alkali(-Manganese)
Battery	2×1.5 V AA
Battery connection	Battery insert
Battery operating time	70 h

1

## KERN **EHA 500-2**



The compact all-round model with robust stainless steel weighing plate for use in laboratories, industries, and for teaching

Environmental conditions	
Ambient temperature [Min]	5 °C
Ambient temperature [Max]	40 °C
Humity of environment [Max]	80 %
Storage temperature [Min]	-20 °C
Storage temperature [Max]	60 °C

Packing & Shipping	
Delivery time	1 d
Dimensions packaging (W×D×H)	245×204×76 mm
Net weight	0,5 kg
Shipping method	Parcel service
Net weight approx.	0,50 kg
Gross weight approx.	0,75 kg
Shipping weight	0,8 kg

Services (optional)	
Article number for adjustment at the location of installation	961-247
Article number for DAkkS calibration	963-127
Article number for certificate of conformity (verification)	969-517

## Pictograms

## **STANDARD**















**OPTION** 

